

Submit 3 Copies To Appropriate District  
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.  
30-037-20031 20051

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Anna Katheryn

8. Well No.

1

9. Pool name or Wildcat  
Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator  
Prairie Sun, Inc.

3. Address of Operator 10713 RR 620 N., Bldg F Suite 621, Austin Tx 78726

4. Well Location

Unit Letter I : 660 feet from the West line and 1980 feet from the South line

Section 19 Township 10N Range 27E NMPM Quay County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
4365' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Drill 11" hole with 10# brine water to 3095'. Rig up and run 71 jts, 3116', 8 5/8" 24# & 32# J55 LT&C csg.  
Set 8 5/8" csg shoe at 3095'. Float collar at 3052'. Cement csg with 670 sx Lite cmt (65/35/6) + 1/4#/sx celloflake + 2% CaCl2, Yld 1.88 cu ft @ 12.8#/gal, Tail with 200 sx. Class C + 2% CaCl2., Yld--1.32 cu ft @ 14.6#/gal. Did not circulate cmt.

Plug down at 0230 hrs on 9/26/02.

Nipple up 11" 3000 psi WP Double Ram BOP. Install 8 5/8" slips, seal assembly and "B" section.

Test head, csg and BOP to 3000 psi--OK.

WOC for 18 hrs. Drill out with 7 7/8" bit at 0300 hrs on 9/27/02

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Gene Lee TITLE Agent DATE 10/5/02

Type or print name Gene Lee

Telephone No. (505) 622-7355

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 12/4/02  
Conditions of approval, if any