Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103	
District I	Energy, Minerals and Natural Resources		Revised March 25, 1999	
1625 N. French Dr., Hobbs, NM 87240 District II	OH COMBERNATION DUMOION		WELL API NO.	80-007-20479
811 South First, Artesia, NM 87210 District III	OIL CONSERVATION DIVISION		5. Indicate Type of	
1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St Frances Santa Fe, NM 87505		STATE C	
<u>District IV</u> 1220 South St Francis, Santa Fe, NM	Saita 1 0, 1414 0 / 505		6. State Oil & G	as Lease No.
87505 SUNDRY NOTI	CES AND REPORTS ON WELLS		7 Leosa Nama ar	Unit Agraement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			7. Lease Name or Unit Agreement Name:	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				VPR A
1. Type of We <u>ll:</u>				
Oil Well Gas Well Other X Coalbed Methane 2. Name of Operator			0 17/1131	133
EL PASO ENERGY RATON, L.L.C.			8. Well No.	123
3. Address of Operator			9. Pool name or W	Vildcat
P.O. Box 190, Raton, NM 87740 4. Well Location				
4. Well Education				
Unit Letter P: 1097 feet from the South line and 810 feet from the East line				
Section 20 Township 32N Range 19E NMPM Colfax County				
10. Elevation (Show whether DR, RKB, RT, GR, etc.)				
8595' (GL) 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF IN			Report or Other 1	
PERFORM REMEDIAL WORK		REMEDIAL WOR		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRI	LLING OPNS. 🌉	PLUG AND ABANDONMENT
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AN CEMENT JOB	ID 🗆	
OTHER:		OTHER:		
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
01/29/04 Spud in @ 9:45 p.m. Drill 11" surface hole to 365'. Ran 8 jts of 8 5/8", J-55, 24 ppf ST&C casing to 360'. Halliburton mixed and pumped 100 sks Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 110 psi with 6% salt, .3% gilsonite, .3% versaset, and 25# flocele per sack. Circulated 7 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 min.				
01/30/04 Drill 7 7/8" hole f/ 365' - 2905'. Reached TD at 2905'. MIRU Schlumberger & log well. Logger TD at 2867'. Ran 71 jts of 5 ½", 17#, J-55 LT &C casing to 2847'. Halliburton mixed and pump 40 bbls gel pre flush at 4 bpm at 25 psi, 399 sks Midcon II, 13.0 ppg, yield 2.04, .3% versaset, 5#/sx gilsonite, 2#/sk granulite, 6% salt and .1% Super CBL. Plug bumped w/ 1500 psi. Circulated 31 bbls of cement to surface. Well shut in.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Shirley Stritchell TITLE Senior Specialist DATE 02/05/04 Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785				
(This space for State use) APPPROVED BY Conditions of approval, if any:		ISTRICT SU		DATE 2/20/04