

Submit 1 Copy To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-007-20969
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name
8. Well Number A-579
9. OGRID Number 180514
10. Pool name or Wildcat Stubblefield Canyon Raton-Vermejo Gas
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 8449'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other CBM

2. Name of Operator
El Paso E&P Company, L.P.

3. Address of Operator
1001 Louisiana, Rm 2730D, Houston, Texas 77002

4. Well Location

Unit Letter L : 2163 feet from the South line and 958 feet from the West line
Section 28 Township 32N Range 19E NMPM 6th County Colfax

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
8449'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/12/11: Spudded @ 1245 hrs. Set conductor. Drilled 11" surface hole to 334'. Set 8 5/8", 24#, J-55, LT&C casing @ 324'. Pumped 10 bbls water, 20 bbls water with n-seal, barcarb, flozell, 10 bbls of water, and 29 bbls (100 sx) Trinidad blend cement. Displaced. 5 bbls of cement returned to pit. WOC.

03/13/11: WOC. Drilled and circulated out cement from 250' - 334'. Drilled 7 7/8" production hole to 2665'. Estimated top of Trinidad @ 2345'. C&C hole. Logged.

03/14/11: Washed & reamed hole. C&C hole. Logged. Ran 5 1/2", 15.5#, J-55, LT&C. Landed casing @ 2620'. ECP @ 2147' - 2158'. Released rig. Stage 1: Pumped 20 bbls of fresh water, pumped 20 gel water with flozell, barcarb, n-seal, 30 bbls fresh water. Cemented with 29 bbls (75 sx) Trinidad blend cement. Dropped plug on fly. Displaced. Bumped plug @ 1600 psi. Pressured to 2600 psi set ECP. Dropped bomb. Stage tool opened @ 1300 psi. Stage 2: Pumped 20 bbls fresh water, 200 bbls gel water. Got returns after 40 bbls pumped. Lost circulation after 160 bbls gel pumped. 120 bbls gel LCM pill, (got returns after 113 bbls pumped), w/n-seal, barcarb, flozell & 10 bbls fresh water. Cemented with 140 bbls (391 sx) Trinidad blend cement. Held returns though out job. 28 bbls cement returned to pit. Final lift 700 psi. Bumped plug @ 1969 psi. Plug held.

Spud Date:

03/12/11

Rig Release Date:

03/14/11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Maria S. Gomez

TITLE

Sr. Regulatory Analyst

DATE

05/23/11

Type or print name

Maria S. Gomez

E-mail address:

maria.gomez@elpaso.com

PHONE:

713-420-5038/832-683-0361

For State Use Only

APPROVED BY:

[Signature]

TITLE

DISTRICT SUPERVISOR

DATE

5/25/2011

Conditions of Approval (if any):