

1R - 426-215

# WORKPLANS

Date:

8-5-13

# Rice Environmental Consulting & Safety

---

P.O. Box 2948, Hobbs, NM 88241  
Phone 575.393.2967

CERTIFIED MAIL  
RETURN RECEIPT NO. 7007 2560 0000 4569 8227

**August 5<sup>th</sup>, 2013**

**Mr. Edward Hansen**  
New Mexico Energy, Minerals, & Natural Resources  
Oil Conservation Division, Environmental Bureau  
1220 S. St. Francis Drive  
Santa Fe, New Mexico 87505

RECEIVED OGD  
2013 AUG - 5 P 2:12

**RE: Investigation and Characterization Plan (ICP)  
Rice Operating Company – BD SWD System  
BD Jct. N-20 (1R426-215): UL/N sec. 20 T21S R37E**

Mr. Hansen:

RICE Operating Company (ROC) has retained Rice Environmental Consulting and Safety (RECS) to address potential environmental concerns at the above-referenced site in the BD Salt Water Disposal (SWD) system. ROC is the service provider (agent) for the BD SWD System and has no ownership of any portion of the pipeline, well, or facility. The system is owned by a consortium of oil producers, System Parties, who provide all operating capital on a percentage ownership/usage basis.

For all such environmental projects, ROC will choose the path forward that:

- Protects public health,
- Provides the greatest net environmental benefit,
- Complies with NMOCD Rules, and
- Is supported by good science.

Each site shall generally have three submissions:

1. This Investigation and Characterization Plan (ICP) is proposed for gathering data and site characterization and assessment.
2. Upon evaluating the data and results from the ICP, a recommended remedy will be submitted in a Corrective Action Plan (CAP), if warranted.
3. Finally, after implementing the remedy, a Termination Request with final documentation will be submitted.

## **Background and Previous Work**

The site is located approximately 2 miles northwest of Eunice, New Mexico at UL/N sec. 20 T21S R37E as shown on the Site Location Map (Figure 1). NM OSE records indicate that groundwater will likely be encountered at a depth of approximately 99 +/- feet.

In 2007, ROC initiated work on the former BD N-20 junction box. The site was delineated using a backhoe to form a 25 ft x 25 ft x 12 ft deep excavation and soil samples were screened at regular intervals for both hydrocarbons and chlorides. From the excavation, the four-wall composite, the bottom composite and the blended backfill were taken to a commercial laboratory for analysis. Laboratory tests of the four-wall composite showed a chloride reading of 1,070 mg/kg and a gasoline range organics (GRO) and a diesel range organics (DRO) reading of non-detect. The bottom composite showed a chloride laboratory reading of 2,000 mg/kg and a GRO and DRO reading of non-detect. The backfill sample showed a chloride laboratory reading of 944 mg/kg, a GRO reading of non-detect and a DRO reading of 10.1 mg/kg.

The excavated soil was blended on site and used to backfill the excavation to 6 ft bgs. At 6 – 5 ft bgs, a 1 ft thick clay layer was installed and properly seated into the excavation. The remaining blended soil was used to backfill the excavation to ground surface and contour it to the surrounding location. An identification plate was placed on the surface of the site to mark its location for future environmental considerations. The site was then needed with a blend of native vegetation. A new water-tight junction box was installed 25 ft north of the former junction box site.

To further delineate the site, two soil bores were installed on April 18<sup>th</sup>, 2007. SB-1 was installed at the source of the former junction box and SB-2 was installed 15 ft east of the former junction box. While the bores were being advance, samples were taken every 5 ft and field tested for chlorides and hydrocarbons. The deepest sample from each bore, located at 75 ft bgs, was taken to a commercial laboratory for analysis. SB-1 returned a laboratory chloride result of 624 mg/kg and SB-2 returned a laboratory chloride result of 752 mg/kg.

NMOCD was notified of potential groundwater impact on July 25<sup>th</sup>, 2008 and a junction box disclosure report (Appendix A) was submitted to NMOCD with all the 2008 junction box closures and disclosures.

ROC proposes additional investigative work at the site to determine if there is potential for groundwater degradation from residual chlorides at the site.

### **Proposed Work Elements**

1. Conduct vertical and lateral delineation of residual chlorides and hydrocarbons from samples taken using a drill rig, hand augur and/or backhoe (see Appendix B for Quality Procedures).
  - a. Vertical sampling will be conducted until of the following criteria are met in the field.
    - i. Three samples in which the chloride concentration decreases and the third sample has a chloride concentration of  $\leq 250$  ppm; and,
    - ii. Three samples in which PID readings decrease and the third sample has a PID reading of  $\leq 100$  ppm; or,
    - iii. The sampling reaches the capillary fringe.

- b. Lateral sampling will be conducted until the following criteria are met in the field.
  - i. A decrease is observed in chloride concentrations between lateral bores at similar depths; and,
  - ii. A chloride concentration of  $\leq 250$  ppm is observed in a lateral surface sample; or,
  - iii. Safety concerns impede further lateral delineation
2. If warranted, install a monitor well to provide direct measurement of the potential groundwater impact at the site. Additional monitoring wells may be required to fully delineate groundwater quality. (All monitor wells will be installed by EPA, NMOCD, and industry standards.)
3. Evaluate the risk of groundwater impact based on the information obtained.

If the evaluation of the site shows no threat to groundwater from residual chlorides, then only a vadose zone remedy will be undertaken. However, if groundwater shows impact from residual chlorides, a CAP will be developed to address these concerns.

RECS appreciates the opportunity to work with you on this project. Please call Hack Conder at (575) 393-2967 or me if you have any questions or wish to discuss the site.


Sincerely,



Lara Weinheimer  
Project Scientist  
RECS  
(575) 441-0431

Attachments:

- Figure 1 – Site Location Map
- Figure 2 – Geographical Location Map
- Appendix A – Junction Box Disclosure Report
- Appendix B – Quality Procedures



# Figures

**RICE Environmental Consulting and Safety (RECS)**  
P.O. Box 2948, Hobbs, NM 88241  
Phone 575.393.2967

# Site Location Map




## ***BD Jct. N-20***

**Legals: UL/N sec. 20  
T-21-S R-37-E  
LEA COUNTY, NM**

**NMOCD Case #: 1R426-215**

## **Figure 1**



Drawing date: 8/1/13  
Drafted by: L. Weinheimer

# Geographical Location Map




## ***BD Jct. N-20***


**Legals: UL/N sec. 20  
T-21-S R-37-E  
LEA COUNTY, NM**

**NMOCD Case #: 1R426-215**

## **Figure 2**



Drawing date: 8/1/13  
Drafted by: L. Weinheimer



# Appendix A

## Junction Box Disclosure Report

**RICE Environmental Consulting and Safety (RECS)**  
P.O. Box 2948 Hobbs, NM 88241  
Phone 575.393.2967

**RICE OPERATING COMPANY  
JUNCTION BOX DISCLOSURE\* REPORT**

**BOX LOCATION**

| SWD SYSTEM             | JUNCTION  | UNIT | SECTION | TOWNSHIP | RANGE | COUNTY | BOX DIMENSIONS - FEET |       |       |
|------------------------|-----------|------|---------|----------|-------|--------|-----------------------|-------|-------|
|                        |           |      |         |          |       |        | Length                | Width | Depth |
| Blinebry-Drinkard (BD) | Jct. N-20 | N    | 20      | 21S      | 37E   | Lea    | moved 25 ft north     |       |       |

LAND TYPE: BLM \_\_\_\_\_ STATE \_\_\_\_\_ FEE LANDOWNER \_\_\_\_\_ Millard Deck \_\_\_\_\_ OTHER \_\_\_\_\_

Depth to Groundwater \_\_\_\_\_ 99 \_\_\_\_\_ feet NMOCD SITE ASSESSMENT RANKING SCORE: \_\_\_\_\_ 20 \_\_\_\_\_

Date Started \_\_\_\_\_ 3/8/2007 \_\_\_\_\_ Date Completed \_\_\_\_\_ 4/18/2007 \_\_\_\_\_ OCD Witness \_\_\_\_\_ no \_\_\_\_\_

Soil Excavated \_\_\_\_\_ 277.8 \_\_\_\_\_ cubic yards Excavation Length \_\_\_\_\_ 25 \_\_\_\_\_ Width \_\_\_\_\_ 25 \_\_\_\_\_ Depth \_\_\_\_\_ 12 \_\_\_\_\_ feet

Soil Disposed \_\_\_\_\_ 0 \_\_\_\_\_ cubic yards Offsite Facility \_\_\_\_\_ n/a \_\_\_\_\_ Location \_\_\_\_\_ n/a \_\_\_\_\_

**FINAL ANALYTICAL RESULTS:** Sample Date \_\_\_\_\_ 3/14/2007, 3/15/2007, 4/18/2007 \_\_\_\_\_ Sample Depth \_\_\_\_\_ 12 ft, 75 ft \_\_\_\_\_

Procure 5-point composite sample of bottom and 4-point composite sample of sidewalls. TPH and Chloride laboratory test results completed by using an approved lab and testing procedures pursuant to NMOCD guidelines.

**CHLORIDE FIELD TESTS**

| Sample Location | PID (field) ppm | GRO mg/kg | DRO mg/kg | Chloride mg/kg |
|-----------------|-----------------|-----------|-----------|----------------|
| 4-WALL COMP.    | 0.0             | <10.0     | <10.0     | 1070           |
| BOTTOM COMP.    | 3.5             | <10.0     | <10.0     | 2000           |
| BACKFILL        | 5.5             | <10.0     | 10.1      | 944            |
| SOIL BORE #1    |                 |           |           | 624            |
| SOIL BORE #2    |                 |           |           | 752            |

| LOCATION   | DEPTH | mg/kg |
|--|-------|-------|
| 4-wall comp.                                     | n/a   | 1121  |
| bottom comp.                                     | 12'   | 1859  |
| backfill   | n/a   | 912   |
| vertical delineation trench at junction (source) | 2'    | 235   |
|  | 3'    | 291   |
|  | 4'    | 259   |
|  | 5'    | 477   |
|  | 6'    | 355   |
|  | 7'    | 1140  |
|  | 8'    | 1188  |
|  | 9'    | 1584  |
|  | 10'   | 1790  |
|  | 11'   | 1650  |
| 12'  | 1841  |       |

**General Description of Remedial Action:** This junction was addressed under the pipeline replacement/upgrade program. A new, watertight junction box was installed 25 ft north of the former. After the former box was removed, an investigation was conducted using a backhoe to collect soil samples at regular intervals producing a 25x25x12-ft-deep hole. Each sample was field tested for chlorides and organic vapors. Field chloride tests yielded elevated concentrations of chloride that did not relent with depth. Representative composite samples were sent to a commercial laboratory for analysis. The excavated soil was then blended on site and return to the excavation up to 6 ft below ground surface. At 6-5 ft BGS, a 1-ft-thick clay barrier was installed.

The remaining fill was used to backfill the excavation to ground surface and contour to the surrounding area. An identification plate was placed on the surface at the former junction site to mark the presence of the clay below. On 3/16/2007, the site was seeded with a blend of native vegetation and is expected to return to a productive capacity at a normal rate. To further investigate depth of chloride presence, two soil borings were initiated on 4/18/2007 at the former junction box site and 15 ft east of the former box site. Each boring was advanced to 75 ft BGS while soil samples were collected every 5 ft and tested for chloride concentrations. The deepest sample, 75 ft BGS, was sent to a commercial laboratory for analysis. Each bore hole was plugged with bentonite to ground surface. NMOCD was notified of potential groundwater impact on 7/25/2008.

**ADDITIONAL EVALUATION IS HIGH PRIORITY**

enclosures: photos, cross-section, lab results, PID screenings, tonng data, chloride graph

I HEREBY CERTIFY THAT THE INFORMATION ABOVE IS TRUE AND COMPLETE TO THE BEST OF MY KNOWLEDGE AND BELIEF.

SITE SUPERVISOR \_\_\_\_\_ Noel Carmona \_\_\_\_\_ SIGNATURE \_\_\_\_\_ COMPANY \_\_\_\_\_ RICE OPERATING COMPANY \_\_\_\_\_

REPORT ASSEMBLED BY \_\_\_\_\_ Katie Jones \_\_\_\_\_ INITIAL \_\_\_\_\_ KJ \_\_\_\_\_

PROJECT LEADER \_\_\_\_\_ Larry Bruce Baker Jr. \_\_\_\_\_ SIGNATURE \_\_\_\_\_ DATE \_\_\_\_\_ 1-21-09 \_\_\_\_\_

\*This site is a "DISCLOSURE." It will be placed on a prioritized list of similar sites for further consideration.

# BD Jct. N-20

Unit N, Section 20, T21S, R37E



excavation site, facing east

3/14/2007



backfilling excavation site up to 6 ft BGS, facing north

3/15/2007



backfilled site up to 6 ft BGS with new, watertight box in background

3/15/2007



clay barrier, facing east

3/15/2007

# BD Jct. N-20

Unit N, Section 20, T21S, R37E



site complete, prior to seeding with new, watertight box in background, facing north

3/16/2007



clay marker, facing north

3/16/2007



seeding backfilled site, facing south

3/16/2007




soil boring 15 ft east of former junction box, facing north

4/18/2007

# BD Jct. N-20


Unit N, Section 20, T21S, R37E

## Excavation Cross-Section



W


E





PHONE (325) 673-7001 • 2111 BEECHWOOD • ABILENE, TX 79603

PHONE (505) 393-7326 • 101 E. MARLAND • HOBBS, NM 88240



ANALYTICAL RESULTS FOR  
RICE OPERATING CO.  
ATTN: ROY R. RASCON  
122 W. TAYLOR  
HOBBS, NM 88240  
FAX TO: (505) 397-1471

Receiving Date: 03/15/07  
Reporting Date: 03/19/07  
Project Number: NOT GIVEN  
Project Name: B.D. JCT N-20  
Project Location: NOT GIVEN

Sampling Date: 03/14 & 03/15/07  
Sample Type: SOIL  
Sample Condition: COOL & INTACT  
Sample Received By: BC  
Analyzed By: BC/HM

**COPY**

| LAB NUMBER | SAMPLE ID                   | GRO   | DRO   | CI*      |
|------------|-----------------------------|---|---|----------|
|            |                             | (C <sub>6</sub> -C <sub>10</sub> )<br>(mg/Kg) | (>C <sub>10</sub> -C <sub>28</sub> )<br>(mg/Kg) | (mg/Kg)  |
|            | ANALYSIS DATE               | 03/15/07                                      | 03/15/07  | 03/18/07 |
| H12343-1   | BTTM. 5 PT. COMP. @ 12'     | <10.0   | <10.0   | 2000     |
| H12343-2   | 4 WALL COMP. @ 25'x25'      | <10.0   | <10.0   | 1070     |
| H12343-3   | BLENDED BACKFILL            | <10.0   | 10.1  | 944      |
|            | Quality Control             | 742   | 760   | 480      |
|            | True Value QC               | 800   | 800   | 500      |
|            | % Recovery                  | 92.8  | 95.0  | 96.0     |
|            | Relative Percent Difference | 2.5   | 1.7   | 4.1      |

METHODS TPH GRO & DRO: EPA SW-846 8015 M, CI: Std. Methods 4500-CI B

\*Analyses performed on 1:4 w/v aqueous extracts.

*Burges J. Cook*  
Chemist

*3/19/07*  
Date

H12343

PLEASE NOTE: **Liability and Damages** Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analysis. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of services hereunder by Cardinal, regardless of whether such claim is based upon any of the above-stated reasons or otherwise.





# ARDINAL LABORATORIES

PHONE (325) 673-7001 • 2111 BEECHWOOD • ABILENE, TX 79603  
PHONE (505) 393-2326 • 101 E. MARLAND • HOBBS, NM 88240

ANALYTICAL RESULTS FOR  
RICE OPERATING CO  
ATTN: ROY RASCON  
122 W TAYLOR  
HOBBS, NM 88240  
FAX TO (505) 397-1471

COPY

Receiving Date: 04/20/07  
Reporting Date: 04/20/07  
Project Number: NOT GIVEN  
Project Name: NOT GIVEN  
Project Location: BD N-20

Analysis Date: 04/20/07  
Sampling Date: 04/18/07  
Sample Type: SOIL  
Sample Condition: COOL & INTACT  
Sample Received By: BC  
Analyzed By: HM

| LAB NUMBER                  | SAMPLE ID                  | Cl <sup>-</sup><br>(mg/Kg) |
|-----------------------------|----------------------------|----------------------------|
| H12486-1                    | SB #1 @ 75' 15' E          | 624                        |
| H12486-2                    | SB #2 @ 75' at former jet. | 752                        |
|                             |                            |                            |
|                             |                            |                            |
|                             |                            |                            |
|                             |                            |                            |
| Quality Control             |                            | 480                        |
| True Value QC               |                            | 500                        |
| % Recovery                  |                            | 96                         |
| Relative Percent Difference |                            | 2.1                        |

METHOD: Standard Methods 4500-Cl<sup>-</sup>B

Note: Analyses performed on 1:4 w:v aqueous extracts

  
Chemist

04-20-07  
Date

H12486

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for any claim. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of services hereunder by Cardinal, regardless of whether such claim is based upon any of the above stated reasons or otherwise.



# CARDINAL LABORATORIES, INC.

2117 Beechwood, Abilene, TX 79603 101 East Marland, Hobbs, NM 88240  
 (325) 673-7001 Fax (325) 673-7020 (505) 393-2326 Fax (505) 393-2476

# COPY

## CHAIN-OF-CUSTODY AND ANALYSIS REQUEST

Page \_\_\_\_ of \_\_\_\_

|   |  |             |  |                  |  |  |  |  |  |
|---|--|-------------|--|------------------|--|--|--|--|--|
| Company Name: <u>Rice Operations CO.</u>              |  | BILL TO     |  | ANALYSIS REQUEST |  |  |  |  |  |
| Project Manager: <u>Roy Falcone</u>                   |  | P.O. #:     |  |                  |  |  |  |  |  |
| Address: <u>128 W TAYLOR</u>                          |  | Company:    |  |                  |  |  |  |  |  |
| City: <u>Hobbs</u> State: <u>NM</u> Zip: <u>88240</u> |  | Attn:       |  |                  |  |  |  |  |  |
| Phone #: <u>393-9174</u> Fax #: <u>397-1471</u>       |  | Address:    |  |                  |  |  |  |  |  |
| Project #:  |  | City:       |  |                  |  |  |  |  |  |
| Project Name:   |  | State: Zip: |  |                  |  |  |  |  |  |
| Project Location: <u>BD N-20</u>                      |  | Phone #:    |  |                  |  |  |  |  |  |
| Sample Name: <u>T. G.</u>                             |  | Fax #:      |  |                  |  |  |  |  |  |

| Lab I.D.        | Sample I.D.        | G/RAB OR CONTAINERS | MATRIX      |            |                                     |     |        |       | PRESERV.                            |            | SAMPLING       |              |                                     |
|-----------------|--------------------|---------------------|-------------|------------|-------------------------------------|-----|--------|-------|-------------------------------------|------------|----------------|--------------|-------------------------------------|
|                 |                    |                     | GROUNDWATER | WASTEWATER | SOIL                                | OIL | SLUDGE | OTHER | ACID/BASE                           | ICE / COOL | OTHER          | DATE         | TIME                                |
| <u>H12486-1</u> | <u>SB #1 @ 75'</u> | <u>G 1</u>          |             |            | <input checked="" type="checkbox"/> |     |        |       | <input checked="" type="checkbox"/> |            | <u>4-18-07</u> | <u>10:15</u> | <input checked="" type="checkbox"/> |
| <u>-2</u>       | <u>SB #2 @ 75'</u> | <u>G 1</u>          |             |            | <input checked="" type="checkbox"/> |     |        |       | <input checked="" type="checkbox"/> |            | <u>4-18-07</u> | <u>12:26</u> | <input checked="" type="checkbox"/> |

PLEASE NOTE: Agency and Manager herein's liability and client's recourse remedy for any claim arising whether based in contract or tort, shall be limited to the amount paid by the client for the analysis, all other monies including those for collection and any other costs whatsoever shall be deemed waived unless made in writing and provided by Cardinal within 30 days after completion of the applicable service. In no event shall Cardinal be liable for indirect or consequential damages, including without limitation, business interruption, loss of use, or loss of profits caused by other, its subsidiaries, affiliates or subcontractors and its failure to meet its obligations under this contract shall be deemed to be the sole responsibility of the client and its subcontractors. In the event of any dispute, the client shall be deemed to have agreed to the jurisdiction of the courts in the state of Texas and the county of Tarrant, Texas.

|  |                      |  |  |
|--|----------------------|--|--|
| Sampler Requested By: <u>John Brooks</u> | Date: <u>4-20-07</u> | Received By:                                   | Phone Result: <input type="checkbox"/> Yes <input type="checkbox"/> No |
|  | Time: <u>1145</u>    |  | Fax Result: <input type="checkbox"/> Yes <input type="checkbox"/> No   |
| Relinquished By:                         | Date:                | Received By: (Lab Staff) <u>Bryant A. Cook</u> | REMARKS: <u>E mail krascon@rice.SWD.com</u>                            |
|  | Time:                |  | <u># CC to J Purvis@rice.SWD.com</u>                                   |
| Delivered By: (Circle One)               | Sample Condition     | Temp °C  | Checked By: (Initials)   |
| Replaces UPS Bas - Other:                | <u>Cool</u>          | <u>5</u>                                       | <u>AK</u>  |

Cardinal cannot accept verbal changes. Please fax written changes to (325) 673-7020.

# RICE OPERATING COMPANY

122 West Taylor Hobbs, NM 88240  
 Phone: (505) 393-9174 Fax: (505) 397-1471

# COPY

## VOC FIELD TEST REPORT FORM

PID METER READING & CALIBRATION

CK.  MODEL: PGM 761S  
 MODEL  MODEL: PGM 7600  
 NO.  MODEL: PGM 7600  
 MODEL: PGM 7600

SERIAL NO: 104412  
 SERIAL NO: 110-013744  
 SERIAL NO: 110-12383  
 SERIAL NO: 110-012920

LOT NO: CS-2992  
 FILL DATE: 11-28-05  
 ACCURACY: +/- 2%

GAS COMPOSITION: ISOBUTYLENE 100PPM / AIR: BALANCE  
 EXP. DATE: 5-28-07  
 METER READING ACCURACY: 100.0

| SYSTEM | JUNCTION | UNIT | SECTION | TOWNSHIP | RANGE |
|--------|----------|------|---------|----------|-------|
| BD     | N-20     | N    | 20      | 215      | 37E   |

| SAMPLE        | PID Results | Sample        | PID Results |
|---------------|-------------|---------------|-------------|
| N. WALL 1     | 8.9         | E. WALL 1     | 1.2         |
| 2             | 3           | 2             | 0.5         |
| 3             | 0           | 3             | 0           |
| 4             | 0.3         | 4             | 3.1         |
| 5             | 0.3         | 5             | 0           |
| N. WALL Comp. | 0.8         | E. WALL Comp. | 6.1         |
| S. WALL 1     | 1.6         | W. WALL 1     | 0.9         |
| 2             | 0           | 2             | 1.5         |
| 3             | 2.2         | 3             | 1           |
| 4             | 8.2         | 4             | 0.7         |
| 5             | 0.3         | 5             | 0           |
| S. WALL Comp. | 10.4        | W. WALL Comp. | 3.3         |
| 4 WALL Comp.  | 0           |               |             |

I verify that I have calibrated the above instrument in accordance to the manufacture operation manual.

SIGNATURE: [Signature]

DATE: 3-14-07

# RICE OPERATING COMPANY

122 West Taylor Hobbs, NM 88240  
 Phone: (505) 393-9174 Fax: (505) 397-1471

COPY

## VOC FIELD TEST REPORT FORM

PID METER READING & CALIBRATION

CK.  
 MODEL  
 NO.

|                                     |
|-------------------------------------|
| <input type="checkbox"/>            |
| <input checked="" type="checkbox"/> |
| <input type="checkbox"/>            |
| <input type="checkbox"/>            |

MODEL: PGM 761S  
 MODEL: PGM 7600  
 MODEL: PGM 7600  
 MODEL: PGM 7600

SERIAL NO: 104412  
 SERIAL NO: 110-013744  
 SERIAL NO: 110-12383  
 SERIAL NO: 110-012920

LOT NO: 05-2992  
 FILL DATE: 5-28-05  
 ACCURACY: +/- 2%

GAS COMPOSITION: ISOBUTYLENE 100PPM / AIR: BALANCE

EXP. DATE: 5-28-07

METER READING ACCURACY: 100.0

| SYSTEM | JUNCTION | UNIT | SECTION | TOWNSHIP | RANGE |
|--------|----------|------|---------|----------|-------|
| BD     | N-20     | N    | 20      | 215      | 37E   |

| SAMPLE              | PID Results | Sample | PID Results |
|---------------------|-------------|--------|-------------|
| 5 FT BTM            | 3.5         |        |             |
| BTM                 | 1           | 1.9    |             |
|                     | 2           | 6.2    |             |
|                     | 3           | 3.5    |             |
|                     | 4           | 4.7    |             |
|                     | 5           | 3.9    |             |
| <del>BTM Comp</del> |             |        |             |
| Bleaded Backfill    | 5.5         |        |             |
|                     |             |        |             |
|                     |             |        |             |
|                     |             |        |             |
|                     |             |        |             |
|                     |             |        |             |

I verify that I have calibrated the above instrument in accordance to the manufacture operation manual.

SIGNATURE: 

DATE: 3-14-07





# CHLORIDE CONCENTRATION CURVE


RICE Operating Company

## BD Jct. N-20


unit 'N', Sec. 20, T21S, R37E

Backhoe samples at junction (source)

| Depth bgs (ft) | [Cl <sup>-</sup> ] ppm |
|----------------|------------------------|
| 2              | 235                    |
| 3              | 291                    |
| 4              | 259                    |
| 5              | 477                    |
| 6              | 355                    |
| 7              | 1140                   |
| 8              | 1188                   |
| 9              | 1584                   |
| 10             | 1790                   |
| 11             | 1650                   |
| 12             | 1841                   |



Groundwater = 99 ft



# Appendix B

Quality Procedures

**RICE Environmental Consulting and Safety (RECS)**  
P.O. Box 2948 Hobbs, NM 88241  
Phone 575.393.2967

# Rice Environmental Consulting and Safety

## Quality Procedures

### Table of Contents

- QP-1 Soil Samples for Transportation to a Laboratory
- QP-2 Chloride Titration Using 0.282 Normal Silver Nitrate Solution
- QP-3 Development of Cased Water-Monitoring Wells
- QP-4 Sampling of Cased Water-Monitoring Well
- QP-5 Composite Sampling of Excavation Sidewalls and Bottoms for TPH and Chloride Analysis
- QP-6 Sampling and Testing Protocol for VOC in soil
- QP-7 Composite Sampling of Excavation Sidewalls and Bottoms for BTEX
- QP-8 Procedure for Plugging and Abandonment of Cased Water-Monitoring wells

## **Rice Environmental Consulting and Safety**

---

### **Quality Procedure Soil Samples for Transportation to a Laboratory**

---

#### **1.0 Purpose**

This procedure outlines the methods to be employed when obtaining soil samples to be taken to a laboratory for analysis.

#### **2.0 Scope**

This procedure is to be used when collecting soil samples intended for ultimate transfer to a testing laboratory.

#### **3.0 Preliminary**

- 3.1 Obtain sterile sampling containers from the testing laboratory designated to conduct analyses of the soil.
- 3.2 If collecting TPH, BTEX, RCRA 8 metals, cation /anions or O&G, the sample jar may be a clear 4 oz. container with Teflon lid. If collecting PAH's, use an amber 4 oz. container.

#### **4.0 Chain of Custody**

- 4.1 Prepare a Sample Plan. The plan will list the number, location and designation of each planned sample and the individual tests to be performed on the sample. The sampler will check the list against the available inventory of appropriate sample collection bottles to insure against shortage.
- 4.2 Transfer the data to the Laboratory Chain of Custody Form. Complete all sections of the form except those that relate to the time of delivery of the samples to the laboratory.
- 4.3 Pre-label the sample collection jars. Include all requested information except time of collection. (Use a fine point Sharpie to insure that the ink remains on the label.) Affix the labels to the jars.

#### **5.0 Sampling Procedure**

- 5.1 Do not touch the soil with your bare hands. Use new nitrile gloves to help minimize any contamination.
- 5.2 Go to the sampling point with the sample container. If not analyzing for ions or metals, use a trowel to obtain the soil.

- 5.3 Pack the soil tightly into the container leaving the top slightly domed. Screw the lid down tightly. Enter the time of collection onto the sample collection jar label.
- 5.4 Place the sample directly on ice for transport to the laboratory if required.
- 5.5 Complete the Chain of Custody form to include the collection times for each sample. Deliver all samples to the laboratory.

## **6.0 Documentation**

- 6.1 The testing laboratory shall provide the following minimum information:
  - a. Project and sample name.
  - b. Signed copy of the original Chain of Custody Form including the time the sample was received by the lab.
  - c. Results of the requested analyses
  - d. Test Methods employed
  - e. Quality Control methods and results

## **Rice Environmental Consulting and Safety**

---

### QUALITY PROCEDURE Chloride Titration Using 0.282 Normal Silver Nitrate Solution

---

#### **1.0 Purpose**

This procedure is to be used to determine the concentration of chloride in soil.

#### **2.0 Scope**

This procedure is to be used as the standard field measurement for soil chloride concentrations.

#### **3.0 Sample Collection and Preparation**

3.1 Collect at least 80 grams of soil from the sample collection point. Take care to insure that the sample is representative of the general background to include visible concentrations of hydrocarbons and soil types. If necessary, prepare a composite sample for soils obtained at several points in the sample area. Take care to insure that no loose vegetation, rocks or liquids are included in the sample(s).

3.2 The soil sample(s) shall be immediately inserted into a one-quart or larger polyethylene freezer bag. Care should be taken to insure that no cross-contamination occurs between the soil sample and the collection tools or sample processing equipment.

3.3 The sealed sample bag should be massaged to break up any clods.

#### **4.0 Sample Preparation**

4.1 Tare a clean glass vial having a minimum 40 ml capacity. Add at least 10 grams of the soil sample and record the weight.

4.2 Add at least 20 grams of reverse osmosis water to the soil sample and shake well.

4.3 Allow the sample to set for a period of 5 minutes or until the separation of soil and water.

#### **5.0 Titration Procedure**

5.1 Using a graduated pipette, remove 10 ml extract and dispense into a clean plastic cup.

5.2 Add 2-3 drops potassium chromate ( $K_2CrO_4$ ) to mixture if necessary.

5.3 Using a 1 ml pipette, carefully add .282 normal silver nitrate (one drop at a time) to the sample while constantly agitating it. Stop adding silver nitrate when the solution begins to change from yellow to red. Be consistent with endpoint recognition.

5.4 Record the ml of silver nitrate used.

### 6.0 Calculation

To obtain the chloride concentration, insert measured data into the following formula:

$$\frac{.282 \times 35,450 \times \text{ml AgNO}_3}{\text{ml water extract}} \times \frac{\text{grams of water in mixture}}{\text{grams of soil in mixture}}$$

Using Step 5.0, determine the chloride concentration of the RO water used to mix with the soil sample. Record this concentration and subtract it from the formula results to find the net chloride in the soil sample.

Record all results on the delineation form.

---

## **Rice Environmental Consulting and Safety**

---

### **Quality Procedure Development of Cased Water-Monitoring Wells**

---

#### **1.0 Purpose**

This procedure outlines the methods to be employed to develop cased monitoring wells.

#### **2.0 Scope**

This procedure shall be used for developed, cased water monitoring wells. It is not to be used for standing water samples such as ponds or streams.

#### **3.0 Sample Collection and Preparation**

- 3.1 Prior to development, the static water level and height of the water column within the well casing will be measured with the use of an electric D.C. probe.
- 3.2 All measurements will be recorded within a field log notebook.
- 3.3 All equipment used to measure the static water level will be decontaminated after each use by means of Liquinox, a phosphate free laboratory detergent, and water to reduce the possibility of cross-contamination. The volume of water in each well casing will be calculated.

#### **4.0 Purging**

- 4.1 Wells will be purged by using a 2" decontaminated submersible pump or dedicated one liter Teflon bailer. Wells should be purged until the pH and conductivity are stabilized and the turbidity has been reduced to the greatest extent possible.
- 4.2 If a submersible is used the pump will be decontaminated prior to use by scrubbing the outside surface of tubing and wiring with a Liquinox water mixture, pumping a Liquinox-water mixture through the pump, and a final flush with fresh water.

#### **5.0 Water Disposal**

- 5.1 All purge and decontamination water will be temporarily stored within a portable tank to be later disposed of in an appropriate manner.

#### **6.0 Records**

- 6.1 Rice Environmental Consulting and Safety will record the amount of water removed from the well during development procedures. The purge volume will be reported to the appropriate regulatory authority when filing the closure report.

## **Rice Environmental Consulting and Safety**

---

### Quality Procedure Sampling of Cased Water-Monitoring Well

---

#### **1.0 Purpose**

This procedure outlines the methods to be employed in obtaining water samples from cased monitoring wells.

#### **2.0 Scope**

This procedure shall be used for developed, cased water monitoring wells. It is not to be used for standing water samples such as ponds or streams.

#### **3.0 Preliminary**

3.1 Obtain sterile sampling containers from the testing laboratory designated to conduct analyses of the water.

3.2 The following table shall be used to select the appropriate sampling container, preservative method and holding times for the various elements and compounds to be analyzed.

| <b>Compound to be Analyzed</b> | <b>Sample Container Size</b> | <b>Sample Container Description</b>   | <b>Cap Requirements</b> | <b>Preservative</b>  | <b>Maximum Hold Time</b> |
|--------------------------------|------------------------------|---------------------------------------|-------------------------|----------------------|--------------------------|
| BTEX                           | 40 ml                        | VOA Container                         | Teflon Lined            | HCL                  | 14 days                  |
| TPH (8015 Extended)            | 40 ounces                    | (2) 40ml VOA vials                    | Teflon Lined            | HCL and Ice          | 14 days                  |
| PAH                            | 1 liter                      | amber glass                           | Teflon Lined            | Ice                  | 7 days                   |
| Cation/Anion                   | 1 liter                      | HD polyethylene                       | Any Plastic             | None                 | 48 Hrs                   |
| Metals                         | 1 liter                      | HD polyethylene                       | Any Plastic             | Ice/HNO <sub>3</sub> | 28 Days                  |
| TDS                            | 300 ml                       | clear glass or 250 ml HD polyethylene | Any Plastic             | Ice                  | 7 Days                   |
| Cl-                            | 500 ml                       | HD polyethylene                       | Any Plastic             | None                 | 28 Days                  |

#### **4.0 Chain of Custody**

- 4.1 Prepare a Sample Plan. The plan will list the well identification and the individual tests to be performed at that location. The sampler will check the list against the available inventory of appropriate sample collection bottles to insure against shortage.
- 4.2 Transfer the data to the Laboratory Chain of Custody Form. Complete all sections of the form except those that relate to the time of delivery of the samples to the laboratory.
- 4.3 Pre-label the sample collection jars. Include all requested information except time of collection. (Use a fine point Sharpie to insure that the ink remains on the label). Affix the labels to the jars.

#### **5.0 Bailing Procedure**

- 5.1 Identify the well from the sites schematics. Place pre-labeled jar(s) next to the well. Remove the plastic cap from the well bore by first lifting the metal lever and then unscrewing the entire assembly.
- 5.2 Using a dedicated one liter Teflon bailer or submersible pump, purge a minimum of three well volumes. Place the water in storage container for transport to a ROC disposal facility.
- 5.3 If using a bailer, take care to insure that the bailing device and string does not become cross-contaminated. A clean pair of nitrile gloves should be used when handling either the retrieval string or bailer. The retrieval string should not be allowed to come into contact with the ground.

#### **6.0 Sampling Procedure**

- 6.1 Once the well has been bailed in accordance with 5.2 of this procedure, a sample may be decanted into the appropriate sample collection jar directly from the bailer or submersible pump.
- 6.2 Note the time of collection on the sample jar with a fine Sharpie.
- 6.3 Place the sample directly on ice for transport to the laboratory. The preceding table shows the maximum hold times between collection and testing for the various analyses.

6.4 Complete the Chain of Custody form to include the collection times for each sample. Deliver all samples to the laboratory.

## 7.0 Documentation

- 7.1 The testing laboratory shall provide the following minimum information:
- A. Project and sample name.
  - B. Signed copy of the original Chain of Custody Form including the time the sample was received by the lab.
  - C. Results of the requested analyses
  - D. Test Methods employed
  - E. Quality Control methods and results

### Calculation for Determining the Minimum Bailing Volume for Monitor Wells

$$\text{Formula } V = (\pi r^2 h)$$

$$2'' \text{ well } [V/231 = \text{gal}] \times 3 = \text{Purge Volume}$$

V=Volume

$\pi$ =pi

r=inside radius of the well bore

h=maximum height of well bore in water table

Example:

| $\pi$  | $r^2$ | h(in) | V(cu.in) | V(gal) | X 3 Volumes | Actual  |
|--------|-------|-------|----------|--------|-------------|---------|
| 3.1416 | 1     | 180   | 565.488  | 2.448  | 7.34 gal    | >10 gal |

---

## Rice Environmental Consulting and Safety

---

### Quality Procedure Composite Sampling of Excavation Sidewalls and Bottoms For TPH and Chloride Analysis

---

#### 1.0 Purpose

This procedure outlines the methods to be employed when obtaining final composite soil samples for TPH and Chloride analysis.

#### 2.0 Scope

This procedure is to be used in conjunction with *Quality Procedure – 02: Soil Samples for Transportation to a Laboratory* and will be inserted at subparagraph 5.2 of Section 5.0: Sampling Procedure.


#### 3.0 Sampling Procedure

Follow *Quality Procedure – 02: Soil Samples for Transportation to a Laboratory* for all Sections and subparagraphs until subparagraph 5.2 of Section 5.0: Sampling Procedure. Instead of 5.2 instructions, perform the composite sample collection procedure as follows:

3.1 Go to the excavation with a new plastic baggie. If not analyzing for ions or metals, use a trowel to obtain the soil. If the excavation is deeper than 6' BGS, do not enter the pit, but use a backhoe to assist in procurement of the sample. (If a backhoe is used, the backhoe will obtain an amount of soil from each composite point; bring the purchase to the surface staging area where a sample-portion of soil will be extracted from the backhoe purchase. The remainder of the backhoe purchase will be staged on the surface with other staged soils.)

#### 3.2 Sidewall samples

3.2.1 On each sidewall, procure a 5oz sample from each of five distinct points on the sidewall with distinct points resembling the "W" pattern:



- 3.2.2 Thoroughly blend these five samples in a labeled baggie.
- 3.2.3 Repeat steps 3.2.1 through 3.2.4 for each remaining sidewall.
- 3.2.4 From each labeled baggie, procure a 5 oz portion and pour into a baggie labeled "Sidewall Composite". Blend this soil mixture completely.
- 3.2.5 Obtain proper laboratory sample container for "Sidewall Composite" and continue with subparagraph 5.3 of QP – 01.

### 3.3 Bottom Sample

- 3.3.1 From bottom of excavation, procure a 5oz sample from each of five distinct points with distinct points resembling the "W" pattern as illustrated above.
- 3.3.2 Thoroughly blend these five samples in a clean baggie.
- 3.3.3 Obtain proper laboratory sample container for "Bottom Composite" and continue with subparagraph 5.3 of QP – 01.

## Rice Environmental Consulting and Safety

---

### QUALITY PROCEDURE

#### Sampling and Testing Protocol for VOC in Soil

---

#### 1.0 Purpose

This procedure is to be used to determine the concentrations of Volatile Organic Compounds in soils.

#### 2.0 Scope

This procedure is to be used as the standard field measurement for soil VOC concentrations. It is not to be used as a substitute for full spectrographic speciation of organic compounds.

#### 3.0 Procedure

##### 3.1 Sample Collection and Preparation

3.1.1 Collect at least 500 g. of soil from the sample collection point. Take care to insure that the sample is representative of the general background to include visible concentrations of hydrocarbons and soil types. If necessary, prepare a composite sample of soils obtained at several points in the sample area. Take care to insure that no loose vegetation, rocks or liquids are included in the sample(s).

3.1.2 The soil sample(s) shall be immediately inserted into a one-quart or larger polyethylene freezer bag and sealed. When sealed, the bag should contain a nearly equal space between the soil sample and trapped air. Record the sample name and the time that the sample was collected on the Field Analytical Report Form.

3.1.3 The sealed samples shall be allowed to set for a minimum of five minutes at a temperature of between 10-15 Celsius, (59-77<sup>0</sup> F). The sample temperatures may be adjusted by cooling the sample in ice, or by heating the sample within a generally controlled environment such as the inside of a vehicle. The samples should not be placed directly on heated surfaces or placed in direct heat sources such as lamps or heater vents.

3.1.4 The sealed sample bag should be massaged to break up any clods, and to provide the soil sample with as much exposed surface area as practically possible.

### 3.2 Sampling Procedure

3.2.1 The instrument to be used in conducting VOC concentration testing shall be a RAE Systems Photoionization device. (Device will be identified on VOC Field Test Report Form.) Prior to use, the instrument shall be zeroed-out in accordance with the appropriate maintenance and calibration procedure outlined in the instrument operation manual. The PID device will be calibrated each day it's used.

3.2.2 Carefully open one end of the collection bag and insert the probe tip into the bag taking care that the probe tip not touch the soil sample or the sidewalls of the bag.

3.2.3 Set the instrument to retain the highest result reading value. Record the reading onto the Field Test Report Form.

**3.2.4 If the instrument provides a reading exceeding 100 ppm, proceed to QP-7. If the reading is 100 ppm or less, NMOCD BTEX guideline has been met and no further testing for BTEX is necessary. File the Field Test Report Form in the project file.**

### 4.0 Clean-up

After testing, the soil samples shall be returned to the sampling location, and the bags collected for off-site disposal. **IN NO CASE SHALL THE SAME BAG BE USED TWICE. EACH SAMPLE CONTAINER MUST BE DISCARDED AFTER EACH USE.**

---

## Rice Environmental Consulting and Safety

---

### Quality Procedure Composite Sampling of Excavation Sidewalls and Bottoms For BTEX

---

#### 1.0 Purpose

This procedure outlines the methods to be employed when obtaining final composite soil samples for BTEX analysis.

#### 2.0 Scope

This procedure is to be used when collecting soil samples intended for ultimate transfer to a testing laboratory for BTEX analysis. This procedure is to be used only when the PID field-test results for OVM exceeds 100 ppm.

#### 3.0 Preliminary

3.1 Obtain sterile, clear, 2 oz. glass containers with Teflon lid from a laboratory supply company or the testing laboratory designated to conduct analyses of the soil.

#### 4.0 Chain of Custody

- 4.1 Prepare a Sample Plan. The plan will list the number, location and designation of each planned sample and the individual tests to be performed on the sample. The sampler will check the list against the available inventory of appropriate sample collection bottles to insure against shortage.
- 4.2 Transfer the data to the Laboratory Chain of Custody Form. Complete all sections of the form except those that relate to the time of delivery of the samples to the laboratory.
- 4.3 Pre-label the sample collection jars. Include all requested information except time of collection. (Use a fine point Sharpie to insure that the ink remains on the label.) Affix the labels to the jars.


#### 5.0 Sampling Procedure

- 5.1. Do not touch the soil with your bare hands. Use new nitrile gloves to help minimize any cross-contamination.
- 5.2. If safe and within OSHA regulations, go to the sampling point with the sample container. If not analyzing for ions or metals, use a trowel to

obtain the soil. If the excavation is deeper than 6' BGS, do not enter the pit, but use a backhoe to assist in procurement of the sample. (If a backhoe is used, the backhoe will obtain an amount of soil from each composite point; bring the purchase to the surface staging area where a sample-portion of soil will be extracted from the backhoe purchase. The remainder of the backhoe purchase will be staged on the surface with other staged soils.)

### 5.3. Sidewall Samples

5.3.1. On each sidewall, procure a 2oz sample from each of five distinct points on the sidewall with distinct points resembling the "W" pattern:



5.4. Pack the soil tightly into the container leaving the top slightly domed. Screw the lid down tightly. Enter the time of collection onto the sample collection jar label. Repeat for each sampling point.

5.5. Place the samples directly on ice for transport to the laboratory if required.

5.6. Complete the Chain of Custody form to include the collection times for each sample. Deliver all samples to the laboratory.

## 6.0 Documentation

6.1 The testing laboratory shall provide the following minimum information:

- a. Project and sample name.
- b. Signed copy of the original Chain of Custody Form including the time the sample was received by the lab.
- c. Results of the requested analyses
- d. Test Methods employed
- e. Quality Control methods and results

## **Rice Environmental Consulting and Safety**

---

### **Procedure for Plugging & Abandonment of Cased Water Monitoring Wells**

---

#### **1.0 Purpose**

This procedure outlines the methods to be employed to plug and abandon cased monitoring wells.

#### **2.0 Scope**

This procedure shall be used for developed, cased water monitoring wells located in the State of New Mexico

#### **3.0 Preliminary**

**3.1** No well may be drilled, modified or plugged without NMOCD approval. Additional approvals may be required if the well is situated in a sensitive area, within municipal jurisdictions or on federal or tribal lands.

#### **4.0 Plugging**

**4.1** Each bore will be filled with a 1% - 3% bentonite/concrete slurry to three feet bgs. The remaining three feet will be capped with concrete only.

**4.2** All wellheads will be removed to below ground surface.

#### **5.0 Records**

**5.1** The company plugging the well shall prepare a report on their company letter head listing the site name and describing general well construction including total depth of the well, the diameter of casing, material used to plug the well (e.g. bentonite/cement slurry), and date of the plugging operation.

**5.2** It is recommended but not required that photographs of the final surface restoration be taken and included within the records.

**5.3** Copies of the plugging report shall be submitted to all appropriate agencies and retained by the well operator for a minimum period of ten years.