# State of New Mexico Energy, Minerals and Natural Resources Department

Susana Martinez Governor

David Martin
Cabinet Secretary

Brett F. Woods, Ph.D. Deputy Cabinet Secretary Jami Bailey, Division Director Oil Conservation Division



Administrative Order SWD-1512 December 16, 2014

## ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Pursuant to the provisions of Division Rule 19.15.26.8B. NMAC, Sahara Operating Company (the "operator") seeks an administrative order for its Monument 1 State SWD Well No. 26 with a location of 2279 feet from the South line and 2276 feet from the East line, Unit letter J of Section 1, Township 19 South, Range 36 East, NMPM, Lea County, New Mexico, for produced water disposal purposes.

#### THE DIVISION DIRECTOR FINDS THAT:

The application has been duly filed under the provisions of Division Rule 19.15.26.8B. NMAC and satisfactory information has been provided that affected parties as defined in said rule have been notified and no objections have been received within the prescribed waiting period. The applicant has presented satisfactory evidence that all requirements prescribed in Rule 19.15.26.8 NMAC have been met and the operator is in compliance with Rule 19.15.5.9 NMAC.

### IT IS THEREFORE ORDERED THAT:

The applicant, Sahara Operating Company (OGRID 20077) is hereby authorized to utilize its Monument 1 State SWD Well No. 26 (API 30-025-34477) located 2279 feet from the South line and 2276 feet from the East line, Unit letter J of Section 1, Township 19 South, Range 36 East, NMPM, Lea County, New Mexico, for disposal of oil field produced water (UIC Class II only) through perforations within the Bone Spring formation (or other Permian-aged rocks) from 5400 feet to 6050 feet. Injection shall occur through internally-coated tubing and a packer set a maximum of 100 feet above the top of the perforated disposal interval.

Prior to perforating for disposal, the operator shall install an additional CIBP and cement at approximately 6250 feet.

During completion operations, the operator shall perforate the Bone Spring formation below depths of 5624 feet and swab test this Bone Spring interval for hydrocarbon productivity. If productive, this well shall be either produced or those perforations squeezed prior to perforating up hole for disposal. If not productive below 5624 feet, the operator may include perforations up to 5400 feet and utilize the entire permitted interval for disposal.

#### IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the disposed water enters only the approved disposal interval and is not permitted to escape to other formations or onto the surface. This includes the well construction proposed and described in the application.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The well shall pass an initial mechanical integrity test ("MIT") prior to initially commencing disposal and prior to resuming disposal each time the disposal packer is unseated. All MIT procedures and schedules shall follow the requirements in Division Rule 19.15.26.11A. NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in this well.

The wellhead injection pressure on the well shall be limited to **no more than 1080 psi**. In addition, the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressure to the maximum allowable pressure for this well. If requested by the Division's District office, the operator shall install and maintain a chart recorder showing casing and tubing pressures.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formation. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable Step-Rate Test.

The operator shall notify the supervisor of the Division's District office of the date and time of the installation of disposal equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of disposal to the Division's District office. The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Division Rules 19.15.26.13 and 19.15.7.24 NMAC.

Without limitation on the duties of the operator as provided in Division Rules 19.15.29 and 19.15.30 NMAC, or otherwise, the operator shall immediately notify the Division's District office of any failure of the tubing, casing or packer in the well, or of any leakage or release of water, oil or gas from around any produced or plugged and abandoned well in the area, and shall take such measures as may be timely and necessary to correct such failure or leakage.

The injection authority granted under this order is not transferable except upon Division approval. The Division may require the operator to demonstrate mechanical integrity of any disposal well that will be transferred prior to approving transfer of authority to inject.

The Division may revoke this injection permit after notice and hearing if the operator is in violation of Rule 19.15.5.9 NMAC.

The disposal authority granted herein shall terminate two (2) years after the effective date of this order if the operator has not commenced injection operations into the subject well. One year after the last date of reported disposal into this well, the Division shall consider the well abandoned, and the authority to dispose will terminate ipso facto. The Division, upon written request mailed by the operator prior to the termination date, may grant an extension thereof for good cause.

Compliance with this order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.

Director

JB/prg

cc:

Oil Conservation Division - Hobbs District Office New Mexico State Land Office - Oil, Gas, and Minerals Division