NM OIL CONSERVATION

ARTESIA DISTRICT

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

FEB 1.5 201/

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in RECEIVE Coordance with 19.15.29 NMAC.

Release Notification and Corrective Action OPERATOR ☐ Initial Report Final Report WPX Energy Inc/RKI AUIDAS Name of Company Contact Karolina Blaney 5315 Buena Vista Dr. Address Telephone No. 970 589 0743 Facility Name: McKitrick 29-22 Facility Type: Well Pad Surface Owner: Private Mineral Owner: Federal API No. 30- 015-29351 LOCATION OF RELEASE Unit Letter Section Feet from the North/South Line Feet from the East/West Line Township Range County 29 1715 1160 **FWL** E **22S** 26E **FNL** Eddy **Latitude: 32.01139288N Longitude: -103.86641694W** NATURE OF RELEASE Volume of Release: 32 Bbls Type of Release. Oil Volume Recovered: 0 Bbls Source of Release Date and Hour of Occurrence Date and Hour of Discovery Tank 1/30/2017 1/30/2017 - 11:30 hrs MT Was Immediate Notice Given? If YES, To Whom? ☑ Yes □ No □ Not Required NMOCD Crystal Weaver & Michael Bratcher, BLM Shelly Tucker Date and Hour: 2/1/17 - 6:50 hrs MT By Whom? Karolina Blaney Was a Watercourse Reached? If YES, Volume Impacting the Watercourse. ☐ Yes ⊠ No N/A If a Watercourse was Impacted, Describe Fully.* N/A Describe Cause of Problem and Remedial Action Taken.* The spill was caused by equipment failure; corroded hole in the oil tank. Approximately 32 bbls of oil leaked out of the tank into a dirt SPCC containment. Less than 0.5 bbl saturated the berm and stained a small area outside the berm. The spill did not migrate off location. Describe Area Affected and Cleanup Action Taken.* The impacted area was mapped with a Trimble. The impacted soil was field screened for hydrocarbons and exceeded the cleanup thresholds of 5,000 ppm at 10" below surface. The delineation plan for the hydrocarbon and chloride impacts will be sent to BLM and OCD within 30 days of this submittal. I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations. OIL CONSERVATION DIVISION Kambina Blancy Signature: Approved by Environmental Specialist Printed Name: Karolina Blaney Approval Date **Expiration Date:** Title: Environmental Specialist Conditions of Approval: E-mail Address: Karolina.blaney@wpxenergy.com Attached

* Attach Additional Sheets If Necessary

Date: 2/15/2016

Phone: 970-589-0743

2RP-4121

Operator/Responsible Party,

The OCD has received the form C-141 you provided on ________ regarding an unauthorized release. The information contained on that form has been entered into our incident database and remediation case number _________ has been assigned. Please refer to this case number in all future correspondence.

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete <u>division-approved corrective action</u> for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District $\frac{2}{\sqrt{2}}$ office in $\frac{2}{\sqrt{2}}$ on or before $\frac{3}{\sqrt{2}}$. If and when the release characterization workplan is approved, there will be an associated deadline for submittal of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

- Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.
- Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.
- Nominal detection limits for field and laboratory analyses must be provided.
- Composite sampling is not generally allowed.
- Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

- •Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.
- If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method 8260 full list), total dissolved solids, pH, major anions and cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.
- Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold
OCD Environmental Bureau Chief
1220 South St. Francis Drive
Santa Fe, New Mexico 87505
505-476-3465
jim.griswold@state.nm.us

Bratcher, Mike, EMNRD

From: Blaney, Karolina < Karolina.Blaney@wpxenergy.com >

Sent: Wednesday, February 15, 2017 3:51 PM

To: Bratcher, Mike, EMNRD; 'stucker@blm.gov'; Weaver, Crystal, EMNRD

Subject: RE: WPX McKittrick 29-22 - initial spill notification

Attachments: McKittrick 29-22 - C-141.doc

Good afternoon,

Attached is the initial C-141 for the McKittrick 29-22 spill. Please let me know if you have any questions or concerns. Thank you,

Karolina Blaney

Environmental Specialist WPX Energy Office: (575) 885-7514

Cell: (970) 589-0743

karolina.blaney@wpxenergy.com

From: Blaney, Karolina

Sent: Wednesday, February 01, 2017 6:50 AM

To: 'Bratcher, Mike, EMNRD' <mike.bratcher@state.nm.us>; 'stucker@blm.gov' <stucker@blm.gov>; 'Weaver, Crystal,

EMNRD' < Crystal. Weaver@state.nm.us>

Subject: WPX McKittrick 29-22 - initial spill notification

Good morning,

WPX had a spill yesterday, 1/30/17, at the Mckittrick 29 Federal com 22; API 30-015-29351; E-29-22S-26E. The spill was caused by equipment failure - hole in the oil tank. Approximately 32 bbls of oil leaked out of the tank into a dirt SPCC containment. Less than 0.5 bbl saturated the berm and stained a small area outside the berm. The spill did not migrate off location.

The C-141 report will be submitted in the next 15 days.

Thank you and have a great day

Karolina Blaney

Environmental Specialist WPX Energy Office: (575) 885-7514

Cell: (970) 589-0743

karolina.blaney@wpxenergy.com

Bratcher, Mike, EMNRD

From: Blaney, Karolina < Karolina.Blaney@wpxenergy.com>

Sent: Wednesday, February 1, 2017 6:51 AM

To: Bratcher, Mike, EMNRD; 'stucker@blm.gov'; Weaver, Crystal, EMNRD

Subject: WPX McKittrick 29-22 - initial spill notification

Good morning,

WPX had a spill yesterday, 1/30/17, at the Mckittrick 29 Federal com 22; API 30-015-29351; E-29-22S-26E. The spill was caused by equipment failure - hole in the oil tank. Approximately 32 bbls of oil leaked out of the tank into a dirt SPCC containment. Less than 0.5 bbl saturated the berm and stained a small area outside the berm. The spill did not migrate off location.

The C-141 report will be submitted in the next 15 days.

Thank you and have a great day

Karolina Blaney

Environmental Specialist WPX Energy

Office: (575) 885-7514 Cell: (970) 589-0743

karolina.blaney@wpxenergy.com