ARTESIA DISTRICT District I 1625 N. French Dr., Hobbs, NM 88240 State of New Mexico MAY 2 3 2017 Form C-141 **Energy Minerals and Natural Resources** Revised August 8, 2011 District II 811 S. First St., Artesia, NM 88210 Submit 1 Copy to appropriate District Office in **RECEIVE** Daccordance with 19.15.29 NMAC. **District III Oil Conservation Division** 1000 Rio Brazos Road, Aztec, NM 87410 1220 South St. Francis Dr. **District IV** 1220 S. St. Francis Dr., Santa Fe, NM 87505 Santa Fe, NM 87505 **Release Notification and Corrective Action** 817146507 **OPERATOR** Initial Report Final Report Name of Company OGRID Number Contact New forms can be found in the EOG Y Resources, Inc. 25575 Robert Asher New Mexico State Website in forms: Address Telephone No. 104 S. 4th Street 575-748-1471 http://www.emnrd.state.nm.us/ Facility Name Facility Type OCD/forms.html Voight AJD Com Battery Battery Mineral Owner Surface Owner API No. Fee Fee LOCATION OF RELEASE Township North/South Line Unit Letter Section Feet from the Feet from the East/West Line County Range D 29 19S 25Ē 660 North 660 West Eddv Latitude 32.63719 Longitude 104.51278 NATURE OF RELEASE Volume Recovered Type of Release Volume of Release Produced Water 15 B/PW 5 BPW Source of Release Date and Hour of Occurrence Date and Hour of Discovery Poly to steel transition 5/3/2017; AM 5/3/2017; AM Was Immediate Notice Given? If YES, To Whom? Yes No X Not Required NA By Whom? Date and Hour NA NA Was a Watercourse Reached? If YES, Volume Impacting the Watercourse. 🗌 Yes 🛛 No If a Watercourse was Impacted, Describe Fully.* Describe Cause of Problem and Remedial Action Taken.* A poly to steel transition came apart on the discharge side of the pump (pump not running) causing the release. Closed valves to isolate the leak, vacuum truck(s) and roustabout crews were called. Describe Area Affected and Cleanup Action Taken.* An approximate area of 5' X 75', south edge of battery. Remaining produced water was recovered using a vacuum truck. Roustabout crew repaired the line, a backhoe scraped approximately 12" of impacted soils, hauled to an approved NMOCD facility. Vertical and horizontal delineation samples will be taken and analysis ran for TPH & BTEX. If initial analytical results for TPH & BTEX are under RRAL's (site ranking is 0) a Final Report, C-141 will be submitted to the OCD requesting closure. If the analytical results are above the RRAL's a work plan will be submitted to the OCD. Depth to Ground Water>100' (approximately 222', Section 30, T19S-R25E per NMOSE), Wellhead Protection Area: No, Distance to Surface Water Body: >1000', SITE RANKING IS 0 I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations. OIL CONSERVATION DIVISION Signature: Approved by Environmented Specialist Printed Name: Robert Asher NIA Approval Date: 5 Expiration Date: Title: Environmental Supervisor E-mail Address: Robert Asher@eogresources.com Conditions of Approval: Attached See attached Date: May 23, 2017 Phone: 575-748-4217 2RP-)RP-4226

Attach Additional Sheets If Necessary

NM

OIL	. C	0	N	IS	ER	VA	TI	ÔN
								~ • • •

Operator/Responsible Party,

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete <u>division-approved corrective action</u> for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District 2 office in <u>ARTESIA</u> on or before <u>6/23/2017</u>. If and when the release characterization workplan is approved, there will be an associated deadline for submittal of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

• Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.

• Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.

• Nominal detection limits for field and laboratory analyses must be provided.

• Composite sampling is not generally allowed.

• Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

•Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.

• If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method 8260 full list), total dissolved solids, pH, major anions and cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.

• Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold OCD Environmental Bureau Chief 1220 South St. Francis Drive Santa Fe, New Mexico 87505 505-476-3465 jim.griswold@state.nm.us

Bratcher, Mike, EMNRD

From:Bob Asher <Bob_Asher@eogresources.com>Sent:Tuesday, May 23, 2017 10:20 AMTo:Bratcher, Mike, EMNRDCc:Weaver, Crystal, EMNRDSubject:Form C-141 Initial Report (Voight ADJ Com Battery)Attachments:Form C-141 Initial (Voight ADJ Com Battery).pdf

Thank you,

Robert C. "Bob" Asher

Environmental Supervisor Safety & Environmental Department EOG Resources, Inc. Artesia Division Artesia, NM 88210 575-748-4217 (Office) 575-365-4021 (Cell) EOG Safety Begins With YOUR Safety

