NM OIL CONSEIVATION

ARTESTA DISTRICT

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

JAN 08 2018

Form C-141 Revised April 3, 2017

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Submit 1 Copy to appropriate District Office in RECEI WEAD ance with 19.15.29 NMAC.

Release Notification and Corrective Action													
NAB1800954389							ГOR		✓ Initia	ıl Report		Final Report	
Name of Co		OXY USA					VADE DITTRIC						
Address I Facility Nar		294; HOUS' ERNMENT		77210	Telephone Nacility Typ								
Surface Owner FEDERAL Mineral Owner FEDERAL API No. 30-015-27964													
Unit Letter Section Township Range Feet from the North/South Line Feet from the East/West Line County												· ·	
			•	i cet nom the	Non	South Line	rect nom the	Last v	CSI LINC		•		
A 10 20S 28E					<u> </u>					EDDY			
Latitude <u>32.5946274</u> Longitude104.1572189_ NAD83													
NATURE OF RELEASE													
Type of Release PRODUCED WATER							Volume of Release 10 BBLS Volume Recovered TBD						
Source of Release 3 inch Vic Check Valve failure											Hour of Discovery		
Was Immediate Notice Given? ☑ Yes ☐ No ☐ Not Required							If YES, To Whom?						
							TUCKER-BLM Date and Hour 01/03/2018 @ 11:57 AM						
By Whom? WADE DITTRICH Was a Watercourse Reached?							If YES, Volume Impacting the Watercourse.						
☐ Yes ☑ No													
If a Watercourse was Impacted, Describe Fully.*													
Describe Cause of Problem and Remedial Action Taken,*													
Leak was caused from 3 inch Vic check valve failure. Check valve will be repaired and returned to service.													
Describe Area Affected and Cleanup Action Taken.*													
The affected													
The affected area is 5 ft x 45 ft (measurements are subject to change with GPS tracking). Remediation will be completed in accordance with a remediation plan approved by the NMOCD and the SLO.													
I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and													
regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability													
should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health													
or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.													
OIL CONSERVATION DIVISION											etti oli oni etti etti etti etti etti etti etti et		
Signature: //w//													
						Approved by Environmental Specialist:							
Title; ENVIROMENTAL SPECIALIST						Approval Date: 1818 Expiration Date: NIA					IA		
E-mail Address: wade_dittrich@oxy.com						Conditions of Approval:			Attached				
Date:	8-18	Pho		See attached			Attache	200 U565					
		ets If Necess		5-390-2828		પ્રા	/ WITHOUT	VI.		1 6	114		

Operator/Responsible Party,

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete <u>division-approved corrective action</u> for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District 2 office in ARTESIA on or before 2/8/2018. If and when the release characterization workplan is approved, there will be an associated deadline for submittal of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

- Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.
- Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.
- Nominal detection limits for field and laboratory analyses must be provided.
- Composite sampling is not generally allowed.
- Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

- •Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.
- If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method 8260 full list), total dissolved solids, pH, major anions and cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.
- Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold
OCD Environmental Bureau Chief
1220 South St. Francis Drive
Santa Fe, New Mexico 87505
505-476-3465
jim.griswold@state.nm.us

Bratcher, Mike, EMNRD

From: Wade_Dittrich@oxy.com

Sent: Monday, January 8, 2018 7:50 AM

To: Bratcher, Mike, EMNRD; Weaver, Crystal, EMNRD; stucker@blm.gov

Cc: Jennifer_Smith@oxy.com
Subject: Government AB #9 Initial C141

Attachments: Signed-Initial C141.pdf

All,

Attached is the Initial C141. Please review and let me know if there are any questions. Thank you.

Wade Dittrich

Environmental Specialist

Oxy Permian-New Mexico 575-390-2828 cell 575-397-8214 office Wade_Dittrich@Oxy.com

Bratcher, Mike, EMNRD

From: Wade_Dittrich@oxy.com

Sent: Wednesday, January 3, 2018 10:57 AM

To: Bratcher, Mike, EMNRD; Weaver, Crystal, EMNRD

Cc: stucker@blm.gov; duskie@trinityoilfieldservices.com; ben@trinityoilfieldservices.com;

tristan@trinityoilfieldservices.com; Jennifer_Smith@oxy.com

Subject: Government AB 0009

All,

This is to inform you that Oxy Permian had a **Reportable** release in **Eddy County** at the **Government AB 0009** on 1/2/2018.

- Release Location: Legal -10-20S-28E, API: 30-015-27964
- Release Volume: 0 bbls of Oil and 10 bbls of Produced Water.
- Recovered: TBD bbls recovered
- Cause of Release: 3 inch Vic Check Valve failure
- Approximate Area impacted by release: 5ftx45ft (measurements are subject to change with GPS tracking)
- GPS Coordinates and Driving Direction: 32.5946274,-104.1572189
 FROM CARLSBAD GO E ON 62-180 8 MILES, TURN LEFT ON MAGNUM ROAD GO N 6 MILES. TURN LEFT ON BURTON FLATS ROAD GO 1.7 MILE, TURN RIGHT ON BUCKSKIN ROAD GO N 1 MILE, TURN LEFT ON LEASE ROAD GO W .75 MILE, 3 WAY INTERSECTION TURN RIGHT GO NORTH .5 MILE TO FAC

Please let me know if you have any questions.

Wade Dittrich

Environmental Specialist

Oxy Permian-New Mexico 575-390-2828 cell 575-397-8214 office Wade_Dittrich@Oxy.com