



# NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

**BILL RICHARDSON**

Governor

**Joan Prukop**

Cabin Secretary

**Mark E. Fesmire, P.E.**

Director

Oil Conservation Division

ADMINISTRATIVE ORDER SWD-1084

## APPLICATION OF KAISER-FRANCIS OIL COMPANY FOR PRODUCED WATER DISPOSAL, LEA COUNTY, NEW MEXICO

### ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Rule 701(B), KAISER-FRANCIS OIL COMPANY made application to the New Mexico Oil Conservation Division for permission to utilize for produced water disposal its North Bell Lake Unit 4 Well No. 15 (API No. 30-025-24771) located 1980 feet from the South line and 1980 feet from the West line of Section 8, Township 23 South, Range 34 East, NMPM, Lea County, New Mexico.

#### THE DIVISION DIRECTOR FINDS THAT:

- (1) The application has been duly filed under the provisions of Rule 701(B) of the Division Rules and Regulations;
- (2) Satisfactory information has been provided that all offset operators and surface owners have been duly notified;
- (3) The applicant has presented satisfactory evidence that all requirements prescribed in Rule 701 will be met; and
- (4) No objections have been received within the waiting period prescribed by said rule.

#### IT IS THEREFORE ORDERED THAT:

The applicant is hereby authorized to utilize its North Bell Lake Unit 4 Well No. 15 (API No. 30-025-24771) located 1980 feet from the South line and 1980 feet from the West line of Section 8, Township 23 South, Range 34 East, NMPM, Lea County, New Mexico, in such manner as to permit the injection of produced water for disposal purposes into the Bell Canyon and Cherry Canyon members of the Delaware Mountain Group through perforations from 5060 feet to 6550 feet and through plastic-lined tubing set with a packer located within 100 feet of the

top of the injection interval.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

As preparation for injection, the operator shall determine the cement top behind the 7-5/8 inch casing and raise this top with squeeze cementing to at least the 10-3/4 inch casing shoe at 4,773 feet. The cement squeeze shall be pressure tested to ensure vertical isolation of the permitted injection interval.

The 7-5/8 inch casing shall be plugged back with a cast iron bridge plug and cement to within 200 feet of the lowermost injection interval.

Within 6 months of commencing injection, an injection survey shall be run to determine which intervals are taking fluid and a copy sent to the engineering bureau of the Division in Santa Fe.

The casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer.

After installing injection tubing, the casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The wellhead injection pressure on the well shall be limited to **no more than 1012 psi**. In addition, the injection well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface injection pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the injection formation. Such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Hobbs district office of the Division of the date and time of the installation of disposal equipment and of any mechanical integrity test so that the same may be inspected and witnessed.

The operator shall immediately notify the supervisor of the Hobbs district office of the Division of the failure of the tubing, casing, or packer in said well and shall take such steps as may be timely and necessary to correct such failure or leakage.


PROVIDED FURTHER THAT, jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh water or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the injection authority granted herein.

The operator shall provide written notice of the date of commencement of injection to the Hobbs district office of the Division.

The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Rule Nos. 706 and 1120 of the Division Rules and Regulations.

The injection authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into the subject well, provided however, the Division, upon written request by the operator, may grant an extension thereof for good cause shown.

This order approved at Santa Fe, New Mexico on May 17, 2007.

  
MARK E. FESMIRE, P.E.  
Director

MEF/wvj

cc: Oil Conservation Division – Hobbs  
State Land Office – Oil, Gas, and Minerals Division