Bill Richardson

Governor

Joanna Prukop Cabinet Secretary Reese Fullerton Deputy Cabinet Secretary Mark Fesmire
Division Director
Oil Conservation Division



Administrative Order SWD-1141 September 18, 2008

APPLICATION OF JOHN CRAVEY DBA JRC PETROLEUM FOR PRODUCED WATER DISPOSAL, EDDY COUNTY, NEW MEXICO

ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Rule 701(B), John Cravey dba JRC Petroleum (OGRID 252682) made application to the New Mexico Oil Conservation Division for permission to utilize for produced water disposal its Bradley Federal Well No. 6 (API No. 30-015-00386) located 1650 feet from the South line and 990 feet from the East line of Section 11, Township 24 South, Range 26 East, NMPM, Eddy County, New Mexico.

THE DIVISION DIRECTOR FINDS THAT:

The application has been duly filed under the provisions of Rule 701(B) of the Division Rules and Regulations. Satisfactory information has been provided that affected parties as defined in Rule 701B(2) have been notified and no objections have been received within the prescribed waiting period. The applicant has presented satisfactory evidence that all requirements prescribed in Rule 701 will be met and the operator will be in compliance with the Division's Rule 40 after production wells surrounding this subject injection well are re-activated.

IT IS THEREFORE ORDERED THAT:

John Cravey dba JRC Petroleum is hereby authorized to utilize its Bradley Federal Well No. 6 (API No. 30-015-00386) located 1650 feet from the South line and 990 feet from the East line of Section 11, Township 24 South, Range 26 East, NMPM, Eddy County, New Mexico, in such manner as to permit the injection of produced water for disposal purposes into the Delaware Mountain Group through an open hole from 1987 feet to 2100 feet and through plastic-lined tubing set with a packer located within 100 feet of the top of the injection interval.

IT IS FURTHER ORDERED THAT:



The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

As preparation and prior to injection in this well, the operator shall ensure the Division has copies of sundry notices showing the deepening of this well from 2000 to 2100 feet and showing squeeze operations on any older perforations in the 7 inch casing. The operator shall report to the Division on sundry notice the initial standing fluid level or reservoir pressure of the injection interval prior to beginning injection.

Within 6 months of beginning injection, the operator shall supply the Division with a copy of an injection [temperature and tracer survey] log run while injecting at this well's average injection rate, identifying the injection intervals within the open hole.

After installing injection tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The wellhead injection pressure on the well shall be limited to **no more than 640 psi.** In addition, the injection well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface injection pressure to the maximum allowable pressure for this well.

This well is NOT eligible for future injection pressure increases, except after sufficient evidence and notice are presented at an examiner hearing. Such notice shall include new cement bond log run on the injection casing.

The operator shall notify the supervisor of the Division's district office of the date and time of the installation of disposal equipment and of any mechanical integrity test so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of injection to the Division's district office. The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Rule Nos. 706 and 1115 of the Division Rules and Regulations.

Without limitation on the duties of the operator as provided in Division Rules 19 and 116, or otherwise, the operator shall immediately notify the Division's district office of any failure of the tubing, casing or packer in the well, or of any leakage or release of water, oil or gas from around any produced or plugged and abandoned well in the area, and shall take such measures as may be timely and necessary to correct such failure or leakage.

In accordance with Rule No 705.C, the injection authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into the subject well, provided however, the Division, upon written request, mailed by the operator prior to the termination date, may grant an

extension thereof for good cause shown. One year after injection operations into the well has ceased, the injection authority will terminate *ipso facto*.

Compliance with this order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the injection authority granted herein.

MARK É. FESMIRE, P.E.

Director

MEF/wvjj

cc: C

Oil Conservation Division – Artesia Bureau of Land Management - Carlsbad