

1R - 428-57

REPORTS

DATE:

10-20-09

Katie Lee

From: Katie Lee [katie@rthicksconsult.com]
Sent: Tuesday, October 20, 2009 2:05 PM
To: Edward J. EMNRD Hansen (edwardj.hansen@state.nm.us)
Cc: Hack Conder (hconder@riceswd.com); Katie Jones; Lara Weinheimer
Subject: Hobbs B-32, NMOCD #1R428-57, plugging report

RECEIVED
OCT 21 2009
Environmental Bureau
Oil Conservation Division

Dear Mr. Hansen,

RT Hicks Consultants is pleased to submit documentation of the plugging and abandonment of MW-1 at Hobbs B-32 Boot, (NMOCD #1R428-57) on September 30, 2009. This well was plugged using a 1% - 3% bentonite slurry and a 3 foot cap of concrete at the surface.

If you have any questions, please contact me at the number below or Hack Conder at the Rice office in Hobbs.

Best regards,

Katie Lee
Project Scientist
R.T. Hicks Consultants, Ltd.
ph. 505-266-5004
fax 505-266-0745
mobile 505-400-7925

10/20/2009

Plugging Well MW-1 at Hobbs B-32 Boot, NMOCD Case #1R428-57
9-30-09





HARRISON & COOPER, INC.

Drilling & Pump Professionals

7414 85th Street, Lubbock, Texas 79424-4951

P.O. Box 96, Wolfforth, Texas 79382-0096

Ph: (806) 866-4026

Fax: (806) 866-4044

harrisoncooper-drilling.com

Plugging Report

Client	Rice Operating
Contractor	Harrison & Cooper
Date Completed	9/30/2009
Site	Hobbs B-32 Boot
Well ID	MW-1
Casing Diameter	2"
Well Depth	50'
Casing Material	PVC
Plugging Material	Portland/Bentonite Slurry
Slurry Interval	3'-50'
Cement Interval	0'-3'

Copies: File

Email (Lara Weinheimer)

Mail (Rice-Hobbs)

Regulated by: Texas Dept. of Licensing & Regulation, Water Well Division, P.O. Box 12157, Austin, TX 78711, (800) 803-9202