

ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION



BRUCE KING
GOVERNOR



POST OFFICE BOX 2088
STATE LAND OFFICE BUILDING
SANTA FE, NEW MEXICO 87504
(505) 827-5800

ADMINISTRATIVE ORDER NO. WFX-628

APPLICATION OF MERIDIAN OIL COMPANY TO EXPAND ITS WATERFLOOD PROJECT IN THE SHUGART POOL IN EDDY COUNTY, NEW MEXICO

**ADMINISTRATIVE ORDER
OF THE OIL CONSERVATION DIVISION**

Under the provisions of Division Order No. R-3431, Meridian Oil Company has made application to the Division on February 17, 1992, for permission to expand its Shugart - Yates, Seven Rivers, Queen and Grayburg Waterflood Project in the Shugart Pool in Eddy County, New Mexico.

THE DIVISION DIRECTOR FINDS THAT:

- (1) The application has been filed in due form.
- (2) Satisfactory information has been provided that all offset operators have been duly notified of the application.
- (3) No objection has been received within the waiting period as prescribed by Rule 701(B).
- (4) The proposed injection well is eligible for conversion to injection under the terms of Rule 701.
- (5) The proposed expansion of the above referenced Shugart - Yates, Seven Rivers, Queen and Grayburg Waterflood Project will not cause waste nor impair correlative rights.
- (6) The application should be approved.

IT IS THEREFORE ORDERED THAT:

The applicant, Meridian Oil Company, be and the same is hereby authorized to inject water into the Yates formation at approximately 2538 feet to approximately 2554 feet through 2 3/8 inch plastic lined tubing set in a packer at approximately 2438 feet in the following described well shown on Exhibit "A" attached hereto for purposes of secondary recovery to wit.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

Prior to commencing injection into subject well, operator shall either cement squeeze the production casing string or plug and abandon the Kenwood No. 3, in a manner satisfactory to the supervisor or the Artesia District Office.

Prior to commencing injection operations into the well, the casing shall be pressure tested from the surface to the packer setting depth to assure the integrity of said casing.

The casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing or packer.

The injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 408 psi. or .2 psi/ft. of depth to the uppermost perforation.

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Yates formation. Such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Artesia district office of the Division of the date and time of the installation of injection equipment and of the mechanical integrity tests so that the same may be inspected and witnessed.

Administrative Order WFX-628
Meridian Oil Company
April 8, 1992
Page 3


The operator shall immediately notify the supervisor of the Artesia district office of the Division of the failure of the tubing, casing or packer in said well and shall take such steps as may be timely and necessary to correct such failure or leakage.

The subject well shall be governed by all provisions of Division Order No. R-3431, as amended and Rules 702-706 of the Division Rules and Regulations not inconsistent herewith.

PROVIDED FURTHER THAT, jurisdiction of this cause is hereby retained by the Division for the entry of such further order or orders as may be deemed necessary or convenient for the prevention of waste and/or protection of correlative rights; upon failure of the operator to conduct operations in a manner which will ensure the protection of fresh water or in a manner inconsistent with the requirements set forth in this order, the Division may, after notice and hearing, terminate the injection authority granted herein.

DONE at Santa Fe, New Mexico, on this 8th day of April, 1992.

STATE OF NEW MEXICO
OIL CONSERVATION DIVISION



WILLIAM J. LEMAY
Director

S E A L

jc/

cc: Oil Conservation Division - Artesia

EXHIBIT "A"
 DIVISION ORDER NO. WFX-628
 SHUGART-YATES, SEVEN RIVERS, QUEEN AND GRAYBURG WATERFLOOD PROJECT
 APPROVED INJECTION WELLS

Well Number	Location	Unit	S-T-R	Injection Perforations	Packer Depth	Tubing Size	Injection Pressure
SHUGART "A" No. 4	1650' FSL - 2310' FWL	K	29-18S-31E	2538' - 2554'	2438'	2 3/8"	408 PSIG

Located in Eddy County, New Mexico