



STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT
OIL CONSERVATION DIVISION

TONY ANAYA
GOVERNOR

Amended
ORDER SWD-247

POST OFFICE BOX 2088
STATE LAND OFFICE BUILDING
SANTA FE, NEW MEXICO 87501
(505) 827-5800

THE APPLICATION OF FLUID WASTE, INC.

ADMINISTRATIVE ORDER
OF THE OIL CONSERVATION DIVISION

Under the provisions of Rule 701(B), Fluid Waste Inc. made application to the New Mexico Oil Conservation Division on September 17, 1984, for permission to complete for salt water disposal its Dorstate SWD Well No. 1 located in Unit H of Section 27, Township 25 South, Range 28 East, NMPM, Eddy County, New Mexico.

The Division Director finds:

- (1) That application has been duly filed under the provisions of Rule 701(B) of the Division Rules and Regulations;
- (2) That satisfactory information has been provided that all offset operators and surface owners have been duly notified; and
- (3) That the applicant has presented satisfactory evidence that all requirements prescribed in Rule 701 will be met.
- (4) That no objections have been received within the waiting period prescribed by said rule.

IT IS THEREFORE ORDERED:

That the applicant herein, Fluid Waste Inc., is hereby authorized to complete its Dorstate SWD Well No. 1, located in Unit H of Section 27, Township 25 South, Range 28 East, NMPM, Eddy County, New Mexico, in such a manner as to permit the injection of salt water for disposal purposes into the Bone Springs formation at approximately 6376 feet to approximately 6825 feet through 2 7/8 inch plastic lined tubing set in a packer located at approximately 6310 feet.

IT IS FURTHER ORDERED:

That the operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

That the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

That the injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 1275 psi.

That the Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Bone Springs formation. That such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

That the operator shall notify the supervisor of the Artesia district office of the Division of the date and time of the installation of disposal equipment so that the same may be inspected.


That the operator shall immediately notify the supervisor of the Division's Artesia district office of the failure of the tubing, casing, or packer, in said well or the leakage of water from or around said well and shall take such steps as may be timely and necessary to correct such failure or leakage.

PROVIDED FURTHER, That jurisdiction of this cause is hereby retained by the Division for such further order or orders as may seem necessary or convenient for the prevention of waste and/or protection of correlative rights; upon failure of applicant to comply with any requirement of this order after notice and hearing, the Division may terminate the authority hereby granted in the interest of conservation. That applicant shall submit monthly reports of the disposal operations in accordance with Rule 706 and 1120 of the Division Rules and Regulations.

NOTE: This order has been amended to change the injection interval from the Delaware Formation to the Bone Springs Formation.

Approved at Santa Fe, New Mexico, on this 18th day of October, 1984.

STATE OF NEW MEXICO
OIL CONSERVATION DIVISION



R. L. STAMETS,
Acting Director

S E A 6