# BJ SERVICES COMPANY MATERIAL SAFETY DATA SHEET

Region USA

## **<u>1 PRODUCT AND COMPANY IDENTIFICATION</u>**

Product Name: Item Number: Product Use: Supplier:

488429, 488430 Surface tension reducer BJ Services Company 11211 FM 2920 Tomball, Texas 77375 (281)351-8131

InFlo 250W

## IN CASE OF EMERGENCY CALL: (800) 424-9300 for CHEMTREC (703) 527-3887 for International

# HMIS HAZARD INDEXHEALTH:1FLAMMABILITY:2REACTIVITY:0PERSONAL PROTECTION:g

#### **2 COMPOSITION/INFORMATION ON INGREDIENTS**

Hazardous Component	CAS#	Percent	Hazard
Surfactants	Proprietary	20-80	
2-Butoxyethanol	000111-76-2	3-20	Irritant
Methanol	000067-56-1	10-30	Flammable
		1 ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) (	toxic

#### **<u>3 HAZARDS IDENTIFICATION</u>**

PRIMARY ROUTES OF EXPOSURE: Eye con

Eye contact. Ingestion. Skin contact.

ACUTE OVEREXPOSURE EFFECTS:

**INHALATION:** None known.

**INGESTION:** May be harmful if swallowed.

EYE CONTACT: Contact with liquid may cause eye irritation.

BEFORE THE OIL CONSERVATION COMMISSION Santa Fe, New Mexico Case No. 14753 Exhibit No. 4 Submitted by: <u>THE NEW MEXICO OIL & GAS ASSOCIATION</u> Hearing Date: <u>November 17, 2011</u>

SKIN CONTACT: May cause skin irritation. May cause redness and blistering of skin.

EXPOSURE LIMITS:

HAZARDOUS COMPONENT	ACGIH TLV	OSHA PEL	LC50 (inhalation)	LD50 (oral)
Surfactants	NA	NA	NA	NA

2-Butoxyethanol	20 ppm	50 ppm	450 ppm/4 rat	250 mg/kg rat
Methanol	200 ppm, skin	200 ppm TWA	64000 ppm/4 rat	5600 mg/kg rat
		· · · · · · · · · · · · · · · · · · ·		

## **<u>4 FIRST AID MEASURES</u>**

#### INHALATION:

None known.

## INGESTION:

Do not induce vomiting. Give victim plenty of water. Obtain medical attention immediately. Never give anything by mouth to an unconscious person.

#### EYES:

Flush eyes immediately with large amounts of water for at least 15 minutes. Lift upper and lower lids occasionally. Get medical attention.

#### SKIN:

In case of contact, immediately flush skin with plenty of soap and water. Remove contaminated clothing and launder before reuse. Seek medical attention if irritation persists.

### **5 FIRE FIGHTING MEASURES**

FLASHPOINT (METHOD): LOWER EXPLOSION LIMIT (% v/v): UPPER EXPLOSION LIMIT (% v/v): AUTO-IGNITION TEMPERATURE:

113°F(ASTM D - 6450) Not available Not available Not available

SPECIAL HAZARDS: Product may burn in fire conditions. EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, foam. SPECIAL FIREFIGHTING PROCEDURES: Fire-fighters should wear self-contained breathing apparatus and full protective clothing when fighting chemical fires. HAZARDOUS COMBUSTION PRODUCTS:

None.

## **6 ACCIDENTAL RELEASE MEASURES**

Wear specified protective equipment. Remove sources of ignition. Small spills - Cover spill with absorbent material. Scoop absorbed material into a suitable container for disposal. Large spills - Dike to contain. Prevent from entering sewers or waterways. Recover product to suitable containers or vessel for reuse, if possible, or for disposal. Use only explosion proof transfer equipment.

#### 7 HANDLING AND STORAGE

#### HANDLING:

Avoid contact with skin and eyes. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Electrically ground/bond during pumping or transfer to avoid static accumulation/discharge. Use only in a well ventilated area. Use only spark-proof and explosion-proof tools and equipment. Wash hands before eating and smoking.

#### STORAGE REQUIREMENTS:

Keep container tightly closed, in a cool, well ventilated place. Keep away from ignition sources. Keep away from incompatible materials.

## **8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

SPECIFIC ENGINEERING CONTROLS: Local exhaust. Use only in a well ventilated area.

PERSONAL PROTECTIVE EQUIPMENT:

Chemical resistant gloves. Chemical resistant goggles. Coveralls. Appropriate respiratory protection shall be worn when applied engineering controls are not adequate to protect against inhalation exposure. (Cartridge respirator)

#### **9 PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE: COLOR: ODOR THRESHOLD: SPECIFIC GRAVITY: VAPOR PRESSURE: VAPOR DENSITY (air = 1): EVAPORATION RATE: BOILING POINT: FREEZING POINT: pH: VISCOSITY (F):	Liquid Clear/yellow None Not available 0.9 - 1.0 Not available Not available Not available Not available Not available 8 - 11 (1% solution) Not available
VISCOSITY (F): SOLUBILITY IN WATER:	Not available Soluble

#### **10 STABILITY AND REACTIVITY**

STABILITY: Stable under normal conditions of use. INCOMPATIBILITY/CONDITIONS OF REACTIVITY: Contact with oxidizing agents. Contact with strong acids. Reducing agents. HAZARDOUS THERMAL DECOMPOSITION PRODUCTS: Oxides of carbon and nitrogen. HAZARDOUS POLYMERIZATION: Will not occur.

#### **11 TOXICOLOGICAL PROPERTIES**

CHRONIC EFFECTS: None known.

SENSITIZATION: Not known. CARCINOGENICITY: None of the components of this product have been listed as carcinogenic by IARC, NTP or OSHA. (IARC-International Agency for Research on Cancer) (NTP - National Toxicology Program) (OSHA - Occupational Safety & Health Administration (US)). MUTAGENICITY: Not known. REPRODUCTIVE TOXICITY: Not known.

#### **12 ECOLOGICAL INFORMATION**

No specific information available.

#### **13 DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL:

Disposal should be made in accordance with national and local regulations. Consult local waste authorities for direction and/or approvals prior to disposal.

#### **14 TRANSPORT INFORMATION**

#### LAND TRANSPORT (DOT)

Proper Shipping Name:	Combustible liquid, n.o.s.
Technical Name(s):	2-Butoxyethanol, Methanol
UN/ID No.:	NA 1993
Hazard Class - Primary:	Combustible
Hazard Class - Secondary:	
Packing Group:	111
Reportable Quantity (RQ):	5000 lbs (Methanol)
Emergency Response Guide #:	128

#### **AIR TRANSPORT (ICAO/IATA)**

Proper Shipping Name:	Flammable Liquid, n.o.s.
Technical Name(s):	2-Butoxyethanol, Methanol
UN/ID No.:	UN 1993
Hazard Class - Primary:	Flammable
Hazard Class - Secondary:	
Packing Group:	<u>{}1</u>

#### MARINE TRANSPORT (IMDG/IMO)

Proper Shipping Name:	Flammable Liquid, n.o.s.
Technical Name(s):	2-Butoxyethanol, Methanol
UN No.:	UN 1993
Hazard Class - Primary:	Flammable
Hazard Class - Secondary:	
Packing Group:	III
EmS:	

#### **15 REGULATORY INFORMATION**

#### SARA TITLE III:

SECTION 302/304This product does not contain substances listed in Appendix A and B as an ExtremelyHazardous Substance.SECTION 311/312SECTION 311/312Immediate, FireSECTION 313This product contains the following substance(s) which appear on the List of ToxicChemicals:, Methanol CAS # 67-56-1

TSCA INVENTORY: The substances in this product are included on or exempted from the TSCA 8(b) Inventory (40 CFR 710) CALIFORNIA PROP 65: This product does not contain substances which require warning under California Proposition 65. PRIORITY POLLUTANTS:

#### **16 OTHER INFORMATION**

ISSUE DATE: PREPARED BY: 02/20/2009 BJ Services Environmental Group

REFERENCES:

CCINFO Web Information Service, Canadian Centre for Occupational Health and Safety, 2006. Guide to Occupational Exposure Values - 2006, American Conference of Governmental Industrial Hygienists, 2006. Supplier's Literature. SAX's Dangerous Properties of Industrial Materials Suspect Chemicals Sourcebook Dangerous Goods Regulations, 48th ed., International Air Transport Association, 2007.

The information contained herein is based on data considered accurate. However, no warranty is expressed or

implied regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

.