

TEXTURE	Vol moisture		parameters		SAT flow	CALCULATED at mid-saturation	
	RESID	SATUR	alpha (1/cm)	n	Ksat (cm/d)	Suction (atm)	Kunsat (cm/d)
1 Sand	0.045	0.43	0.145	2.68	713	88	25.
2 Loamy sand	0.057	0.41	0.124	2.28	350	117	7.6
3 Sandy loam	0.065	0.41	0.075	1.89	106	248	1.0 loose
4 Loam	0.078	0.43	0.036	1.56	25	849	5.0E-2
5 Sandy clay loam	0.10	0.39	0.059	1.48	31	647	3.5E-2 moderate
6 Silt loam	0.067	0.45	0.02	1.41	11	2480	5.0E-3
7 Silt	0.034	0.46	0.016	1.37	6.0	3760	1.9E-3
8 Clay loam	0.095	0.41	0.019	1.31	6.2	4630	7.4E-4 tight
9 Sandy clay	0.10	0.38	0.027	1.23	2.9	7240	4.4E-5
10 Silty clay loam	0.089	0.43	0.01	1.23	1.7	19600	2.6E-5
11 Silty clay	0.07	0.36	0.005	1.09	0.5	4.3M	1.2E-10

=====

Volumetric moisture, parameters, and saturated hydraulic conductivity are from the U.S. Environmental Protection Agency, Unsaturated Soil Hydraulic Database, EPA/600/R-96/095, August, 1996.