

Denton No. 3

Fasken Oil and Ranch, Ltd.

Location: 660' FNL, 1939.5' FEL
Sec 11, T15S, R37E
Lea County, New Mexico
Compl.: 21-Nov-51
API #: 30-025-05290
IP:
TD: 12,800'
PBTB:
Casing: 13-3/8", 27.3#, Armco Spiral Weld 337.73'
Cmt 350 sx regular
TOC surf
8-5/8", 32&28#, @ 4642.85'
Cmt 3600sx w/4%gel
TOC surf, circ 150 sx
5-1/2" 15.5-23# @ 12,797'
Cmt 1st stg 360sx 8% sloset+62sx stratacrete
Circ trace 1st stg cmt thru DV
DV: 8994'
Cmt 2nd stg w/630 sx 8% gel regular
TOC 3700' by temp

Tubing 2-7/8" EUE 8rd N-80 tubing 11757.47

BP 11,810' per file "bridge plug"(Sep 55)

Perfs: Devonian
11700-740 (160h,Aug 55)
11800-805 (20h,Sep 55)(Sqzd Sep 55)
12716-66 s(200h,Dec '51)(Sqzd Aug '55)
12781-95 s(56h,Dec '51)(Sqzd Aug '55)

As of: 9-18-00

GL: 3794.5'

KB: 3812'

13-3/8", 27.3#, Armco Spiral Weld 337.73'

Cmt 350 sx regular

TOC surf, circ 150 sx

8-5/8", 32&28#, @ 4642.85'

Cmt 3600sx w/4%gel

TOC surf, circ 150 sx

DV: 8994'

Circ trace 1st stg cmt thru DV

Prf 11700-740

Prf 11800-805 sqzd

BP 11,810' per file "bridge plug"(Sep 55)

Prf 12716-66 sqzd

Prf 12781-95 sqzd

TD: 12,800'

5-1/2" 15.5-23# @ 12,797'

TOC 3700' by temp

BEFORE THE
OIL CONSERVATION DIVISION
Case No. 13601 Exhibit No. 9
Submitted By:
Fasken Oil and Ranch
Hearing Date: December 15, 2005

cwb
12/13/2005
Denton wb diagrams.xls