



U.S. Department of Labor
Occupational Safety & Health Administration

www.osha.gov

MyOSHA Search

GO Advanced Search | A

Regulations (Standards - 29 CFR)

TABLE Z-2 - 1910.1000 TABLE Z-2

Regulations (Standards - 29 CFR) - Table of Contents

• **Part Number:** 1910
 • **Part Title:** Occupational Safety and Health Standards
 • **Subpart:** Z
 • **Subpart Title:** Toxic and Hazardous Substances
 • **Standard Number:** 1910.1000 TABLE Z-2
 • **Title:** TABLE Z-2

TABLE Z-2

Substance	8-hour time weighted average	Acceptable ceiling concentration	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	
			Concentration	Maximum duration
Benzene ^(a) (Z37.40-1969)	10 ppm	25 ppm	50 ppm	10 minutes.
Beryllium and beryllium compounds (Z37.29-1970)	2 ug/m(3)	5 ug/m(3)	25 ug/m(3)	30 minutes.
Cadmium fume ^(b) (Z37.5-1970)	0.1 mg/m(3)	0.3 mg/m(3)		
Cadmium dust ^(b) (Z37.5-1970)	0.2 mg/m(3)	0.6 mg/m(3)		
Carbon disulfide (Z37.3-1968)	20 ppm	30 ppm	100 ppm	30 minutes.
Carbon tetrachloride (Z37.17-1967)	10 ppm	25 ppm	200 ppm	5 min. in any 3 hrs.
Chromic acid and chromates (Z37-7-1971)		1 mg/10 m(3)		
Ethylene dibromide (Z37.31-1970)	20 ppm	30 ppm	50 ppm	5 minutes.
Ethylene dichloride (Z37.21-1969)	50 ppm	100 ppm	200 ppm	5 min. in any 3 hrs.
Fluoride as dust (Z37.28-1969)	2.5 mg/m(3)			
Formaldehyde: see 1910.1048				
Hydrogen fluoride	3 ppm			

NMOCD CASE NO. 13589
MARCH 13, 2006
SMITH, SNYDER & AC
EXHIBIT NO. 17

(Z37.28-1969)				
Hydrogen sulfide (Z37.2-1966)		20 ppm	50 ppm	10 mins. once only if no other meas. exp. occurs.
Mercury (Z37.8-1971)		1 mg/10m(3)		
Methyl chloride (Z37.18-1969)	100 ppm	200 ppm	300 ppm	5 mins. in any 3 hrs.
Methylene Chloride: see 1910.1052				
Organo (alkyl) mercury (Z37.30-1969)	0.01mg/m (3)	0.04 mg/m (3)		
Styrene (Z37.15-1969)	100 ppm	200 ppm	600 ppm	5 mins. in any 3 hrs.
Tetrachloroethylene	100 ppm	200 ppm	300 ppm	5 mins. in any 3 hrs.
Toluene (Z37.12-1967)	200 ppm	300 ppm	500 ppm	10 minutes
Trichloroethylene (Z37.19-1967)	100 ppm	200 ppm	300 ppm	5 mins. in any 2 hrs.

Footnote^(a) This standard applies to the industry segments exempt from the 1 ppm 8-hour TWA and 5 ppm STEL of the benzene standard at 1910.1028.

Footnote^(b) This standard applies to any operations or sectors for which the Cadmium standard, 1910.1027, is stayed or otherwise not in effect.

[62 FR 42018, August 4, 1997]

◀ [Next Standard \(1910.1000 TABLE Z-3\)](#)

◀ [Regulations \(Standards - 29 CFR\) - Table of Contents](#)

⬆ [Back to Top](#)

www.osha.gov

[Contact Us](#) | [Freedom of Information Act](#) | [Customer Survey](#)
[Privacy and Security Statement](#) | [Disclaimers](#)

Occupational Safety & Health Administration
200 Constitution Avenue, NW
Washington, DC 20210