

API NUMBER

OPERATOR NAME Cross et al

WELL NUMBER #1

PROPERTY NAME Blackjack

SECTION 15 TOWNSHIP 29N

RANGE 13W

FOOTAGE 2843 FEL 2600 FWL

Sur Csg OD

OJO ALAMO 400-500' SUR CSG TD

Kirtland 500-800' SUR CSG WT

TOP OF CMT

ACTUAL

CACULATED

PROD CSG OD

PROD CSG TD

PROD CSG WT

TOP OF CMT

ACTUAL

CACULATED

PERF TOP

PERF BOTTOM

PACKER

TYPE OF PLUG

CIBP & CMT

CMT

XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX

PROPOSED PLUGGING OPERATION

TD @ 740' We have no record of the casing size, weight, or depth.

Do site prepration, dig out wellbore area. Determine casing size, Rig up well head

Install ancores, MIPU, install bop equipment, clean out well bore to TD 740 +-,

set bottom plug, test casing, fill well bore with cement from TD to surface.

NDBOP, cut off casing and install P&A Marker.

RDPU , cut off ancores,

Close pits according to guidelines: Clean and level location

BEFORE EXAMINER STOCNER

OIL CONSERVATION DIVISION

0CD EXHIBIT NO. 3

CASE NO. 12822