

6- (

CHRONOLOGICAL WELL HISTORY
SUPPLIED BY READ & STEVENS

Coquina Oil Corporation
R & S Federal #1
Section 20 - 20S-24E
Eddy County, New Mexico

R S Federal 1
Hobbs

7-8

7680' drlg. Lm & sh. 390' progress. Rotated 20 3/4 hrs.
Drlg w/brine, Wt. 9.2, V 29, pH 10. 50 RPM, 35,000#, 1500 ps
Bit #6, Reed FP63, 7 7/8", drld 2026' in 112 3/4 hrs. Dev.
3 1/4° @ 7335' & 3° @ 7461'.

R S Federal 1
Hobbs

7-9

7845' trip for DST #1. Lm & sd. 165' progress. Rotated
6 3/4 hrs. Wt. 9.3, V 31, WL 10, FC film, pH 10. 46 RPM,
40,000#, 1500 psi. Bit #6, Reed FP63, 7 7/8", drld 2143' in
113 1/4 hrs. Bit #7, HTC J55, 7 7/8", drld 43' in 1 1/4 hrs.
Dev. 1 3/4° @ 7713' & 2° @ 7800'.

R S Federal 1
Hobbs

7997' drlg. Lm, sd & sh. 152' progress. Rotated 7 3/4 hrs.
Wt. 9.3, V 32, WL 30, pH 10. 46 RPM, 44,000#, 1500 psi.
Bit #7, HTC J55, 7 7/8", drld 195' in 9 hrs.

DST #1 7708'-7845' Cisco Dolomite

7-10

15" Preflow	212-403 psi	Weak blow thruout.
60" ISIP	2887 psi	
60" Flow	466-763 psi	Weak blow thruout.
120" FSIP	2887 psi	
IHyd	3825 psi	
FHyd	3825 psi	

Rec.: 1457' Sulfur wtr - Cl 67,000 ppm.