

TITLE NO.

WELL RECORD

ELEV. 3607'
AUTH. NO. 7-1988

WELL NO. 3

O. L. Coleman

FARM OR LEASE

DESCRIPTION

160 Acres, W¹/₄

SEC. 17

TWP. 21N

RNG. 36E

LOCATION

660' from North & East lines

COUNTY

Lea County, New Mexico

RIG COMMENCED

COMPLETED

RIG CONTRACTOR

DRILLING COMMENCED

Aug 29, 1934

COMPLETED

Oct 7, 1934

DRILLING CONTRACTOR

G. H. Vaughn Drilling Co., Dallas, Tex

PRICE PER FOOT. \$

CASING AND TUBING RECORD

SIZE	PUT IN WELL		PULLED OUT		MAKE OF CASING	TUBING USED			PACKERS
	FEET	IN.	FEET	IN.		SIZE	FEET	IN.	
12 1/2" 50#	43'		None		LW Steel				TP Csg Shoe
9-5/8" 36#	2860'		None		Seam. Steel				Halliburton Float Shoe
7" 24#	3804'		None		Seam. Steel				do do
Tubing:									
2" Up. 4.7#	3935'	10"	Reading WI (6' of bottom joint perforated & bottom bull nosed)						

SAND	TOP	BOTTOM	THICKNESS	INITIAL TORPEDO		
				QUARTS	DATE OF SHOT	TORPEDO COMPANY
Gray Sandy Lime	3835	3845				
Gray Lime	3875	3905				
Gray Lime	3915	3925				

TOTAL DEPTH 3925'

Did not shoot or Acid Treat.

RECORD OF SAND AND OIL SHOWINGS

3795 - 3800' Sandy Lime - Light oil show.

3835 - 3845' Gray Sandy Lime - Light oil show.

3875 - 3905' Gray lime - Good show oil.

3915 - 3925' Gray lime - Good show oil.

PRODUCTION FIRST 24 HOURS-NATURAL

936 bbls

AFTER SHOT

GRAVITY

33.5

DETAIL OF SHOT

None

COMMENCED PRODUCING

10/9/34

SUBSEQUENT HISTORY

1st 24 hrs natural flowed 936 bbls - 99% oil, 1% emulsion (Drilling fluid)
Manometer gas test 852,480 cu ft.

No^w producing thru surface choke on tubing at prorated allowance.

12 1/2" Csg cemented to top w/ 40 sax. Set @ 61'.

9-5/8" Casing cemented by Halliburton 2-Stage job, 175 sax Inoor cement below, 325 Sax Inoor above. Set @ 2860'.

7" OD Casing cemented by Halliburton @ 3789' w/ 310 sax.