



## TEMPERATURE SURVEY

<b>Location</b>	COMPANY <u>THOMAS W DOSWELL</u>		<b>WELL</b> <u>FEDERAL LAND # 1</u>	<b>FIELD</b> <u>Wildcat</u>	<b>County</b> <u>Rio Arriba</u>	<b>Sec.</b> <u>Twp</u>	<b>State</b> <u>New Mexico</u>	<b>Survey</b>	<b>FILE</b>	<b>COMPANY THOMAS W DOSWELL</b>																				
	FILE _____																													
	WELL <u>FEDERAL LAND # 1</u>																													
	FIELD <u>Wildcat</u>																													
	County <u>Rio Arriba</u> State <u>New Mexico</u>																													
	Sec. _____ Twp _____ Rge _____																													
Survey _____																														
Log Measured From <u>Top of drive bushing</u> Elevation _____																														
Drilling Measured From <u>Top of drive bushing</u> Elevation _____																														
Permanent Datum <u>13 3/8" Casing flange</u> Elevation _____																														
Date of Cementing <u>7 - 22 - 50</u> Time <u>7 15 P M</u>																														
Date of Survey <u>7 - 23 - 50</u> Time <u>6 30 P M</u>																														
Amount of Cement <u>300 sacks</u> Type <u>Slo-set</u>																														
Amount of Admix _____ Type _____																														
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th style="width: 15%;">Casing Size</th> <th style="width: 15%;">Casing Depth</th> <th style="width: 15%;">Diam. of Hole</th> <th style="width: 15%;">Depth</th> </tr> </thead> <tbody> <tr> <td><u>13 3/8</u></td> <td>from <u>0</u> to <u>315'</u></td> <td><u>17 1/4"</u></td> <td>from <u>0</u> to <u>315'</u></td> </tr> <tr> <td><u>9 5/8"</u></td> <td>from <u>0</u> to <u>2915'</u></td> <td><u>12"</u></td> <td>from <u>315'</u> to <u>2915'</u></td> </tr> <tr> <td><u>7"</u></td> <td>from <u>0</u> to <u>7210'</u></td> <td><u>8 5/8"</u></td> <td>from <u>2915'</u> to <u>7210'</u></td> </tr> <tr> <td> </td> <td>from _____ to _____</td> <td> </td> <td>from _____ to _____</td> </tr> </tbody> </table>											Casing Size	Casing Depth	Diam. of Hole	Depth	<u>13 3/8</u>	from <u>0</u> to <u>315'</u>	<u>17 1/4"</u>	from <u>0</u> to <u>315'</u>	<u>9 5/8"</u>	from <u>0</u> to <u>2915'</u>	<u>12"</u>	from <u>315'</u> to <u>2915'</u>	<u>7"</u>	from <u>0</u> to <u>7210'</u>	<u>8 5/8"</u>	from <u>2915'</u> to <u>7210'</u>		from _____ to _____		from _____ to _____
Casing Size	Casing Depth	Diam. of Hole	Depth																											
<u>13 3/8</u>	from <u>0</u> to <u>315'</u>	<u>17 1/4"</u>	from <u>0</u> to <u>315'</u>																											
<u>9 5/8"</u>	from <u>0</u> to <u>2915'</u>	<u>12"</u>	from <u>315'</u> to <u>2915'</u>																											
<u>7"</u>	from <u>0</u> to <u>7210'</u>	<u>8 5/8"</u>	from <u>2915'</u> to <u>7210'</u>																											
	from _____ to _____		from _____ to _____																											
Survey Begins at <u>4000</u> Ft. Ends at <u>7175</u> Ft.																														
Bottom Hole Temp. <u>160</u> °F Max. Temp. <u>162</u> °F																														
Run No. <u>One</u> Approx. Top Cement <u>4810</u> Ft.																														
Recorded by <u>MR Lewis</u> Witnessed by <u>JM Myers</u>																														