

REPRODUCED BY
WEST TEXAS ELECTRICAL LOG SERVICE

1305 Commerce Street
Dallas 1, Texas

REFERENCE No. A 77-E

LANE RADIOACTIVITY LOG COMPANY WELLS										
Location of Well Elevation <u>5348</u>	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none; vertical-align: top;"> COMPANY: <u>HUMBLE OIL & REFIN. CO.</u> WELL: _____ STATE: <u>TX</u> NO. <u>2</u> LOCATION: <u>1980' FS. & WL SEC. 2 T2S</u> <u>S7E</u> FIELD: <u>PADDOCK</u> COUNTY OR PARISH: <u>LRA</u> STATE: <u>NEW MEXICO</u> DATE: <u>SEPTEMBER 8, 1946</u> </td> <td style="width: 50%; border: none; vertical-align: top; text-align: center;"> COUNTY, TX FIELD OR PADDOCK SURVEY WELL: _____ STATE: <u>TX</u> NO. <u>2</u> COMPANY: <u>HUMBLE OIL & REFIN. CO.</u> </td> </tr> </table>	COMPANY: <u>HUMBLE OIL & REFIN. CO.</u> WELL: _____ STATE: <u>TX</u> NO. <u>2</u> LOCATION: <u>1980' FS. & WL SEC. 2 T2S</u> <u>S7E</u> FIELD: <u>PADDOCK</u> COUNTY OR PARISH: <u>LRA</u> STATE: <u>NEW MEXICO</u> DATE: <u>SEPTEMBER 8, 1946</u>	COUNTY, TX FIELD OR PADDOCK SURVEY WELL: _____ STATE: <u>TX</u> NO. <u>2</u> COMPANY: <u>HUMBLE OIL & REFIN. CO.</u>							
COMPANY: <u>HUMBLE OIL & REFIN. CO.</u> WELL: _____ STATE: <u>TX</u> NO. <u>2</u> LOCATION: <u>1980' FS. & WL SEC. 2 T2S</u> <u>S7E</u> FIELD: <u>PADDOCK</u> COUNTY OR PARISH: <u>LRA</u> STATE: <u>NEW MEXICO</u> DATE: <u>SEPTEMBER 8, 1946</u>	COUNTY, TX FIELD OR PADDOCK SURVEY WELL: _____ STATE: <u>TX</u> NO. <u>2</u> COMPANY: <u>HUMBLE OIL & REFIN. CO.</u>									
WELL RECORD										
Bottom Depth Company: <u>5209</u> ft. Maximum Depth Reached: <u>5205</u> ft. Surveyed From: <u>5205</u> ft. to <u>5500</u> ft. Footage Recorded: <u>1705</u> ft. Well Fluid: <u>OIL</u> Fluid Level: <u>FULL</u> ft.										
CASING RECORD										
<table style="width: 100%; border: none;"> <tr> <td style="width: 30%;">10 3/4 in.</td> <td style="width: 30%;"># from SURFACE to 247 ft.</td> <td style="width: 40%;"></td> </tr> <tr> <td>7 5/8 in.</td> <td># from SURFACE to 2790 ft.</td> <td></td> </tr> <tr> <td>5 1/2 in.</td> <td>15 # from SURFACE to 5205 ft.</td> <td></td> </tr> </table>		10 3/4 in.	# from SURFACE to 247 ft.		7 5/8 in.	# from SURFACE to 2790 ft.		5 1/2 in.	15 # from SURFACE to 5205 ft.	
10 3/4 in.	# from SURFACE to 247 ft.									
7 5/8 in.	# from SURFACE to 2790 ft.									
5 1/2 in.	15 # from SURFACE to 5205 ft.									
REMARKS SCALE: GAMMA RAY CURVE - 274 STANDARD 7.1" DEFLECTION FROM 5205 TO 5500 SCALE: NEUTRON CURVE - 275 STANDARD 6.0" DEFLECTION FROM 5205 TO 5500 PERMANENT DEPTH REFERENCE-DRIVE BUSHING IS 12.7" ABOVE 5 1/2" BRADEN READ PLATE.										
Depths Measured From: <u>DRIVE BUSHING</u> Ordered By: <u>MR. YARBOROUGH</u> Recorded By: <u>HALBERT</u> Witnessed By: <u>MR. YARBOROUGH</u>										
Depth	RADIOACTIVITY INCREASES GAMMA RAY NEUTRON									