



GAMMA RAY/NEUTRON
BHC Acoustilog

LE NO.	COMPANY <u>HANSON OIL CORPORATION</u>			
	WELL <u>LOUISE B. BENSON NO.1</u>			
	FIELD <u>SHUGART</u>			
	COUNTY <u>EDDY</u>	STATE <u>NEW MEXICO</u>		
	LOCATION: <u>2310' FSL & 1650' FEL</u>			
	SEC <u>26</u>	TWP <u>18-S</u>	RGE <u>30-E</u>	Other Services

Permanent Datum <u>G.L.</u>	Elev. <u>3473.8'</u>	KB <u>3483.8'</u>
Log Measured from <u>K.B.</u>	<u>10</u> Ft. Above Permanent Datum	DF <u>3473.8'</u>
Drilling Measured from <u>K.B.</u>		GL <u>3473.8'</u>

Date	<u>1-19-72</u>	CONFIDENTIAL DO NOT RELEASE BEFORE EXAMINER <u>UTZ</u> OIL CONSERVATION COMMISSION BIT NO. <u>5</u> CASE NO. <u>4710</u> Submitted to <u>Hanson Oil Corp.</u> Hearing Date <u>May 5, 1972</u>
Run No.	<u>ONE</u>	
Type Log	<u>BHC/AL/GRN</u>	
Depth-Driller	<u>3520</u>	
Depth-Logger	<u>3532</u>	
Bottom Logged Interval	<u>3530</u>	
Top Logged Interval	<u>SURF</u>	
Type Fluid in Hole	<u>WATER</u>	
Salinity Ppm Cl.		
Density Lb. Gal.		
Level	<u>FULL</u>	
Max Rec. Temp. Deg. F		
Op. Rig Time	<u>3 HRS.</u>	
Recorded By	<u>HOWE</u>	
Witnessed By	<u>MR. HARRINGTON</u>	

Bore Hole Record				Casing Record			
Run No.	Bit	From	To	Size	Wgt.	From	To
1				5 1/2		SURF	T.D.

THIS HEADING AND LOG CONFORMS TO API RECOMMENDED STANDARD PRACTICE RP-31

FOLD HERE ↓