

COUNTY EDDY FIELD KENNEDY FARMS MORROW LOCATION J. H. ANSLEY UNIT #1 WELL J. H. ANSLEY UNIT #1 COMPANY TEXAS PACIFIC OIL	COMPANY TEXAS PACIFIC OIL COMPANY INC.																																																																
	WELL J. H. ANSLEY UNIT #1																																																																
	FIELD KENNEDY FARMS MORROW																																																																
	COUNTY EDDY STATE NEW MEXICO																																																																
LOCATION 660' FNL & 660' FEL		Other Services DLL-MSFL																																																															
API SERIAL NO. 27 17-S 26-E																																																																	
Permanent Datum: G.L. Elev 3318 Log Measured From: K.B. 19 Ft. Above Perm. Datum Drilling Measured From: K.B.		Elev K.B. 3337 D.F. 3336 G.L. 3318																																																															
<table border="1"> <tr> <td>Date</td> <td>12-17-74</td> <td rowspan="10"> BEFORE EXAMINER STAMETS OIL CONSERVATION COMMISSION EXHIBIT NO. 4 CASE NO. 5410 Submitted by T.P. Hearing Date 12-5-75 </td> </tr> <tr> <td>Run No.</td> <td>ONE</td> </tr> <tr> <td>Depth-Driller</td> <td>8806</td> </tr> <tr> <td>Depth-Logger</td> <td>8809</td> </tr> <tr> <td>Btm. Log Interval</td> <td>8808</td> </tr> <tr> <td>Top Log Interval</td> <td>0</td> </tr> <tr> <td>Casing-Driller</td> <td>8 5/8 @ 1500</td> </tr> <tr> <td>Casing-Logger</td> <td>1504</td> </tr> <tr> <td>Bit Size</td> <td>7 7/8</td> </tr> <tr> <td>Type Fluid in Hole</td> <td>KCL MUD</td> </tr> <tr> <td>Dens.</td> <td>9.0</td> <td>36</td> </tr> <tr> <td>pH</td> <td>9</td> <td>9.2 ml</td> </tr> <tr> <td>Source of Sample</td> <td colspan="2">CIRCULATED</td> </tr> <tr> <td>Rm @ Meas. Temp.</td> <td>.232 @ 69 F</td> <td></td> </tr> <tr> <td>Rmf @ Meas. Temp.</td> <td>.188 @ 63 F</td> <td></td> </tr> <tr> <td>Rmc @ Meas. Temp.</td> <td>.348 @ 69 F</td> <td></td> </tr> <tr> <td>Source: Rmf</td> <td>M</td> <td>C</td> </tr> <tr> <td>Rm @ BHT</td> <td>.125 @ 130 F</td> <td></td> </tr> <tr> <td>TIME</td> <td>Circulation Stopped</td> <td>1200</td> </tr> <tr> <td></td> <td>Logger on Bottom</td> <td>1600</td> </tr> <tr> <td></td> <td>Max. Rec Temp.</td> <td>130 F</td> </tr> <tr> <td></td> <td>Equip. Location</td> <td>7732 HOBBS</td> </tr> <tr> <td></td> <td>Recorded By</td> <td>KEMPER-WYANT</td> </tr> <tr> <td></td> <td>Witnessed By Mr.</td> <td>KEYES</td> </tr> </table>			Date	12-17-74	BEFORE EXAMINER STAMETS OIL CONSERVATION COMMISSION EXHIBIT NO. 4 CASE NO. 5410 Submitted by T.P. Hearing Date 12-5-75	Run No.	ONE	Depth-Driller	8806	Depth-Logger	8809	Btm. Log Interval	8808	Top Log Interval	0	Casing-Driller	8 5/8 @ 1500	Casing-Logger	1504	Bit Size	7 7/8	Type Fluid in Hole	KCL MUD	Dens.	9.0	36	pH	9	9.2 ml	Source of Sample	CIRCULATED		Rm @ Meas. Temp.	.232 @ 69 F		Rmf @ Meas. Temp.	.188 @ 63 F		Rmc @ Meas. Temp.	.348 @ 69 F		Source: Rmf	M	C	Rm @ BHT	.125 @ 130 F		TIME	Circulation Stopped	1200		Logger on Bottom	1600		Max. Rec Temp.	130 F		Equip. Location	7732 HOBBS		Recorded By	KEMPER-WYANT		Witnessed By Mr.	KEYES
Date	12-17-74	BEFORE EXAMINER STAMETS OIL CONSERVATION COMMISSION EXHIBIT NO. 4 CASE NO. 5410 Submitted by T.P. Hearing Date 12-5-75																																																															
Run No.	ONE																																																																
Depth-Driller	8806																																																																
Depth-Logger	8809																																																																
Btm. Log Interval	8808																																																																
Top Log Interval	0																																																																
Casing-Driller	8 5/8 @ 1500																																																																
Casing-Logger	1504																																																																
Bit Size	7 7/8																																																																
Type Fluid in Hole	KCL MUD																																																																
Dens.	9.0	36																																																															
pH	9	9.2 ml																																																															
Source of Sample	CIRCULATED																																																																
Rm @ Meas. Temp.	.232 @ 69 F																																																																
Rmf @ Meas. Temp.	.188 @ 63 F																																																																
Rmc @ Meas. Temp.	.348 @ 69 F																																																																
Source: Rmf	M	C																																																															
Rm @ BHT	.125 @ 130 F																																																																
TIME	Circulation Stopped	1200																																																															
	Logger on Bottom	1600																																																															
	Max. Rec Temp.	130 F																																																															
	Equip. Location	7732 HOBBS																																																															
	Recorded By	KEMPER-WYANT																																																															
	Witnessed By Mr.	KEYES																																																															