

Schlumberger

SIMULTANEOUS
COMPENSATED NEUTRON-
FORMATION DENSITY

COUNTY <u>LEA</u> FIELD <u>DRINKARD-GRANITE</u> LOCATION <u>WASH</u> WELL <u>N.G. PENROSE #3</u> COMPANY <u>EXXON COMPANY, U.S.A.</u>	COMPANY <u>EXXON COMPANY, U.S.A.</u>																																																																																																																																																
	WELL <u>N.G. PENROSE #3</u>																																																																																																																																																
	FIELD <u>DRINKARD-GRANITE WASH</u>																																																																																																																																																
	COUNTY <u>LEAH</u> STATE <u>NEW MEXICO</u>																																																																																																																																																
LOCATION <u>1980'FEL, & 1980'FNL</u> API SERIAL NO. <u>13</u> SEC. <u>22-S</u> RANGE <u>37-E</u>			Other Services: <u>DLL</u>																																																																																																																																														
Permanent Datum: <u>G.L.</u> ; Elev.: <u>3334</u> Log Measured From <u>K.B.</u> , <u>12</u> Ft. Above Perm. Datum Drilling Measured From <u>K.B.</u>					Elev.: K.B. <u>3346</u> D.F. <u>3345</u> G.L. <u>3334</u>																																																																																																																																												
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>Date</td><td colspan="5"><u>5-27-75</u></td></tr> <tr> <td>Run No.</td><td colspan="5"><u>ONE</u></td></tr> <tr> <td>Depth-Driller</td><td><u>7500</u></td><td colspan="4" rowspan="2" style="text-align: center; vertical-align: middle;"><u>#4</u></td></tr> <tr> <td>Depth-Logger</td><td><u>7506</u></td></tr> <tr> <td>Btm. Log Interval</td><td><u>7503</u></td><td colspan="4"></td></tr> <tr> <td>Top Log Interval</td><td><u>70</u></td><td colspan="4"></td></tr> <tr> <td>Casing-Driller</td><td><u>8 5/8 @ 1242</u></td><td><u>@</u></td><td><u>@</u></td><td><u>@</u></td><td><u>@</u></td></tr> <tr> <td>Casing-Logger</td><td><u>1242</u></td><td colspan="4"></td></tr> <tr> <td>Bit Size</td><td><u>7 7/8</u></td><td colspan="4"></td></tr> <tr> <td>Type Fluid in Hole</td><td colspan="5"><u>BRINE-STARCH</u></td></tr> <tr> <td>Dens.</td><td><u>10</u></td><td><u>48</u></td><td colspan="3"></td></tr> <tr> <td>pH</td><td><u>9</u></td><td><u>17 ml</u></td><td><u>ml</u></td><td><u>ml</u></td><td><u>ml</u></td></tr> <tr> <td>Source of Sample</td><td colspan="5"><u>CIRC.</u></td></tr> <tr> <td>Rm @ Meas. Temp.</td><td><u>.05 @ 75 °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td></tr> <tr> <td>Rmf @ Meas. Temp.</td><td><u>.04 @ 75 °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td></tr> <tr> <td>Rmc @ Meas. Temp.</td><td><u>.075 @ 75 °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td></tr> <tr> <td>Source: Rmf Rmc</td><td><u>M C</u></td><td colspan="4"></td></tr> <tr> <td>Rm @ BHT</td><td><u>.035 @ 106°F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td><td><u>@ °F</u></td></tr> <tr> <td>TIME Circulation Stopped</td><td><u>1100 5-26</u></td><td colspan="4"></td></tr> <tr> <td>TIME Logger on Bottom</td><td><u>0700 5-27</u></td><td colspan="4"></td></tr> <tr> <td>Max. Rec. Temp.</td><td><u>106 °F</u></td><td><u>°F</u></td><td><u>°F</u></td><td><u>°F</u></td><td><u>°F</u></td></tr> <tr> <td>Equip. Location</td><td><u>7627 HOBBS</u></td><td colspan="4"></td></tr> <tr> <td>Recorded By</td><td colspan="5"><u>LAKE</u></td></tr> <tr> <td>Witnessed By Mr.</td><td colspan="5"><u>JORDAN</u></td></tr> </table>						Date	<u>5-27-75</u>					Run No.	<u>ONE</u>					Depth-Driller	<u>7500</u>	<u>#4</u>				Depth-Logger	<u>7506</u>	Btm. Log Interval	<u>7503</u>					Top Log Interval	<u>70</u>					Casing-Driller	<u>8 5/8 @ 1242</u>	<u>@</u>	<u>@</u>	<u>@</u>	<u>@</u>	Casing-Logger	<u>1242</u>					Bit Size	<u>7 7/8</u>					Type Fluid in Hole	<u>BRINE-STARCH</u>					Dens.	<u>10</u>	<u>48</u>				pH	<u>9</u>	<u>17 ml</u>	<u>ml</u>	<u>ml</u>	<u>ml</u>	Source of Sample	<u>CIRC.</u>					Rm @ Meas. Temp.	<u>.05 @ 75 °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	Rmf @ Meas. Temp.	<u>.04 @ 75 °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	Rmc @ Meas. Temp.	<u>.075 @ 75 °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	Source: Rmf Rmc	<u>M C</u>					Rm @ BHT	<u>.035 @ 106°F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	TIME Circulation Stopped	<u>1100 5-26</u>					TIME Logger on Bottom	<u>0700 5-27</u>					Max. Rec. Temp.	<u>106 °F</u>	<u>°F</u>	<u>°F</u>	<u>°F</u>	<u>°F</u>	Equip. Location	<u>7627 HOBBS</u>					Recorded By	<u>LAKE</u>					Witnessed By Mr.	<u>JORDAN</u>				
Date	<u>5-27-75</u>																																																																																																																																																
Run No.	<u>ONE</u>																																																																																																																																																
Depth-Driller	<u>7500</u>	<u>#4</u>																																																																																																																																															
Depth-Logger	<u>7506</u>																																																																																																																																																
Btm. Log Interval	<u>7503</u>																																																																																																																																																
Top Log Interval	<u>70</u>																																																																																																																																																
Casing-Driller	<u>8 5/8 @ 1242</u>	<u>@</u>	<u>@</u>	<u>@</u>	<u>@</u>																																																																																																																																												
Casing-Logger	<u>1242</u>																																																																																																																																																
Bit Size	<u>7 7/8</u>																																																																																																																																																
Type Fluid in Hole	<u>BRINE-STARCH</u>																																																																																																																																																
Dens.	<u>10</u>	<u>48</u>																																																																																																																																															
pH	<u>9</u>	<u>17 ml</u>	<u>ml</u>	<u>ml</u>	<u>ml</u>																																																																																																																																												
Source of Sample	<u>CIRC.</u>																																																																																																																																																
Rm @ Meas. Temp.	<u>.05 @ 75 °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>																																																																																																																																												
Rmf @ Meas. Temp.	<u>.04 @ 75 °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>																																																																																																																																												
Rmc @ Meas. Temp.	<u>.075 @ 75 °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>																																																																																																																																												
Source: Rmf Rmc	<u>M C</u>																																																																																																																																																
Rm @ BHT	<u>.035 @ 106°F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>	<u>@ °F</u>																																																																																																																																												
TIME Circulation Stopped	<u>1100 5-26</u>																																																																																																																																																
TIME Logger on Bottom	<u>0700 5-27</u>																																																																																																																																																
Max. Rec. Temp.	<u>106 °F</u>	<u>°F</u>	<u>°F</u>	<u>°F</u>	<u>°F</u>																																																																																																																																												
Equip. Location	<u>7627 HOBBS</u>																																																																																																																																																
Recorded By	<u>LAKE</u>																																																																																																																																																
Witnessed By Mr.	<u>JORDAN</u>																																																																																																																																																