

LANE WELLS *constituted*

FILE NO.	COMPANY PHILLIPS PETROLEUM COMPANY	
WELL	SIMS WELL NO. 6	
FIELD	EAST BRUNSON	
COUNTY	LEA	STATE NEW MEXICO
LOCATION:	370' FSL & 330' FWL	
SEC. 24	TWP. 22-S	RGE. 37-E
Permanent Datum	GROUND LEVEL	Elev. 3321
Log Measured from	K. R.	13 ft Above Permanent Datum
Drilling Measured from	K. R.	
Date	1/29/68	
Run No.	ONE	
Depth—Driller	7625	
Depth—Logger	7626	
Bottom Logged Interval	7620	
Top Logged Interval	100	
Casing—Driller	8 5/8" 1137'	
Casing—Logger	1138'	
Bit Size	7 7/8"	
Type Fluid in Hole	LO SOLIDS (ELOSAL & DRISPAQ)	
Density and Viscosity	10 34	
pH and Fluid Loss	6.4 15.2s	
Source of Sample	CIRCULATED	
Rm @ Meas. Temp.	.09 @ 60 F	
Rmf @ Meas. Temp.	.06 @ 60 F	
Rmc @ Meas. Temp.	N.C. @ F	
Source of Rmf and Rmc	MEAS.	
Rm @ BHT	.04 @ 123 F	
Time Since Circ	3 HOURS	
Max Rec Temp Deg. F	193 F	
Equip. No. and Location	1221 HOBBS	
Recorded By	JONIEZ	
Witnessed By	MR. MUELLER	

BEFORE EXAMINER STATES
OIL COMPOSITION OF MENTION

Reproduced By *Phillips* ELECT. LOG NO. *8*

Memphis, Tenn. 37901

REFERENCE W 458P

Submitted By *ELSI* KAUFOR

Hearing Date *3 MAR 76*

24 COMPLETION RECORD

SPUD DATE *1-13-68*

COMP DATE *2-14-68*

DST RECORD

CASING RECORD *8 5/8" 24" 1137'*
4 1/2" 11.6" 7625'

PERFORATING RECORD *East Brunson Ellenburger 7469-7592'*
East Brunson McKee: 7328'-7342'
DRINKARD: 6387' - 7227

ACID FRAC SHOT *Ellenburger: 4000 gal 28% HCL; 2500*
gal 15% HCL; 30,000 gal MOD BRINE
McKee: 1500 gal HF Mud Acid
DRINKARD: 5000 gal 28%, 1500 gal 15% HCL

I.P.

GOR

T.P.