

Dresser Atlas

Dual Cateology

FILE NO

COMPANY INEXCO OIL COMPANYWELL FEDERAL STATE COM. NO. 1-10FIELD UNDESIGNATEDCOUNTY EDDY STATE NEW MEXICO

LOCATION:

1980' FSL & 660' FWL

Other Services

CN/CDL/GRSEC 10TWP 21-SRGE 26-E

Permanent Datum
Log Measured from
Drilling Measured from

GROUND LEVELK. B.23Elev 3249

Ft. Above Permanent Datum

KB 3272DF 3249GL 3249

Date	<u>2-12-77</u>					
Run No	<u>ONE</u>					
Depth—Driller	<u>11100</u>					
Depth—Logger	<u>11096</u>					
Bottom Logged Interval	<u>11095</u>					
Top Logged Interval	<u>SURFACE</u>					
Casing—Driller	<u>8 5/8 @ 2595</u>			<u>@</u>	<u>@</u>	
Casing—Logger	<u>2595</u>					
Bit Size	<u>7 7/8"</u>					
Type Fluid in Hole	<u>SALT MUD</u>					
Density and Viscosity	<u>9.7 45</u>					
pH and Fluid Loss	<u>11 6</u> cc			cc	cc	cc
Source of Sample	<u>PIT</u>					
Rm @ Meas Temp	<u>.046 @ 70 °F</u>			<u>@</u> °F	<u>@</u> °F	<u>@</u> °F
Rmf @ Meas Temp	<u>.037 @ 70 °F</u>			<u>@</u> °F	<u>@</u> °F	<u>@</u> °F
Rmc @ Meas Temp	<u>- @ °F</u>			<u>@</u> °F	<u>@</u> °F	<u>@</u> °F
Source of Rmf and Rmc	<u>MEAS.</u>					
Rm @ BHT	<u>.018 @ 177 °F</u>			<u>@</u> °F	<u>@</u> °F	<u>@</u> °F
Time Since Circ	<u>6 1/2 HOURS</u>					
Max Rec Temp Deg F	<u>177 °F</u>			°F	°F	°F
Equip No. and Location	<u>6123 HOBBS</u>					
Recorded By	<u>HERNDON-MC ATEE</u>					
Witnessed By	<u>CAIN-CONRAD</u>					

Equipment Used

Series No	1221E	1308	1221M
Run No	ONE	ONE	ONE
S.O.	61486	61486	61486
Tool No	31756	32037	31378
Elc No		32021	
Panel No	31427		

THIS HEADING AND LOG CONFORMS TO API RECOMMENDED STANDARD PRACTICE RP 21

FOLD HERE

REMARKS