

Schlumberger

SIMULTANEOUS

COMPENSATED NEUTRON- FORMATION DENSITY

COUNTY LEA FIELD GRAMMA RIDGE MORROW LOCATION WELL GETTY "36" STATE COM #1 COMPANY GETTY OIL COMPANY	COMPANY GETTY OIL COMPANY																																																																																																																																																			
	<i>Appl Ex 2 Ca 6607 & 6608</i>																																																																																																																																																			
	WELL GETTY "36" STATE COM #1																																																																																																																																																			
	FIELD GRAMMA RIDGE MORROW																																																																																																																																																			
COUNTY LEA STATE NEW MEXICO																																																																																																																																																				
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:5%;">LOCATION</td> <td colspan="3">1980' FNL & 1650' FWL</td> <td rowspan="3" style="width:20%;">Other Services: DLL/MSFL CYBERLOOK NGT BHC</td> </tr> <tr> <td>API SERIAL NO.</td> <td>SEC.</td> <td>TWP.</td> <td>RANGE</td> </tr> <tr> <td></td> <td>36</td> <td>21-S</td> <td>34-E</td> </tr> </table>					LOCATION	1980' FNL & 1650' FWL			Other Services: DLL/MSFL CYBERLOOK NGT BHC	API SERIAL NO.	SEC.	TWP.	RANGE		36	21-S	34-E																																																																																																																																			
LOCATION	1980' FNL & 1650' FWL			Other Services: DLL/MSFL CYBERLOOK NGT BHC																																																																																																																																																
API SERIAL NO.	SEC.	TWP.	RANGE																																																																																																																																																	
	36	21-S	34-E																																																																																																																																																	
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:30%;">Permanent Datum: G.L.</td> <td style="width:10%; text-align: center;">3669</td> <td rowspan="3" style="width:20%;">Elev.: K.B. 3692 D.F. G.L. 3669</td> </tr> <tr> <td>Log Measured From K.B.</td> <td style="text-align: center;">23</td> </tr> <tr> <td>Drilling Measured From K.B.</td> <td style="text-align: center;">Ft. Above Perm. Datum</td> </tr> </table>					Permanent Datum: G.L.	3669	Elev.: K.B. 3692 D.F. G.L. 3669	Log Measured From K.B.	23	Drilling Measured From K.B.	Ft. Above Perm. Datum																																																																																																																																									
Permanent Datum: G.L.	3669	Elev.: K.B. 3692 D.F. G.L. 3669																																																																																																																																																		
Log Measured From K.B.	23																																																																																																																																																			
Drilling Measured From K.B.	Ft. Above Perm. Datum																																																																																																																																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:15%;">Date</td> <td style="width:15%;">4-20-79</td> <td style="width:15%;">6-23-79</td> <td style="width:15%;"></td> <td style="width:15%;"></td> <td style="width:15%;"></td> </tr> <tr> <td>Run No.</td> <td>ONE</td> <td>TWO</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Depth-Driller</td> <td>11100</td> <td>13350</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Depth-Logger</td> <td>11114</td> <td>13347</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Btm. Log Interval</td> <td>11113</td> <td>13346</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Top Log Interval</td> <td>SURF</td> <td>CSG</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Casing-Driller</td> <td>9 5/8 @ 5202</td> <td>7" @ 11114</td> <td>@</td> <td>@</td> <td>@</td> </tr> <tr> <td>Casing-Logger</td> <td>5503</td> <td>11114</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Bit Size</td> <td>8 1/2</td> <td>6.125</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Type Fluid in Hole</td> <td>BRINE</td> <td>WEIGHTED BRINE POLYMER KCL</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Dens.</td> <td>9.3</td> <td>28</td> <td>12.9</td> <td>40</td> <td></td> </tr> <tr> <td>pH</td> <td>8.5</td> <td>ml</td> <td>9.5</td> <td>3.2 ml</td> <td>ml</td> </tr> <tr> <td>Source of Sample</td> <td>PIT</td> <td>PIT</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Rm @ Meas. Temp.</td> <td>.055 @ 77 °F</td> <td>.05 @ 89 °F</td> <td>@ °F</td> <td>@ °F</td> <td>@ °F</td> </tr> <tr> <td>Rmf @ Meas. Temp.</td> <td>.055 @ 77 °F</td> <td>.038 @ 89 °F</td> <td>@ °F</td> <td>@ °F</td> <td>@ °F</td> </tr> <tr> <td>Rmc @ Meas. Temp.</td> <td>@ °F</td> <td>.08 @ 89 °F</td> <td>@ °F</td> <td>@ °F</td> <td>@ °F</td> </tr> <tr> <td>Source: Rmf Rmc</td> <td>C</td> <td>M C</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Rm @ BHT</td> <td>.028 @ 154 °F</td> <td>.027 @ 175 °F</td> <td>@ °F</td> <td>@ °F</td> <td>@ °F</td> </tr> <tr> <td>Circulation Stopped</td> <td>1400 4-19</td> <td>1800 6-22</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Logger on Bottom</td> <td>2300 4-19</td> <td>0530 6-23</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Max. Rec. Temp.</td> <td>154 °F</td> <td>175 °F</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Equip. Location</td> <td>8075 HOBBS</td> <td>8069 HOBBS</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Recorded By</td> <td>NEUMAN</td> <td>DANIEL</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Witnessed By Mr.</td> <td>MERCHANT</td> <td>WIPP</td> <td></td> <td></td> <td></td> </tr> </table>					Date	4-20-79	6-23-79				Run No.	ONE	TWO				Depth-Driller	11100	13350				Depth-Logger	11114	13347				Btm. Log Interval	11113	13346				Top Log Interval	SURF	CSG				Casing-Driller	9 5/8 @ 5202	7" @ 11114	@	@	@	Casing-Logger	5503	11114				Bit Size	8 1/2	6.125				Type Fluid in Hole	BRINE	WEIGHTED BRINE POLYMER KCL				Dens.	9.3	28	12.9	40		pH	8.5	ml	9.5	3.2 ml	ml	Source of Sample	PIT	PIT				Rm @ Meas. Temp.	.055 @ 77 °F	.05 @ 89 °F	@ °F	@ °F	@ °F	Rmf @ Meas. Temp.	.055 @ 77 °F	.038 @ 89 °F	@ °F	@ °F	@ °F	Rmc @ Meas. Temp.	@ °F	.08 @ 89 °F	@ °F	@ °F	@ °F	Source: Rmf Rmc	C	M C				Rm @ BHT	.028 @ 154 °F	.027 @ 175 °F	@ °F	@ °F	@ °F	Circulation Stopped	1400 4-19	1800 6-22				Logger on Bottom	2300 4-19	0530 6-23				Max. Rec. Temp.	154 °F	175 °F				Equip. Location	8075 HOBBS	8069 HOBBS				Recorded By	NEUMAN	DANIEL				Witnessed By Mr.	MERCHANT	WIPP			
Date	4-20-79	6-23-79																																																																																																																																																		
Run No.	ONE	TWO																																																																																																																																																		
Depth-Driller	11100	13350																																																																																																																																																		
Depth-Logger	11114	13347																																																																																																																																																		
Btm. Log Interval	11113	13346																																																																																																																																																		
Top Log Interval	SURF	CSG																																																																																																																																																		
Casing-Driller	9 5/8 @ 5202	7" @ 11114	@	@	@																																																																																																																																															
Casing-Logger	5503	11114																																																																																																																																																		
Bit Size	8 1/2	6.125																																																																																																																																																		
Type Fluid in Hole	BRINE	WEIGHTED BRINE POLYMER KCL																																																																																																																																																		
Dens.	9.3	28	12.9	40																																																																																																																																																
pH	8.5	ml	9.5	3.2 ml	ml																																																																																																																																															
Source of Sample	PIT	PIT																																																																																																																																																		
Rm @ Meas. Temp.	.055 @ 77 °F	.05 @ 89 °F	@ °F	@ °F	@ °F																																																																																																																																															
Rmf @ Meas. Temp.	.055 @ 77 °F	.038 @ 89 °F	@ °F	@ °F	@ °F																																																																																																																																															
Rmc @ Meas. Temp.	@ °F	.08 @ 89 °F	@ °F	@ °F	@ °F																																																																																																																																															
Source: Rmf Rmc	C	M C																																																																																																																																																		
Rm @ BHT	.028 @ 154 °F	.027 @ 175 °F	@ °F	@ °F	@ °F																																																																																																																																															
Circulation Stopped	1400 4-19	1800 6-22																																																																																																																																																		
Logger on Bottom	2300 4-19	0530 6-23																																																																																																																																																		
Max. Rec. Temp.	154 °F	175 °F																																																																																																																																																		
Equip. Location	8075 HOBBS	8069 HOBBS																																																																																																																																																		
Recorded By	NEUMAN	DANIEL																																																																																																																																																		
Witnessed By Mr.	MERCHANT	WIPP																																																																																																																																																		