

BENSON-MONTIN-GREER DRILLING CORP.

DRILLING AND COMPLETION HISTORY

WELL NAME Canada Ojitos Unit #22 (F-20)

Location: 1685' FNL 1860' FWL, Section 20, T26N, RLW, Rio Arriba County, New Mexico

Elevation: 7724' GR

Spud: 07/31/81

Drilling Completed: 10/26/81

Well Completed: 10/10/84

Total Depth: 8400' Drilled
8398' Plug Back

Casing:

Surface: 20" Conductor pipe @ 24' with 125 sacks cement
10-3/4" 40.50# J-55 set @ 1039' with 900 sacks cement

Production: 7-5/8" 26.40# & 29.70# N-80 set @ 7219' with 660 sacks cement

Liner: 5-1/2" 20# N-80 7061 - 8396' with 140 sacks cement

Tubing: 2-3/8" EUE set @ 8333'

Logs: Induction Gamma Ray, Induction - SFL, Compensated Neutron - Formation Density

Cores & Drillstem Tests: None

Formation Tops: Log

Nacimiento	surface to 3485'	Niobrara A	7285'
Ojo Alamo	3485'	Niobrara B	7358'
Fruitland	3615'	Niobrara C	7433'
Pictured Cliffs	3813'	Sanostee	7800'
Lewis Shale	3940'	Carlile	7885'
MV Cliff House	5652'	Greenhorn	8100'
Menefee	5712'	Graneros	8180'
Point Lookout	6001'	Dakota	8330'
Mancos	6212'		

Producing Perforations: 8376 - 8384 7 holes .50 OD
8361 - 8365' 4 holes .50 OD
8334 - 8354' 11 holes .50 OD

Treatment: Acidized with 5000 gallons 15% HCl

Initial Potential: 10/10/84 1 BOPD
GOR - 120,000/1

BEFORE EXAMINER CATANACH
OIL CONSERVATION DIVISION

BMG EXHIBIT NO. 2


CASE NO. 9553

BENSON-MONTIN-GREER DRILLING CORP


WELL Canada Ojitos Unit #22 (F-20)

SEC. 20 TOWNSHIP 25N RANGE 1W


STATE NM COUNTY Rio Arriba




7724' GR
20" Conductor .250 wall
set @ 24' with 125 sacks
cement



Satellite 1-1/4" 2.40#
set @ 1039' with 900 sacks
cement




Top 5-1/2" liner
set @ 7051'



7-5/8" 29.7 & 26.4# K-55
set @ 7219'
with 170 sacks 1st stage
490 sacks 2nd stage

Perforations:
8361-8365' 4 holes
8376-8384' 7 holes
8334 - 8354' 11 holes



5-1/2" 17# K-55 liner
7061-8396' with 140 sacks

PBTD 8398'
TD 8400'

