

TYPICAL HOLE PATTERNS
T18S R31E
EDDY CO., NEW MEXICO

Grayburg-San Andres Wells Section 24				
Total Depth	Days on Location	Surface Casing	Inter. Casing	Prod. Casing
4500 Ft.	7	8 5/8" @ 366'	NA	4 1/2" @ T.D.
4500 Ft.	10	8 5/8" @ 687'	NA	4 1/2" @ T.D.
4500 Ft.	10	8 5/8" @ 749'	NA	4 1/2" @ T.D.

Avg. Depth - 4500 Ft.
 Avg. Days - 9.

Delaware Wells Section 13				
Total Depth	Days on Location	Surface Casing	Inter. Casing	Prod. Casing
5410 Ft.	11	8 5/8" @ 353'	NA	5 1/2" @ T.D.
5447 Ft.	12	8 5/8" @ 350'	NA	5 1/2" @ T.D.
5548 Ft.	12	8 5/8" @ 356'	NA	5 1/2" @ T.D.

Avg. Depth - 5468 Ft.
 Avg. Days - 11.6.

Bone Spring Wells Section 2				
Total Depth	Days on Location	Surface Casing	Inter. Casing	Prod. Casing
9025 Ft.	26	13 3/8" @ 358'	8 5/8" @ 2275'	5 1/2" @ T.D.
9040 Ft.	23	13 3/8" @ 359'	8 5/8" @ 2300'	5 1/2" @ T.D.
9092 Ft.	20	13 3/8" @ 356'	8 5/8" @ 2305'	5 1/2" @ T.D.

Avg. Depth - 9052 Ft.
 Avg. Days - 23.

CHEVRON'S 1
 9998