

**JICARILLA Apache 102#10 GALLUP-DAKOTA COMMINGLED
WELLBORE: 890' FNL and 1030' FWL
SEC. 4-T26N-R4W**

AMOCO PRODUCTION COMPANY

SURFACE CASING

Hole size: 13 3/4" to 197'
Casing: 10 3/4" 32.75# H-40
Casing set @ 197' w/140 SX
Top of Cement: Circulate to
Surface

INTERMEDIATE CASING

Hole size: 9 7/8" to 4160'
Casing: 7 5/8" 26.4# J-55
Casing set @ 4160' w/140 SX
Top of Cement: 3500' (est.)

LINER HANGER

Hanger Type: _____
Hanger Top @ _____

(DHC 9-7-77)

BROOKLYN LINER STAMETS
OIL COLLOCATION DIVISION
UTPC

8184 & 8185

Submitted by HERRINGTON

Hearing Date 5-9-84

PERFORATIONS

Gallup: 7664'-7678'

Dakota: 8150'-8345'

Seating Nipple
Perf sub.
Mud Anchor

PRODUCTION LINER

Hole Size: 6 3/4" (Gas Drilled)
Liner: 4 1/2" 10.5# K-55
Liner set @ 8375' w/500 SX
Top of Cement: Circulate (Est.)

PBTD 8360'
TD 8375'

GLE 7177'
KBE 7188'
KB 11'

Rio Arriba County, New Mexico

Field: B.S. Mesa Gallup and Basin Dakota