

**JICARILLA "H" #7 GALLUP-DAKOTA COMMINGLED
WELLBORE; 1450' FSL and 1650' FWL
SEC. 19 - T 26 N - R 4 W**

**UNION TEXAS
PETROLEUM CORP.**

SURFACE CASING

Hole size: 13-3/4" to 325'
Casing: 10-3/4" 32.75# H-40
Casing set @ 323' w/250 SX
Top of cement: Circulate to
Surface

INTERMEDIATE CASING

Hole Size: 9-7/8" to 3360'
Casing: 7-5/8" 26.4# J-55
Casing set @ 3355' w/1048 cu. ft.
Top of Cement: Surface (Calc.)

LINER HANGER

Hanger Type: BOI
Hanger Top @ 3206'

**BEFORE EXAMINER STAMETS
OIL CONSERVATION DIVISION**

UTPC EXHIBIT NO. 3

CASE NO. 8186

Submitted by HERRINGTON

Hearing Date 5-9-84

Seating Nipple
Perf sub
Mud Anchor

PERFORATIONS

Gallup: 6569'-6902'
Dakota: 7400'-7600'

PRODUCTION LINER

Hole Size: 6-3/4" (Gas Drilled)
Liner: 5-1/2" 15.5# J-55
Liner set @ 7689' w/700 cu. ft.
Top of Cement: Circulate (Calc.)

PBTD 7653'
TD 7695'

GLE 6631'
KBE 6642'
KB 11'

**Rio Arriba County, New Mexico
Field: Tapacito Gallup And Basin Dakota**