

0.01 minimum listed when raw data indicated 0.01

EXHIBIT 9. LISTING OF PETROPHYSICAL DATA FOR CORED WELLS IN THE RINCON AREA

WELL ----	INTERVAL -----	DEPTH -----	PERM ----	PORO ----
RINCON UNIT 1				
	G-A1	7363.0	0.01	2.5
	G-A1	7368.0	0.01	3.3
	G-A1	7373.0	0.01	3.1
	G-A1	7378.0	0.01	2.4
	G-A1	7383.0	0.01	2.7
	G-A1	7389.0	0.01	2.5
	G-A2	7394.0	0.01	4.0
	G-A2	7398.0	0.01	1.5
	D-A	7477.5	0.01	3.0
	D-A	7487.5	0.01	2.4
	D-A	7493.5	0.01	1.7
	D-BE	7520.5	0.01	12.1
	D-BE	7525.5	0.01	7.6
	D-BE	7528.0	0.01	9.9
	D-BE	7534.5	0.01	4.2
	D-BE	7535.5	0.01	7.6
	D-BE	7537.0	0.40	11.3
	D-BE	7539.0	0.01	4.2
	D-BE	7541.5	0.01	5.4
	D-BE	7543.5	0.01	6.0
	D-BE	7564.5	0.01	3.4
	D-BE	7567.5	0.01	7.2
	D-BE	7571.0	0.01	4.0
	D-BE	7574.5	0.01	3.3
	D-BE	7578.0	0.01	8.6
	D-BE	7582.0	0.01	6.0
	D-BE	7585.0	0.01	3.4
	D-F	7595.0	0.01	6.9
	D-F	7597.0	0.01	9.9
	D-F	7598.5	0.01	11.6
	D-F	7599.5	0.01	9.0

RINCON UNIT 31

	D-BE	7364.0	0.24	6.9
	D-BE	7366.0	0.24	5.2
	D-BE	7368.0	0.01	10.3
	D-BE	7370.0	0.24	6.2
	D-BE	7372.0	0.24	8.0
	D-BE	7374.0	0.48	7.6
	D-BE	7376.0	0.24	7.4
	D-BE	7383.0	0.24	8.7
	D-BE	7388.0	0.24	6.3
	D-BE	7390.0	0.01	9.1
	D-BE	7392.0	0.01	5.6

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	D-F	7450.0	0.24	4.3
	D-F	7452.0	0.01	5.0
	D-F	7454.0	0.24	4.0
	D-F	7456.0	1.19	8.6

RINCON UNIT 57

G-A1	7183.0	0.01	9.5
G-A1	7185.0	0.01	10.2
G-A1	7187.0	4.03	8.7
G-A1	7189.0	3.56	6.4
G-A1	7191.0	6.35	6.1
G-A1	7193.0	1.11	6.0
G-A1	7195.0	0.38	6.1
G-A1	7197.0	0.13	8.0
G-A1	7199.0	0.30	8.4
G-A1	7201.0	0.21	6.0
G-A1	7203.0	0.38	4.7
G-A1	7205.0	0.13	7.3
G-A1	7207.0	0.38	7.7
G-A1	7211.0	0.21	5.7
G-A1	7212.5	0.38	9.0
G-A1	7214.5	0.04	6.7
G-A1	7217.5	0.04	7.8

RINCON UNIT 127

G-A1	7365.0	0.01	3.8
G-A1	7366.0	0.03	4.4
G-A1	7367.0	0.08	6.9
G-A1	7368.0	0.04	5.7
G-A1	7369.0	0.02	5.2
G-A1	7370.0	0.01	4.8
G-A1	7371.0	0.02	4.4
G-A1	7372.0	0.02	5.0
G-A1	7373.0	0.01	4.4
G-A1	7374.0	0.02	4.0
G-A1	7375.0	0.01	4.2
G-A1	7383.0	0.01	3.9
G-A1	7384.0	0.05	3.7
G-A1	7385.0	0.04	4.3
G-A1	7386.0	0.04	4.9
G-A1	7387.0	0.01	8.1
G-A1	7388.0	0.08	6.7
G-A1	7389.0	0.03	4.6
G-A1	7390.0	0.01	4.6
G-A1	7391.0	0.01	4.5
G-A1	7392.0	0.01	4.2
G-A1	7393.0	0.01	4.2
G-A1	7394.0	0.02	3.8

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	G-A2	7395.0	0.01	3.5
	G-A2	7396.0	0.07	3.7
	G-A2	7397.0	0.02	3.5
	G-A2	7398.0	0.04	3.7
	G-A2	7399.0	0.02	3.8
	G-A2	7400.0	0.01	3.7
	G-A2	7401.0	0.01	4.5
	G-A2	7402.0	0.01	4.3
	G-A2	7403.0	0.01	3.9
	G-A2	7404.0	0.01	2.5
	G-A2	7405.0	0.01	3.8
	G-A2	7406.0	0.01	3.5
	G-A2	7407.0	0.01	3.2
	G-A2	7408.0	0.01	3.4
	G-A2	7409.0	0.01	4.2
	G-A2	7410.0	0.02	3.0
	G-A2	7411.0	0.01	2.8
	G-A2	7412.0	0.01	5.0
	G-A2	7413.0	0.01	3.3
	G-A2	7414.0	0.01	2.7
	G-A2	7415.0	0.01	3.1
	G-A2	7416.0	0.01	3.2
	G-A2	7417.0	0.01	4.3
	G-A2	7418.0	0.01	3.7
	G-A2	7419.0	0.01	3.4
	G-A2	7420.0	0.01	3.9
	D-A	7487.0	0.01	3.8
	D-A	7488.0	0.06	6.9
	D-A	7489.0	0.06	11.1
	D-A	7490.0	0.05	11.5
	D-A	7491.0	0.06	10.6
	D-A	7492.0	0.08	10.4
	D-A	7493.0	0.04	9.9
	D-A	7494.0	0.05	8.0
	D-A	7495.0	0.04	9.4
	D-A	7496.0	0.04	9.4
	D-A	7497.0	0.04	8.8
	D-A	7498.0	0.02	6.6
	D-A	7499.0	0.01	5.0
	D-A	7500.0	0.01	4.7
	D-A	7501.0	0.02	6.1
	D-A	7502.0	0.01	4.9
	D-A	7503.0	0.01	5.4
	D-A	7504.0	0.06	5.9
	D-A	7505.0	0.01	4.6
	D-A	7506.0	0.01	4.5
	D-A	7507.0	0.01	3.8
	D-A	7508.0	0.01	3.9
	D-A	7524.0	0.02	2.9
	D-A	7525.0	0.03	4.9

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	D-BE	7526.0	0.01	2.5
	D-BE	7527.0	0.01	3.9
	D-BE	7528.0	0.01	4.3
	D-BE	7531.0	0.02	6.5
	D-BE	7532.0	0.02	6.9
	D-BE	7533.0	0.02	5.1
	D-BE	7534.0	0.01	3.8
	D-BE	7535.0	0.02	0.8
	D-BE	7536.0	0.01	3.7
	D-BE	7541.0	0.05	6.4
	D-BE	7542.0	0.08	6.3
	D-BE	7543.0	0.05	6.2
	D-BE	7544.0	0.02	6.2
	D-BE	7545.0	0.01	4.1
	D-BE	7546.0	0.01	3.6
	D-BE	7547.0	0.01	2.7
	D-BE	7548.0	0.01	4.9
	D-BE	7549.0	0.01	3.3
	D-BE	7550.0	0.01	1.9
	D-BE	7551.0	0.02	4.0
	D-BE	7552.0	0.01	2.0
	D-BE	7554.0	0.01	2.2
	D-BE	7555.0	0.06	5.1
	D-BE	7556.0	0.02	5.5
	D-BE	7557.0	0.02	6.1
	D-BE	7558.0	0.01	1.6
	D-BE	7559.0	0.01	2.1
	D-BE	7560.0	0.01	2.1
	D-BE	7561.0	0.01	1.9
	D-BE	7562.0	0.01	2.6
	D-BE	7563.0	0.01	1.4
	D-BE	7564.0	0.01	1.0
	D-BE	7565.0	0.01	3.4
	D-BE	7566.0	0.01	1.3
	D-BE	7567.0	0.01	3.6
	D-BE	7568.0	0.01	3.2
	D-BE	7569.0	0.01	3.4
	D-BE	7570.0	0.01	3.0
	D-BE	7571.0	0.04	3.7
	D-BE	7572.0	0.01	2.1
	D-BE	7573.0	0.01	2.1
	D-BE	7574.0	0.05	4.2
	D-BE	7575.0	0.01	2.6
	D-BE	7576.0	0.01	2.7
	D-BE	7577.0	0.24	2.2
	D-BE	7578.0	0.01	2.9
	D-BE	7579.0	0.01	2.6
	D-BE	7580.0	0.01	2.5
	D-BE	7581.0	0.02	1.6
	D-BE	7582.0	0.01	1.7
	D-BE	7583.0	0.01	1.2

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	D-BE	7584.0	0.06	3.1
	D-BE	7585.0	0.01	2.9
	D-BE	7586.0	0.01	1.6
	D-BE	7587.0	0.01	4.5
	D-BE	7588.0	0.01	3.8
	D-BE	7589.0	0.01	2.5
	D-BE	7590.0	0.01	2.4
	D-BE	7591.0	0.01	1.5
	D-BE	7592.0	0.10	0.8
	D-BE	7608.0	0.01	2.8
	D-BE	7609.0	0.01	2.4
	D-BE	7610.0	0.02	2.8
	D-BE	7611.0	0.71	4.1
	D-BE	7612.0	0.08	4.0
	D-BE	7613.0	0.03	6.3
	D-BE	7614.0	0.08	4.5
	D-F	7615.0	0.02	3.9
	D-F	7616.0	0.12	7.7
	D-F	7617.0	0.01	3.7
	D-F	7618.0	0.04	4.3

RINCON UNIT 136

G-A1	7365.0	0.06	7.9
G-A1	7366.0	0.05	7.3
G-A1	7367.0	0.10	5.9
G-A1	7368.0	0.11	4.7
G-A1	7369.0	0.02	5.6
G-A1	7370.0	0.37	6.0
G-A1	7371.0	0.06	4.8
G-A1	7372.0	0.08	4.9
G-A1	7373.0	0.03	6.5
G-A1	7374.0	1.98	5.2
G-A1	7375.0	0.12	6.7
G-A1	7376.0	0.10	6.7
G-A1	7377.0	0.03	3.0
G-A1	7378.0	0.04	6.3
G-A1	7379.0	0.03	2.8
G-A1	7380.0	0.19	6.1
G-A1	7381.0	0.03	6.2
G-A1	7382.0	0.05	6.3
G-A1	7383.0	0.04	5.9
G-A1	7384.0	0.18	6.0
G-A1	7385.0	0.03	8.0
G-A1	7386.0	0.03	8.2
G-A1	7387.0	0.04	7.1
G-A1	7388.0	0.04	8.8
G-A1	7389.0	0.02	6.8
G-A1	7390.0	0.03	8.4
G-A1	7391.0	0.07	9.5
G-A1	7392.0	0.10	12.6

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	G-A1	7393.0	0.05	11.0
	G-A1	7394.0	0.04	8.8
	G-A1	7395.0	0.03	7.4
	G-A1	7396.0	0.01	3.7
	G-A1	7397.0	0.01	1.4
	G-A1	7398.0	0.13	6.1
	G-A1	7399.0	0.03	6.5
	G-A1	7400.0	0.09	6.4
	G-A1	7401.0	0.03	4.1
	G-A1	7402.0	0.02	3.8
	G-A2	7403.0	0.02	6.9
	G-A2	7404.0	0.03	7.0
	G-A2	7405.0	0.02	7.4
	G-A2	7406.0	0.01	6.6
	G-A2	7407.0	0.03	8.4
	G-A2	7408.0	0.08	13.2
	G-A2	7409.0	0.04	10.5
	G-A2	7410.0	0.07	13.0
	G-A2	7411.0	0.08	13.2
	G-A2	7412.0	0.05	11.6
	G-A2	7413.0	0.03	8.7
	G-A2	7414.0	0.17	10.3
	G-A2	7415.0	0.03	5.3
	G-A2	7416.0	0.02	4.1
	G-A2	7417.0	0.04	6.1
	G-A2	7418.0	0.04	7.4
	G-A2	7419.0	0.03	6.6
	G-A2	7420.0	0.03	7.6
	G-A2	7421.0	0.02	7.2
	G-A2	7422.0	0.02	5.8
	G-A2	7423.0	0.01	6.8
	G-B	7486.0	0.01	4.8
	G-B	7487.0	0.01	6.1
	D-A	7505.0	0.08	12.2
	D-A	7506.0	0.10	13.5
	D-A	7507.0	1.11	12.8
	D-A	7508.0	0.08	12.5
	D-A	7509.0	0.05	11.4
	D-A	7510.0	0.07	10.7
	D-A	7511.0	0.08	12.5
	D-A	7512.0	0.18	11.6
	D-A	7513.0	0.08	12.7
	D-A	7514.0	0.08	12.8
	D-A	7515.0	0.06	12.4
	D-A	7516.0	0.04	10.5
	D-A	7517.0	0.03	6.6
	D-A	7518.0	0.03	6.6
	D-A	7519.0	0.03	9.5
	D-A	7520.0	0.02	9.8
	D-A	7521.0	0.02	11.7
	D-A	7522.0	0.03	12.1

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	D-A	7523.0	0.05	10.9
	D-A	7524.0	0.03	8.9
	D-A	7525.0	0.02	6.4
	D-A	7526.0	0.02	7.7
	D-A	7527.0	0.05	7.5
	D-BE	7539.0	0.05	7.7
	D-BE	7540.0	0.03	7.5
	D-BE	7541.0	0.02	6.1
	D-BE	7542.0	0.03	6.1
	D-BE	7543.0	0.03	8.1
	D-BE	7544.0	0.52	8.1
	D-BE	7546.0	0.04	6.9
	D-BE	7547.0	0.03	7.1
	D-BE	7548.0	0.08	7.2
	D-BE	7549.0	0.02	4.6
	D-BE	7550.0	0.04	9.1
	D-BE	7551.0	0.08	11.8
	D-BE	7552.0	0.34	7.5
	D-BE	7553.0	0.04	7.1
	D-BE	7554.0	1.48	7.6
	D-BE	7555.0	0.07	6.7
	D-BE	7556.0	0.05	5.0
	D-BE	7557.0	0.33	6.9
	D-BE	7558.0	0.02	4.8
	D-BE	7562.0	0.03	8.1
	D-BE	7563.0	0.01	5.8
	D-BE	7564.0	0.02	6.0
	D-BE	7565.0	1.08	3.6
	D-BE	7566.0	0.03	7.1
	D-BE	7567.0	0.09	4.5
	D-BE	7568.0	0.02	4.7
	D-BE	7569.0	0.08	6.7
	D-BE	7570.0	0.02	4.6
	D-BE	7571.0	2.03	3.5
	D-BE	7572.0	0.01	3.1
	D-BE	7573.0	0.03	2.5
	D-BE	7574.0	0.04	1.5
	D-BE	7575.0	0.06	6.2
	D-BE	7576.0	0.03	7.7
	D-BE	7577.0	0.05	4.1
	D-BE	7578.0	0.07	4.9
	D-BE	7579.0	0.01	4.5
	D-BE	7580.0	0.02	5.4
	D-BE	7581.0	0.04	4.3
	D-BE	7582.0	0.04	8.7
	D-BE	7590.0	0.03	5.0
	D-BE	7591.0	1.08	4.5
	D-BE	7592.0	0.08	4.3
	D-BE	7593.0	0.01	6.7
	D-BE	7594.0	0.02	5.9
	D-BE	7595.0	0.01	3.8

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	D-F	7610.0	0.03	2.2
	D-F	7615.0	0.28	6.7
	D-F	7616.0	0.16	7.1
	D-F	7623.0	0.04	4.6
	D-F	7624.0	0.03	4.4
	D-F	7625.0	0.07	7.4
	D-F	7626.0	0.02	4.5
	D-F	7627.0	0.06	6.4
	D-F	7628.0	1.58	8.1

RINCON UNIT 159

G-A1	7444.0	0.01	1.8
G-A1	7445.0	0.72	3.5
G-A1	7446.0	0.21	4.4
G-A1	7447.0	0.03	3.4
G-A1	7448.0	0.01	4.1
G-A1	7449.0	0.06	5.6
G-A1	7450.0	0.09	4.5
G-A1	7451.0	0.08	3.3
G-A1	7452.0	0.01	4.1
G-A1	7453.0	0.01	4.2
G-A1	7454.0	0.01	4.9
G-A1	7455.0	0.01	3.9
G-A1	7456.0	0.01	4.6
G-A1	7457.0	0.01	5.0
G-A1	7458.0	0.01	5.1
G-A1	7459.0	0.01	5.4
G-A1	7460.0	0.01	5.2
G-A1	7461.0	0.01	5.0
G-A1	7462.0	0.02	3.5
G-A1	7463.0	0.01	3.6
G-A1	7464.0	0.01	3.2
G-A1	7465.0	0.01	3.6
G-A1	7466.0	0.01	2.7
G-A1	7467.0	0.01	6.8
G-A1	7468.0	0.01	5.0
G-A1	7469.0	0.02	5.4
G-A1	7470.0	0.01	4.4
G-A1	7471.0	0.01	4.0
G-A1	7472.0	0.52	4.3
G-A1	7473.0	0.01	4.2
G-A1	7474.0	0.01	4.0
G-A1	7475.0	0.01	6.3
G-A1	7476.0	0.01	7.1
G-A1	7477.0	0.01	7.0
G-A2	7478.0	0.01	3.9
G-A2	7479.0	0.01	2.9
G-A2	7480.0	0.02	2.4
G-A2	7481.0	0.01	4.9
G-A2	7482.0	0.01	5.0
G-A2	7484.0	0.02	1.7

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	G-A2	7485.0	0.01	2.8
	G-A2	7486.0	0.01	2.9
	G-A2	7487.0	0.01	3.1
	G-A2	7488.0	0.07	3.3
	G-A2	7489.0	0.01	2.6
	G-A2	7490.0	0.01	3.4
	G-A2	7491.0	0.01	2.9
	G-A2	7492.0	0.06	3.0
	G-A2	7493.0	0.01	3.5
	G-A2	7494.0	0.01	3.3
	G-A2	7495.0	0.01	2.8
	G-A2	7496.0	0.01	2.4
	G-A2	7497.0	0.01	2.8
	G-A2	7498.0	0.01	2.4
	G-A2	7499.0	0.01	2.4
	G-A2	7500.0	0.01	1.8
	G-A2	7501.0	0.01	3.1
	G-A2	7502.0	0.01	3.2
	G-A2	7503.0	0.01	3.2
	G-A2	7504.0	0.01	2.2
	G-A2	7505.0	0.01	3.0
	G-A2	7506.0	0.01	2.9
	G-A2	7507.0	0.01	2.6
	G-A2	7508.0	0.01	3.1
	G-A2	7509.0	0.01	3.3
	G-A2	7510.0	0.01	4.2
	G-A2	7511.0	0.01	3.4
	G-B	7540.0	0.01	4.2
	G-B	7542.0	0.07	2.9
	G-B	7544.0	0.01	3.5
	G-B	7546.0	0.01	4.4
	G-B	7550.0	0.01	2.2
	G-B	7553.0	0.01	3.0
	G-B	7555.0	0.01	3.2
	G-B	7556.0	0.01	3.0
	G-B	7557.0	0.01	2.8
	G-B	7558.0	0.01	1.8
	G-B	7559.0	0.01	2.7
	G-B	7560.0	0.01	3.3
	D-A	7572.0	0.01	3.7
	D-A	7573.0	0.07	10.0
	D-A	7574.0	0.27	10.3
	D-A	7575.0	0.07	11.1
	D-A	7576.0	0.05	9.5
	D-A	7577.0	0.06	8.7
	D-A	7578.0	0.04	10.9
	D-A	7579.0	0.32	9.2
	D-A	7580.0	0.05	8.3
	D-A	7581.0	0.01	5.7
	D-A	7582.0	0.01	5.3
	D-A	7583.0	0.01	5.8

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	D-A	7584.0	0.01	4.6
	D-A	7585.0	0.01	5.0
	D-A	7586.0	0.01	4.5
	D-A	7587.0	0.07	5.4
	D-A	7588.0	0.03	4.8
	D-A	7589.0	0.01	4.3
	D-A	7590.0	0.01	4.0
	D-A	7591.0	0.01	3.9
	D-A	7592.0	0.01	3.9
	D-A	7593.0	0.01	3.9
	D-A	7594.0	0.01	3.4
	D-A	7595.0	0.01	3.5
	D-A	7596.0	0.01	4.7
	D-A	7597.0	0.01	2.6
	D-A	7599.0	0.01	1.2
	D-BE	7605.0	0.07	3.7
	D-BE	7606.0	0.05	4.6
	D-BE	7607.0	0.01	2.9
	D-BE	7608.0	0.10	4.8
	D-BE	7609.0	0.06	5.3
	D-BE	7610.0	0.05	4.2
	D-BE	7611.0	0.01	1.7
	D-BE	7612.0	0.01	0.9
	D-BE	7613.0	0.01	4.1
	D-BE	7614.0	0.02	3.9
	D-BE	7616.0	0.01	3.0
	D-BE	7617.0	0.06	3.3
	D-BE	7618.0	0.01	1.6
	D-BE	7619.0	0.01	2.0
	D-BE	7620.0	0.01	2.6
	D-BE	7621.0	0.01	2.2
	D-BE	7622.0	0.03	2.9
	D-BE	7623.0	0.01	3.6
	D-BE	7624.0	0.13	6.3
	D-BE	7625.0	0.03	5.2
	D-BE	7626.0	0.01	2.5
	D-BE	7627.0	0.04	2.7
	D-BE	7629.0	0.01	2.6
	D-BE	7630.0	0.01	2.7
	D-BE	7631.0	0.01	0.9
	D-BE	7632.0	0.01	0.7
	D-BE	7633.0	0.01	0.9
	D-BE	7634.0	0.01	1.2
	D-BE	7635.0	0.01	0.7
	D-BE	7636.0	0.01	1.7
	D-BE	7637.0	0.01	2.2
	D-BE	7638.0	0.01	2.2
	D-BE	7639.0	0.01	3.3
	D-BE	7640.0	0.01	3.1
	D-BE	7641.0	0.02	4.2
	D-BE	7642.0	0.01	2.7

EXHIBIT 9. . cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	D-BE	7643.0	0.01	2.5
	D-BE	7645.0	0.01	1.1
	D-BE	7646.0	0.01	1.1
	D-BE	7647.0	0.01	3.2
	D-BE	7648.0	0.01	1.4
	D-BE	7649.0	0.01	1.1
	D-BE	7650.0	0.01	4.1
	D-BE	7651.0	0.01	3.8
	D-BE	7652.0	0.01	3.5
	D-BE	7656.0	0.01	3.0
	D-BE	7657.0	0.02	7.0
	D-BE	7658.0	0.01	9.0
	D-BE	7659.0	0.03	6.3
	D-BE	7660.0	0.01	4.1
	D-BE	7661.0	0.01	2.7
	D-BE	7662.0	0.01	2.4
	D-BE	7664.0	0.03	4.1
	D-BE	7665.0	0.01	5.2
	D-BE	7666.0	0.02	3.7
	D-BE	7667.0	0.05	6.2
	D-BE	7668.0	0.02	6.0
	D-BE	7669.0	0.05	5.4
	D-F	7681.0	0.21	3.1
	D-F	7682.0	0.01	3.1
	D-F	7683.0	0.10	3.3
	D-F	7684.0	0.01	2.5
	D-F	7685.0	0.01	1.3
	D-F	7686.0	0.01	2.8
	D-F	7687.0	0.10	2.0
	D-F	7688.0	0.01	2.3
	D-F	7689.0	0.10	2.1
	D-F	7690.0	0.01	2.4
	D-F	7691.0	0.01	2.1
	D-F	7692.0	0.01	2.0
	D-F	7693.0	0.01	4.0
	D-F	7694.0	0.09	2.3
	D-F	7695.0	0.01	3.2

HARVEY A 3

	G-B	7194.0	0.04	4.4
	G-B	7195.0	0.02	4.7
	G-B	7196.0	0.01	4.1
	G-B	7197.0	0.02	4.4
	G-B	7198.0	0.04	4.5
	G-B	7199.0	0.02	3.9
	G-B	7226.0	0.01	5.3
	D-A	7232.0	0.02	3.9
	D-A	7233.0	0.02	5.4
	D-A	7234.0	0.88	8.2
	D-A	7235.0	0.08	9.7

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	D-A	7236.0	0.10	9.0
	D-A	7237.0	0.04	9.2
	D-A	7238.0	0.04	7.3
	D-A	7239.0	0.05	10.4
	D-A	7240.0	0.04	8.4
	D-A	7241.0	0.01	6.0
	D-A	7242.0	0.04	6.6
	D-A	7243.0	0.04	5.7
	D-A	7244.0	0.03	5.2
	D-A	7245.0	0.02	4.9
	D-A	7246.0	0.02	4.3
	D-A	7247.0	0.03	5.7
	D-A	7248.0	0.05	5.9
	D-A	7249.0	0.06	5.4
	D-A	7250.0	0.02	4.9
	D-A	7251.0	0.03	5.4
	D-BE	7261.0	0.01	5.1
	D-BE	7262.0	0.01	5.1
	D-BE	7263.0	0.01	5.2
	D-BE	7264.0	0.01	5.9
	D-BE	7267.0	0.01	4.0
	D-BE	7268.0	0.01	5.1
	D-BE	7269.0	0.01	4.4
	D-BE	7270.0	0.08	4.7
	D-BE	7273.0	0.02	5.5
	D-BE	7274.0	0.01	3.9
	D-BE	7275.0	0.01	2.9
	D-BE	7276.0	0.01	3.9
	D-BE	7283.0	0.01	3.6
	D-BE	7284.0	0.01	4.3
	D-BE	7285.0	0.01	3.1
	D-BE	7286.0	0.04	3.9
	D-BE	7287.0	0.01	2.6
	D-BE	7288.0	0.01	4.2
	D-BE	7289.0	0.01	3.8
	D-BE	7295.0	0.01	3.5
	D-BE	7296.0	0.01	2.9
	D-BE	7299.0	0.06	5.8
	D-BE	7300.0	0.04	10.8
	D-BE	7301.0	0.02	11.2
	D-BE	7302.0	0.02	11.3
	D-BE	7303.0	0.01	6.7
	D-BE	7304.0	0.01	6.8
	D-BE	7305.0	0.01	5.2
	D-BE	7306.0	0.01	4.4
	D-BE	7307.0	0.01	4.9
	D-BE	7308.0	0.01	2.9
	D-BE	7309.0	0.01	2.2
	D-BE	7310.0	0.01	3.7
	D-BE	7319.0	0.01	4.3
	D-BE	7320.0	0.01	2.8

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	D-BE	7321.0	0.01	4.3
	D-BE	7322.0	0.01	3.9
	D-BE	7323.0	0.03	8.2
	D-BE	7324.0	0.13	6.8
	D-BE	7325.0	0.08	6.9
	D-BE	7326.0	0.03	5.4
	D-BE	7327.0	0.05	7.7
	D-BE	7332.0	0.14	7.8
	D-BE	7333.0	0.02	3.4
	D-BE	7334.0	0.01	11.4
	D-BE	7337.0	0.01	4.0
	D-BE	7338.0	0.03	6.7
	D-BE	7339.0	0.01	5.0
	D-BE	7340.0	0.01	4.8
	D-BE	7341.0	0.01	2.9
	D-BE	7343.0	0.04	9.8
	D-BE	7344.0	0.04	6.6
	D-BE	7345.0	0.04	9.6
	D-BE	7346.0	0.06	10.3
	D-BE	7347.0	0.02	7.6
	D-BE	7348.0	0.04	11.0
	D-BE	7349.0	0.08	10.1
	D-BE	7350.0	0.12	11.4
	D-BE	7351.0	0.05	8.6
	D-BE	7352.0	0.09	11.4
	D-BE	7353.0	0.01	5.9

SAN JUAN 28-6 UNIT 98

	G-A1	7286.0	0.01	3.7
	G-A1	7287.0	0.01	3.1
	G-A1	7288.0	0.01	4.1
	G-A1	7289.0	0.01	3.4
	G-A1	7290.0	0.01	3.2
	G-A1	7291.0	0.01	3.0
	G-A1	7292.0	0.01	3.7
	G-A1	7293.0	0.01	3.3
	G-A1	7294.0	0.01	3.9
	G-A1	7295.0	0.01	3.5
	G-A1	7296.0	0.01	3.1
	G-A1	7297.0	0.01	3.5
	G-A1	7298.0	0.01	3.2
	G-A1	7299.0	0.01	3.2
	G-A1	7300.0	0.01	3.1
	G-A1	7301.0	0.01	2.0
	G-A1	7302.0	0.01	2.0
	G-A1	7303.0	0.01	3.8
	G-A1	7304.0	0.01	4.2
	G-A1	7305.0	0.01	4.4
	G-A1	7306.0	0.01	4.3
	G-A1	7307.0	0.01	4.0

EXHIBIT 9. cont.

WELL	INTERVAL	DEPTH	PERM	PORO
-----	-----	-----	-----	-----
	G-A1	7308.0	0.02	4.1
	G-A2	7309.0	0.01	4.0
	G-A2	7310.0	0.01	3.4
	G-A2	7311.0	0.01	1.9
	G-A2	7312.0	0.01	2.1
	G-A2	7313.0	0.01	3.5
	G-A2	7314.0	0.01	3.0
	G-A2	7315.0	0.01	1.6
	G-A2	7316.0	0.01	2.9
	G-A2	7317.0	0.01	2.6
	G-A2	7318.0	0.01	2.8
	G-A2	1319.0	0.01	3.1
	G-A2	7320.0	0.01	3.0
	G-A2	7321.0	0.01	2.9
	G-A2	7322.0	0.01	4.3
	G-A2	7323.0	0.01	3.1
	G-A2	7324.0	0.01	3.1
	G-A2	7325.0	0.01	3.1
	G-A2	7326.0	0.01	3.6
	G-A2	7327.0	0.01	3.2
	G-A2	7328.0	0.01	3.2
	G-A2	7329.0	0.01	2.6
	G-A2	7330.0	0.01	3.4
	G-A2	7331.0	0.02	2.6
	G-A2	7332.0	0.01	2.8
	G-A2	7333.0	0.01	2.9
	G-A2	7334.0	0.01	3.4
	G-A2	7335.0	0.01	2.8
	G-A2	7336.0	0.01	3.1
	G-B	7392.0	0.01	2.9
	G-B	7395.0	0.01	3.1
	G-B	7397.0	0.01	1.8
	D-A	7408.0	0.01	1.4
	D-A	7409.0	0.01	1.8
	D-A	7410.0	0.01	4.1
	D-A	7411.0	0.02	7.5
	D-A	7412.0	0.01	6.9
	D-A	7413.0	0.01	8.3
	D-A	7414.0	0.01	7.2
	D-A	7415.0	0.01	5.9
	D-A	7416.0	0.01	4.4
	D-A	7417.0	0.01	2.8
	D-A	7418.0	0.01	3.7
	D-A	7419.0	0.02	5.2
	D-A	7420.0	0.01	6.9
	D-A	7421.0	0.01	6.6
	D-A	7422.0	0.03	4.7
	D-A	7423.0	0.01	2.9
	D-A	7424.0	0.01	2.4
	D-A	7425.0	0.01	4.5
	D-A	7426.0	0.01	3.2

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
	D-A	7427.0	0.01	6.0
	D-A	7428.0	0.01	4.3
	D-A	7429.0	0.01	3.9
	D-A	7430.0	0.02	2.9
	D-A	7431.0	0.01	3.2
	D-A	7432.0	0.01	4.1
	D-A	7433.0	0.01	3.0
	D-A	7434.0	0.01	3.4
	D-A	7435.0	0.39	4.5
	D-A	7436.0	0.01	3.6
	D-A	7437.0	0.01	4.8
	D-A	7438.0	0.01	4.6
	D-A	7439.0	0.01	4.5
	D-A	7440.0	0.01	4.9
	D-A	7441.0	0.01	4.3
	D-A	7442.0	0.01	3.1
	D-A	7443.0	0.01	1.8
	D-BE	7448.0	0.01	2.5
	D-BE	7449.0	0.01	1.3
	D-BE	7450.0	0.01	3.7
	D-BE	9451.0	0.01	2.0
	D-BE	7452.0	0.01	2.8
	D-BE	7453.0	0.01	4.2
	D-BE	7454.0	0.01	3.7
	D-BE	7455.0	0.01	1.1
	D-BE	7456.0	0.01	1.7
	D-BE	7457.0	0.01	2.4
	D-BE	7461.0	0.02	4.4
	D-BE	7462.0	0.01	3.6
	D-BE	7463.0	0.01	1.2
	D-BE	7464.0	0.01	1.0
	D-BE	7465.0	0.01	1.2
	D-BE	7466.0	0.01	1.0
	D-BE	7467.0	0.01	1.2
	D-BE	7474.0	0.01	1.9
	D-BE	7475.0	0.01	0.8
	D-BE	7476.0	0.01	1.2
	D-BE	7477.0	0.01	1.7
	D-BE	7478.0	0.01	1.5
	D-BE	7479.0	0.01	1.2
	D-BE	7480.0	0.02	1.3
	D-BE	7481.0	0.02	2.3
	D-BE	7482.0	0.01	1.2
	D-BE	7483.0	0.01	1.3
	D-BE	7484.0	0.02	1.8
	D-BE	7485.0	0.01	1.8
	D-BE	7486.0	0.02	2.4
	D-BE	7489.0	0.01	0.6
	D-BE	7491.0	0.07	1.4

EXHIBIT 9. cont.

WELL -----	INTERVAL -----	DEPTH -----	PERM -----	PORO -----
SAN JUAN 28-7 UNIT 109				
	G-B	7315.0	0.01	5.3
	G-B	7316.0	0.01	3.1
	G-B	7317.0	0.01	4.1
	G-B	7318.0	0.01	5.8
	G-B	7319.0	0.01	5.4
	G-B	7320.0	0.01	4.6
	G-B	7321.0	0.01	6.1
	G-B	7322.0	0.01	6.4
	G-B	7323.0	0.01	4.6
	G-B	7324.0	0.01	5.4
	G-B	7325.0	0.01	5.5
	G-B	7326.0	0.01	4.7
	G-B	7327.0	0.03	5.6
	G-B	7328.0	0.01	4.0
	D-A	7358.0	0.01	5.0
	D-A	7359.0	0.01	3.7
	D-A	7360.0	0.01	4.4
	D-A	7361.0	0.03	6.5
	D-A	7362.0	0.02	8.8
	D-A	7363.0	0.09	10.5
	D-A	7364.0	0.22	9.7
	D-A	7365.0	0.10	9.9
	D-A	7366.0	0.03	8.9
	D-A	7367.0	0.01	7.0
	D-A	7368.0	0.08	5.1
	D-A	7369.0	0.02	4.7
	D-A	7370.0	0.04	5.6
	D-A	7371.0	0.02	5.2
	D-A	7372.0	0.06	5.4
	D-A	7373.0	0.01	4.5
	D-A	7374.0	0.08	4.8
	D-A	7375.0	0.04	5.8
	D-A	7376.0	0.02	5.5
	D-BE	7377.0	0.01	4.4
	D-BE	7396.0	0.05	4.7
	D-BE	7397.0	0.05	3.1
	D-BE	7398.0	0.01	3.2
	D-BE	7399.0	0.01	3.2
	D-BE	7400.0	0.08	5.0
	D-BE	7401.0	0.01	2.1
	D-BE	7402.0	0.01	3.9
	D-BE	7410.0	0.01	1.4
	D-BE	7411.0	0.01	3.5
	D-BE	7416.0	0.01	1.1
	D-BE	7423.0	0.01	0.9
	D-BE	7431.0	0.01	4.6
	D-BE	7432.0	0.10	6.1
	D-BE	7433.0	0.01	3.7
	D-BE	7434.0	0.01	5.2
	D-BE	7435.0	0.02	4.4

EXHIBIT 9. cont.

WELL	INTERVAL	DEPTH	PERM	PORO
	D-F	7447.0	0.02	3.8
	D-F	7448.0	0.01	3.2
	D-F	7449.0	0.03	4.2
	D-F	7450.0	0.03	2.5
	D-F	7452.0	0.04	5.0
	D-F	7453.0	0.01	5.4
	D-F	7454.0	0.01	5.2

Explanation:

Stratigraphic Unit Abbreviations:

G-A1 = Graneros Formation, A1 Interval
G-A2 = Graneros Formation, A2 Interval
G-B = Graneros Formation, B Interval
D-A = Dakota Formation, A Interval
D-BE = Dakota Formation, B through E Interval
D-F = Dakota Formation, F Interval

All depth values are in feet.

Perm refers to horizontal permeability in millidarcies as determined at laboratory conditions.

Poro refers to porosity in percent.

NOTE: Permeability values listed as zero in Exhibit 8 are listed as 0.01 md in this Exhibit (9).