

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-46297
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No. E0-5073-0007
7. Lease Name or Unit Agreement Name Lady Franklin 25 State
8. Well Number 122H
9. OGRID Number 371449
10. Pool name or Wildcat Winchester; Bone Spring
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3358 GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [X] Gas Well [] Other []
2. Name of Operator Colgate Operating, LLC
3. Address of Operator 300 North Marienfield, Suite 1,000 - Midland, Tx 79701
4. Well Location
Unit Letter: D 1090 feet from the North line and 265 feet from the West line
Section: 25 Township: 19S Range: 28E NMPM County: Eddy

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS [X]
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []
CLOSED-LOOP SYSTEM []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A []
CASING/CEMENT JOB []
OTHER: []

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Based on Colgate Energy's experience in Section 25, will set surface casing at 325' instead of 950' as originally planned. Setting surface at 325' will isolate GW prior to drilling salt section.

Spud Date: []

Rig Release Date: []

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: [Signature]

TITLE: Operations Tech

DATE: 8/3/2020

Type or print name Mikah Thomas
For State Use Only

E-mail address: mthomas@colgateenergy.com

PHONE: 432-695-4272

APPROVED BY: John Garcia
Conditions of Approval (if any):

TITLE Petroleum Specialist

DATE 8/18/2020