Submit 1 Copy To Appropriate District Office <u>District I</u> – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Me Energy, Minerals and Natur OIL CONSERVATION 1220 South St. Fran Santa Fe, NM 87	xico ral Resources DIVISION ccis Dr.	- REC'D 8/5/2020 WELL API NO 30-015-46300 5. Indicate Tyj STATE 6. State Oil & E0-5073-0007	pe of Lease	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name Lady Franklin 25 State		
1. Type of Well: Oil Well 🖾 Gas Well 🗌 Other			8. Well Numb 132H	8. Well Number 132H	
2. Name of Operator			9. OGRID Number		
Colgate Operating, LLC			371449		
3. Address of Operator				10. Pool name or Wildcat	
300 North Marienfeld, Suite 1,000 – Midland, Tx 79701			Winchester; Bone Spring		
4. Well Location					
Unit Letter: <u>D</u> <u>1135</u> feet from the <u>North</u> line and <u>265</u> feet from the <u>West</u> line					
Section: <u>25</u>	Township: <u>19S</u> Ran	ige: <u>28E</u>	NMPM	County: <u>Eddy</u>	
	11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3358 GL				
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
NOTICE OF IN PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING DOWNHOLE COMMINGLE	SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. P AND A CASING/CEMENT JOB I				

OTHER: OTHER: П 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Based on Colgate Energy's experience in Section 25, will set surface casing at 325' instead of 950' as originally planned. Setting surface at 325' will isolate GW prior to drilling salt section.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE:

CLOSED-LOOP SYSTEM

TITLE: Operations Tech

DATE: <u>8/3/2020</u>

Type or print name Mikah Thomas For State Use Only

E-mail address: mthomas@colgateenergy.com

PHONE: <u>432-695-4272</u>

John Garcia APPROVED BY: Conditions of Approval (if any):

TITLE Petroleum Specialist

8/18/2020 DATE