STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

HO. OF COPIES RECEIVES	T	
DISTRIBUTION		
SANTA FE	7	
FILE	7	
U.S.G.S.		
LAND OFFICE		
OPERATOR		

OIL CONSERVATION DIVISION

DISTRIBUTION SANTA FE	P. O. BOX 2 SANTA FE, NEW M		Form C-103 Revised 10-1-78	
FILE]	LXICO 87301	Sa. Indicate Type of Lease	
U.S.G.S.]		State Fee X	
OPERATOR]		5. State Oil & Gas Lease No.	
SUNDE	RY NOTICES AND REPORTS ON WE	LLS		
(DO HOT USE THIS FORM FOR PAUSE "APPLICA"	OPOSALS TO DAILL OR TO DEEPEN OR PLUG BACK FION FOR PERMIT -** (FORM C-10-) FOR SUCH PR	TO A DIFFERENT RESERVOIR,	7. Unit Agreement Name	
OIL GAS X	OTHER-			
2. Name of Operator			8. Farm of Lease Name Blackburn	
HCW Exploration, Inc. 3. Address of Operator			9. Well No.	
P. O. Box 10585	Midland, Texas 7970)2	1	
4. Location of Well D	825 Nonth	1650	10. Field and Pool, or Wildcat Wildcat	
UNIT LETTER B	825 FEET FROM THE North	LINE AND 1650 FEET FRO		
THE East LINE, SECT	10 TOWNSHIP 6-N	RANGE 27-E NMP		
mmmm	15. Elevation (Show whether DF,	RT. GR. etc.)	12. County	
	5049' GR		Quay	
	Appropriate Box To Indicate Natu	re of Notice, Report or C	Other Data	
NOTICE OF I	NTENTION TO:	SUBSEQUE	NT REPORT OF:	
PERFORM REMEDIAL WORK	. PLUG AND ABANDON	EMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON		OMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT	
PULL OR ALTER CASING	CHANGE PLANS CA	OTHER COMMENCE TE-	entry, run prod. 「X	
OTHER		casing and c		
17 Describe Proposed or Completed C	perations (Clearly state all persinent details,	and give pertinent dates, includi	ng estimated date of starting any proposed	
work) SEE RULE 1103.	up pulling unit and reverse		•	
bradenhead. Nippled	up 10" x 3000 psi BOP. Dri	lled cement plug fro	m surface to 10'.	
Ran in hole with 8 3,	/4" bit, 4½" Drill Collars a	and 2 7/8" tubing to	1230'. Drilled	
	D' -]508' for a total of 27 taged in hole circulating ar			
	o'-4770' for a total of 20'			
	running production casing.			
4½", 10.5#, K-55, ST	& C, new and used casing or	12-18-81 as follows		
	ton Auto-fill Float Shoe		1.10'	
l jt. 4½		• ?	42.30	
	ton Auto-fill Float Collar	2	1.10'	
	½" casing sandblasted 4½" casing	45	51.60! 98.90!	
TOTAL CAS		48	05 <u>001</u>	
	pove ground level	_(DE GORBERVALIUM DIVICIO	
· Kally hu	shing to ground level		89.00' SANTA FE	
	anded depth		99.00' RKB	
	(See	Attached Sheet)		
18. I hereby certify that the informatio	n above is true and complete to the best of m	y knowledge and belief.		
X+ 4. 1. 10	tovo Douglas Divis	ion Enginoon	Docombon 21 100	

Cemented with 1975 sx. HLW followed by 400 sx. Class "C" 50:50 Pozmix. Displaced with 78 bbls. fresh water. Plug was down at 7:30 PM 12-18-81. Bumped plug with 1200 psi and then released pressure. Floats held ok. Did not circulate any cement to surface. Present operation is waiting on cement. Plan to commence completion operations 12-21-81 using same pulling unit.