



The Western Company

OIL CONSERVATION DIVISION
SANTA FE

General Offices - Fort Worth, Texas

CEMENTING REPORT

CUSTOMER AND GENERAL INFORMATION

Date: 3-17-83 Field Receipt No.: 618369
Operator: YATES PETROLEUM Lease & Well No.: T-4 CATRE Co. #2
Field: Operator Representative: DELMA MORRIS
Western District: ROSWELL Western Engineer: DAVE MILLER

TYPE JOB AND WELL DATA

Surface ☒ Intermediate ☐ Long String ☐ Liner ☐ Plug ☐ Squeeze ☐ Miscellaneous ☐
Casing Size & Weight: 13^{3/8} 54.50* Depth: Hole Size: 17 1/2 Depth:
Size Tubing: Type Packer: Depth: Casing Perfs:
Excess (calc.): 170 lbs Cement Top (calc.):

CEMENT INFORMATION

Type Cement: CLASS C Amount: 550 Slurry Wt.: 14.8#
Additives: CALCIUM CHLORIDE (2%) Pumping Time:
Type Cement: Amount: Slurry Wt.:
Additives: Pumping Time:
Type Cement: Amount: Slurry Wt.:
Additives: Pumping Time:
Circulating Pressure: Minimum: Maximum:
Plugs-Number & Type: 1- Top RUBBER Down At:
Displacement Fluid: H₂O Bbls.: Wt.: 8.33

TIME	PRESSURE	FLUID PMPD	RATE BMP	REMARKS
12:09	250	10	4.0	H ₂ O AHEAD
12:11	500	130	6.0	SLURRY
12:29	—	—	—	SHOT DOWN
12:31	250	52	6.0	DROP PLUG & DISPLACE WASH & PLUG
12:40	750	2.0	2.0	BUMP PLUG
12:41				FLOAT HEAD

Remarks: PHO 6 CIRCULATE 65 SKS TO PIT.