New Mexico
Institute of Mining and Technology
STATE BUREAU OF MINES
AND
MINERAL RESOURCES
Socorro, New Mexico

WELL LOG DIVISION

CASING-RECORD
Diam. in/Bottom

ELEVATION: 4259 GL

IP: P&A

13-3/8 350 250

LOG NO. 7604

COUNTY: Quay FIELD: Wildcat

COMPANY: Miami Petroleum Co., Inc. LEASE: Hoover Ranch "A" Well No. 1

LOCATION (法): NW NW

SEC., 2. T. 10 N., R. 27 E.

467 feet from the North line and

1980 feet from the West line COMMENCED: May 23, 1959 COMPLETED: June 16, 1959

ABANDONED: June 16, 1959

REMARKS: Rotary tools were used from surface to 6425 feet TOTAL DEPTH.

FORMATION E	BOTTOM, EEET	FORMATION	BOTTOM, FEET
Surface gravel, shale, and lime	1200		
Shale and lime	1855		
Shale and sand	2 38 5		
Lime and shale	27 20		
Shale	3000		
Anhydrite and dolomite	3400		
Red sandy shale and dolomite st	reaks 3780		
Shale and anhydrite	4090		
Granite wash	4315		
Granite wash	4650		
Granite wash	4930		
Granite wash and shale	5200		
Granite wash	<i>5</i> 300		
Shale	5760		
Shale	5904		
Shale and lime	6061		
Dolomite and lime	6165		
Lime and dolomite	6230		
Shale and lime	6348		
Mississippian	6415		
Basement of Mississippian = Tota	al Depth -6425		