

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	<b>X</b>	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

Sept. 25, 1952

(Date)

Tucumcari, N. M.

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Accident &amp; Casualty Co. Of New York, N. Y.

(Company or Operator)

E. L. Kinas

(Lease)

J. R. Watson

(Contractor)

Well No. 1 in the SE 1/4 SE 1/4 of Sec. 11

T. 12N, R. 32E, NMPM, Wildcat Pool, Quay County.

The Dates of this work were as follows: Sept. 13 to Sept. 25, inclusive, 1952

by H. K. Hule, c/o Lyle Adjustment Co. Sta. Fe

Notice of intention to do the work (was) ~~signed~~ submitted ~~on~~ on Sept. 12, 1952, (Cross out incorrect words)and approval of the proposed plan (was) ~~signed~~ obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Moved on Jumbo "C" Ft. Worth spudder Sept. 13 and rigged up completely. Cleaned out cellar. Jarred cement surface plug in 10" casing and pushed same down with tools to \*1650'. Set twenty (20) sacks Portland cement slurry at this depth, leaving plug\*\* at 1650-1620'. Filled interval 1620-0030' with heavy mud. Set surface plug filling interval 30-0' with fifteen (15) sacks Portland cement slurry and set regulation marker in latter. Cleared all junk and levelled premises, per O. G. C. instructions.

RESULTS: \*Well making gas through water in hole.

\*\*Well effectively killed with bottom plug, no additional gas flow evident.

Witnessed by L. V. Rehermeyer

(Name)

himself

(Company)

cementing contractor

(Title)

Approved:

OIL CONSERVATION COMMISSION

Eugene A. Chavez

(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name J. R. Watson

Position Driller-Contractor

Representing Accident &amp; Casualty Co. of N. Y.

Address 610 E. Evans St., Tucumcari, N. M.

Geologist-O. &amp; G. Inspector 9-25-52

(Title)

(Date)