

N. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

**RECEIVED**

**JUL 28 1983**

OIL CONSERVATION DIVISION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-83

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Ortiz	
9. Well No. 1	
10. Field and Pool, or Wildcat Wildcat	
12. County Santa Fe	

**SUNDARY NOTICES AND REPORTS ON WELLS SANTA FE**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER- ☐

2. Name of Operator  
PELTO OIL COMPANY

3. Address of Operator c/o Walsh Engineering & Prod. Corp.  
P. O. Drawer 419 - Farmington, N.M. 87499

4. Location of Well  
UNIT LETTER N 4290 FEET FROM THE North LINE AND 3300 FEET FROM  
West 26 TOWNSHIP 14N RANGE 8E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
5783'GL, 5803'DF, 5804'KB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <u>Complete in Niobrara Formation</u> <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to abandon the Greenhorn completed interval, (Dakota completed interval abandon by cast iron bridge plug set at 7175' with 35 sacks cement on top of bridge plug) in the following manner:

1. Circulate casing with Potassium Chloride water to remove any gas or oil
2. Set cast iron bridge plug at approximately 6600'.
3. Dump 5 sacks cement on top of bridge plug.

It is also proposed to complete in the Niobrara interval (estimated perforation 6236' to 6328') by stimulating the perforated interval.

(Verbal approval received from Carl Ulvog July 22, 1983)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

FOR: PELTO OIL COMPANY  
SIGNED Ewell N. Wapsh, P.E. TITLE President, Walsh Engr. & Production Corp. DATE 7/26/83

APPROVED BY Carl Ulvog TITLE DISTRICT SUPERVISOR DATE 7/28/83

CONDITIONS OF APPROVAL, IF ANY: