

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

JUL 13 1981

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
SANTA FE

3a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Pelto Oil Company	8. Farm or Lease Name Ortiz
3. Address of Operator Two Greenspoint Plaza, Suite 400 16825 Northchase, Houston, Texas 77060	9. Well No. 1
4. Location of Well UNIT LETTER 0, 3450 FEET FROM THE West LINE AND 4290 FEET FROM THE North LINE, SECTION 26 TOWNSHIP 14N RANGE 8E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) KV	12. County Santa Fe

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 8½" Hole to 7450. Schlumberger ran DIL, FDC/CNL, BHC sonic, HR dipmeter. Ran 7" 23# S00 95 Casing and Bot liner hanger, Shoe at 7450, top of liner at 6726. Halliburton cemented 7" liner with 250 sacks 50/50 poz 12# salt, 2% Gel, 8/10% halad 9. Plug down at 0605 hrs 6-6-81 with 1500#. Cleaned out liner and tested top of liner and casing to 2000# 6-7-81. Released Loffland Rig #5.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Carl W. J. [Signature] TITLE Petroleum Consultant DATE 7-10-81

APPROVED BY Carl W. J. [Signature] TITLE SENIOR PETROLEUM GEOLOGIST DATE 7-15-81

CONDITIONS OF APPROVAL, IF ANY: