

DISTRIBUTION		
SANTA FE		
FILE		☒
U.S.G.S.		
LAND OFFICE		
OPERATOR		

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
Pinon Unit	
8. Farm or Lease Name	
9. Well No.	
Pinon Unit No. 2	
10. Field and Pool, or Wildcat	
Wildcat	
12. County	
Santa Fe	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒	GAS WELL ☐	OTHER ☐
Name of Operator		
Chace Oil Company, Inc.		
Address of Operator		
313 Washington, SE, Albuquerque, NM 87108		
Location of Well		
Irr. Section 1583 FEET FROM THE east LINE AND 2583 FEET FROM		
UNIT LETTER south LINE, SECTION 26 TOWNSHIP 14N RANGE 8E NMPM.		

15. Elevation (Show whether DF, RT, GR, etc.)
5798' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
WILL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐	OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

See Well History attached, Day #7 through Day #13.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ED <u>D.W. Miller</u>	TITLE <u>President</u>	DATE <u>July 8, 1985</u>
VED BY <u>Roy Johnson</u>	TITLE <u>DISTRICT SUPERVISOR</u>	DATE <u>7-12-85</u>
DITIONS OF APPROVAL, IF ANY:		

313 Washington S.E.

Albuquerque, New Mexico 87108

Date: 7/1/85Day #: 6 Present operation: drilling Depth today: 2460'24 hour footage: 314' Formation: not givenDrill Collars: No: 18 Size: 5 7/8" Weight: 43,000# Bore: 2 1/4"Rotary: RPM: 70 Weight on bit: 20 Present drilling rate: 22'/hourPump: Liner size: 5 1/2" Pressure: 1,000# Strokes per minute: 55Mud: Vis: 34 Wt.: 9.0 W. L.: 9.0Mud additives last 24 hours: 50 gel, 1 1/2 soda ash, 3 caustic soda, 8 starch,
1 preservative, 4 ICM.Deviation survey: 1° @ 2181'; 3/4° @ 2274'; 1/2° @ 2367'; 3/4° @ 2458'Bit: #4: 7 7/8", V537; 687', 47 3/4 hoursBreak down: 1 3/4 hours rig service and surveys22 1/4 hours drillingDate: 7/2/85Day #: 7 Present operation: drilling Depth today: 2810'24 hour footage: 350' Formation: sand and shaleDrill Collars: No: 18 Size: 5 7/8" Weight: 43,000# Bore: 2 1/4"Rotary: RPM: 70 Weight on bit: 25,000# Present drilling rate: 15'/hourPump: Liner size: 5 1/2" Pressure: 1,000 Strokes per minute: 55Mud: Vis: 35 Wt.: 9 W. L.: 8.5Mud additives last 24 hours: 55 gel, 1 1/2 soda ash, 1 caustic soda, 9 starch,
1 preservativeDeviation survey: 3/4° @ 2579'; 3/4° @ 2671'; 3/4° @ 2762'Bit: #4: 7 7/8", V537; 878', 56 1/4 hours; #5: 7 7/8", V527; 259', 7 hoursBreak down: 2 hours surveys CORRECTION: 1/4 hours rig service
1/4 hour rig service 2 hours survey
21 3/4 hours drilling 17 3/4 hours drlg
1 hour rig repair
3 hours bit tripDate: 7/3/85Day #: 8 Present operation: Drilling Depth today: 3155'24 hour footage: 345' Formation: not givenDrill Collars: No: 18 Size: 5 7/8" Weight: 43,000# Bore: 2 1/4"Rotary: RPM: 70 Weight on bit: 20 Present drilling rate: 15'/hourPump: Liner size: 5 1/2" Pressure: 1,000 Strokes per minute: 55Mud: Vis: 35 Wt.: 1.0 W. L.: 8.2Mud additives last 24 hours: not givenDeviation survey: 1 1/4° @ 2884'; 1° @ 2944'; 1 1/2° @ 3037'; 1 3/4° @ 3129'Bit: #5: 7 7/8", V527; 506', 28 3/4 hoursBreak down: 1/4 hour rig service2 hours surveys21 3/4 hours drlg

Date: 7/4/85Day # 9 . Present operation: drilling . Depth today: 3357'24 hour footage: 202' . Formation: sand and shaleDrill Collars: No: 18 Size: 5 7/8 Weight: 43,000# Bore: 2 1/4"Rotary: RPM: 70 Weight on bit: 10,000# Present drilling rate: 8'/hourPump: Liner size: 5 1/2" Pressure: 1,000# Strokes per minute: 53Mud: Vis: 34 Wt.: 8.8 W. L.: 8.6Mud additives last 24 hours: not givenDeviation survey: 1 3/4° @ 3322'; 2 1/4° @ 3315'; 2 1/4° @ 3318'Bit: #5: 7 7/8", V527; 667', 42 hours - #6: 7 7/8", V537; 39', 5 hoursBreak down: 1/4 hour rig service1 hour surveys1 hour rig repair3 1/2 hours trip18 1/4 hours drillingDate: 7/5/85Day #: 10 Present operation: drilling Depth today: 3597'24 hour footage: 240' Formation: sand and shaleDrill Collars: No: 18 Size: 5 7/8" Weight: 43,000# Bore: 2 1/4"Rotary: RPM: 70 Weight on bit: 10 Present drilling rate: 8'/hourPump: Liner size: 5 1/2" Pressure: 1,000# Strokes per minute: 52Mud: Vis: 35 Wt.: 8.9 W. L.: 8.2Mud additives last 24 hours: not givenDeviation survey: 1 3/4° @ 3407'; 2 1/4° @ 3469'; 2° @ 3531'Bit: #6: 7 7/8", V537; 279', 26 1/2 hoursBreak down: 1/4 hour rig service2 1/4 hours surveys21 1/2 hours drillingDate: 7/6/85Day #: 11 Present operation: drilling Depth today: 3780'24 hour footage: 183 Formation: sand and shaleDrill Collars: No: 18 Size: 5 7/8" Weight: 43,000# Bore: 2 1/4"Rotary: RPM: 70 Weight on bit: 10,000# Present drilling rate: 6'/hourPump: Liner size: 5 1/2" Pressure: 1,000# Strokes per minute: 52Mud: Vis: 36 Wt.: 8.9 W. L.: 8.8Mud additives last 24 hours: none givenDeviation survey: 2 1/4° @ 3624'; 2° @ 3648'; 1 3/4° @ 3687'Bit: #6: 7 7/8", V537; 462', 49 hoursBreak down: 1/2 hour rig service and survey1 surveys22 1/2 hours drilling

Date: 7/7/85Day # 12 . Present operation: drilling . Depth today: 3970'24 hour footage: 190' . Formation: sand and shaleDrill Collars: No: 18 Size: 5 7/8" Weight: 43,000# Bore: 2 1/4"Rotary: RPM: 70 Weight on bit: 8,000# Present drilling rate: 4'/hourPump: Liner size: 5 1/2" Pressure: 1,000# Strokes per minute: 54Mud: Vis: 35 Wt.: 8.8 W. L.: 8.0Mud additives last 24 hours: not givenDeviation survey: 2° @ 3810'; 2 1/4° @ 3935'; 2 1/4° @ 3972'Bit: #6: 7 7/8", V537; 492', 51 hours; #7: 7 7/8", V537; 160', 17 hoursBreak down: 4 hours survey and trip1 hour surveys19 hours drillingDate: 7/8/85Day #: 13 Present operation: drilling Depth today: 4140'24 hour footage: 170' Formation: sand and shaleDrill Collars: No: 18 Size: 5 7/8" Weight: 43,000# Bore: 2 1/4"Rotary: RPM: 70 Weight on bit: 15,000# Present drilling rate: 8'/hourPump: Liner size: 5 1/2" Pressure: 1,000# Strokes per minute: 54Mud: Vis: 38 Wt.: 8.7 W. L.: 8.8Mud additives last 24 hours: not givenDeviation survey: 2° @ 3997'; 1 3/4° @ 4059'; 1 3/4° @ 4122'Bit: #7: 7 7/8", V537; 330', 39 1/2 hourBreak down: 1/2 hour rig service survey1 hour survey22 1/2 hours drilling

Date: _____

Day #: _____ Present operation: _____ Depth today: _____

24 hour footage: _____ Formation: _____

Drill Collars: No: _____ Size: _____ Weight: _____ Bore: _____

Rotary: RPM: _____ Weight on bit: _____ Present drilling rate: _____

Pump: Liner size: _____ Pressure: _____ Strokes per minute: _____

Mud: Vis: _____ Wt.: _____ W. L.: _____

Mud additives last 24 hours: _____

Deviation survey: _____

Bit: _____

Break down: _____