Form 3160-5 (November 1983) (Formerly

UNITED STATES

SUBMIT IN TRIPLICATES
(Other instructions on re-

oum approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

D SERIAL NO.

9-331) DEPARTMENT OF THE INTERIOR verse alde) BUREAU OF LAND MANAGEMENT	NM 23599
SUNDRY NOTICES AND REPORTS ON WELLS o not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such property FILE TO THE PROPERTY OF T	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GT GAS	7. UNIT AGREEMENT NAME

SUNDRY NOTICES AND REPORT OF THE SUNDRY NOTICES AND REPORT OF THE SURE CONTROL OF THE	or plug back to a different reservoir.		
		7. UNIT AGREEMENT NA.	ME
OIL X GAS OTHER	1001 4 7 4000	La Mesa Unit	
. NAME OF OPERATOR	JAN 1 5 1986	8. FARM OR LEASE NAM	E
Yates Petroleum Corporation			
3. ADDRESS OF OPERATOR	BUREAU OF LAND MANAGEMENT	9. WELL NO.	
207 South 4th St., Artesia, NM 88210	FARMINGTON RESOURCE AREA	3	
:. LOCATION OF WELL (Report location clearly and in accordance See also space 17 below.) At surface	with any State requirements.*	10. FIELD AND POOL, OF Wildcat	WILDCAT
330 FNL & 330 FEL, Sec. 13-T1	5N-R8E	11. SEC., T., E., M., OR B SURVEY OR AREA	LX. AND
		Unit A, Sec.	13-15N-8E
14. PERMIT NO. 15. ELEVATIONS (Show w	whether DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE
6320' GR		Santa Fe	NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOT	ICE OF INTE	ENTION TO:		BUB	SEQUENT REP	ORT OF:	
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	X	REPAIRING WELL	
PRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT		ALTERING CASING	
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING		ABANDONMENT*	
REPAIR WELL		CHANGE PLANS		(Other)			
(Other)				Completion or Elec-	ompletion Re	ple completion on Well port and Log form.)	·

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and gones pertinent to this work.)*

Reamed hole to 17-1/2" and resumed drilling with rotary tools at 6:00 PM 1-9-86. Notified Dan Ross with BLM.

Ran 9 joints 13-3/8" 61# K-55 ST&C casing set 374'. 1-Texas Pattern guide shoe set 374'. Insert float set 334'. Cemented w/450 sx Class "C" with 2% CaCl2, 594 cubic feet. Compressive strength of cement - 1250 psi in 12 hrs. PD 7:30 PM 1-10-86. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 60 sx to pit. WOC. Drilled out 10:45 PM 1-11-86. WOC 27 hrs and 15 min. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the foregoing is true and correct	TITLE Production Supervisor	DATE 1-13-86
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE
CONDITIONS OF AFFROVAL, IF ANY.		