

Form 5-331
(May 1962)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved
Budget Bureau No. 43-R-1434

5. LEASE DESIGNATION AND SERIAL NO.

NM 23259

6. IF INDIAN, ALLOTTEE OR TRUST NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

REEVES BROS. PETR. "A", LTD.

9. WELL NO.

Morrison Federal #1

10. FIELD AND FURN. OR WILDCAT

wildcat

11. SEC., T., R., N., OR BLK. AND
SECT. OR AREA

Sec. 22, T4S, R6E

12. COUNTY OR PARISH 13. STATE

Socorro

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Reeves Bros. Petroleum "A" Ltd.

3. ADDRESS OF OPERATOR

2701 Second St. N.W. Albuquerque, NM 87107 D. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL and 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether SP, HY, OR, etc.)

5781 Ground Level

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DANGEROUS PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Drilled to total depth of 2937' with a 7 7/8" diameter bit. Abandoned. Plugged
back from 2800' to 2700' with 35 sacks cement. Halliburton pumped another 35
sacks cement from 1225' to 1126' fifty feet into the 8 5/8"... Shot 8 5/8" pipe off
at 710'. 12 3/4" was left in hole. Turned well over to Hattie Lacy to be
completed as a water well. Welded cap on 12 3/4" casing.

RECEIVED

DEC 15 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

SEP 2 - 1977

R. L. ECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side