ATTROVED BY----

CONDITIONS OF AFFROVAL, IF ANY:

			,	****
Submit 3 Copies to Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources Department		Form C-103 Revised 1-1-89	
DISTRICT I F.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION 2040 Pacheco St.		WELL API NO. 30-053-20011	
DISTRICT II P.O. Drawer DD, Arasia, NM 88210 Santa Fe, 87505		5. Indicate Type of Lesse		
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410			6. State Oil & Gas Lease No.	TEE X
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL, OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				
			7. Lease Name or Unit Agreer	ment Name
I. Type of Well:				
2. Name of Operator			8. Well No.	HA
Davis Petroleum Corp. 3. Address of Operator			9. Pool name or Wildon	
1360 Post Oak Blvd., Suite 2400 Houston, Texas 77056			Santa Fe Gr	oup
4. Well Location Unit Letter N : 800	Feet From The South	Line and 171	6 Fast From The We	st Line
Out peace	Total total tile			- Laur
Section 19	Towaship 4N Ra	inge 1E	NMPM Socorro	County
4844' GL 4856' KB				
11. Check	Appropriate Box to Indicate I		eport, or Other Data	
NOTICE OF INT	ENTION TO:	SUB	SEQUENT REPORT	OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING	CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPNS. X PLUG AND ABANDONMENT		
PULL OR ALTER CASING		CASING TEST AND CEMENT JOB X		
OTHER:		OTHER:		
12. Describe Proposed or Completed Operat work) SEE RULE 1103.	ions (Clearly state all pertinent details, an	d give pertinent dates, includ	ling estimated date of starting any	ı proposed
Commenced drilli	ng 17 1/2" hole @ 6:30 /	AM 3/2/96. Drill	ed to 123' KB. Set	: 13 3/8°
csg. 0 1231 KB for conduc	ctor. Cemented same w/	113 sx Class G +	· 3% CC. Cement cir	culated.
Drilled 12 1/4" hole to :	1026 KB. Set 9 5/8" cs	g. @1022' KB. Ce	mented same w/ 320	sx 65/35
Poz and 100 sx Class G +	2% CC. Cement circulate	ed. Performed to	p <mark>outside job down</mark>	1" pipe
at 40° with 43 sx Class (+ 3% CC. WOC and NU 20	0 1/4 hrs. Teste	d casing to 500psi	g surface
pressure for 30 minutes. Held okay.				
•				
I hereby certify that the information above to true	and compariso if the best of my knowledge and t	perior.		
SIONATURE	Shot m	Aqent	DATE	3/4/96
TYPEORIPADIT NAME Cecil D. G	ritz F		1817) _{n 57} 9-8260
(This space for State Use)			WEATHER TO THE TOTAL PROPERTY OF THE TOTAL P	

-- #ITT ---

DATE ___