

NO. OF COPIES RECEIVED

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease

State ☐Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <u>Dry hole</u>		7. Unit Agreement Name	
2. Name of Operator <u>Houston Oil and Minerals Corporation</u>		8. Farm or Lease Name <u>Berkshire Ranch</u>	
3. Address of Operator <u>1700 Broadway - Suite 504, Denver, Colorado 80202</u>		9. Well No. <u>Berkshire Ranch No. 1</u>	
4. Location of Well UNIT LETTER <u>K</u> , <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>29</u> TOWNSHIP <u>6 North</u> RANGE <u>9 East</u> NMPM.		10. Field and Pool, or Wildcat <u>Wildcat</u>	
15. Elevation (Show whether DF, RT, GR, etc.) <u>GLE 6095'</u>		12. County <u>Torrance</u>	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐TEMPORARILY ABANDON ☐PULL OR ALTER CASING ☐PLUG AND ABANDON ☐CHANGE PLANS ☐OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐COMMENCE DRILLING OPNS. ☐CASING TEST AND CEMENT JOBS ☐OTHER ☐ALTERING CASING ☐PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Obtained verbal permission to plug and abandon at 8:30 p.m., October 14, 1976, from Mr. Carl Ulvog of the Santa Fe office of the New Mexico Oil and Gas Commission. Verbal orders and actual plug and abandon operations were conducted as follows:

Five cement plugs (Class "B") set at the following depths:

2660-2671' (10 sx.)

1740-1800' (20 sx.)

940-1000' (20 sx.)

310-410' (30 sx.)

0-10' (10 sx.)

Spotted plugs with low solids gel/chem mud (9.0 lb/gal.) and finished with surface plug at 9:30 a.m., October 15, 1976. Dry hole marker installed.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ronald D. Scott TITLE District drilling engineer DATE October 21, 1976

APPROVED BY Carl Ulvog TITLE SENIOR PETROLEUM GEOLOGIST DATE August 8, 1977

CONDITIONS OF APPROVAL, IF ANY: