



STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT
OIL CONSERVATION DIVISION

TONEY ANAYA
GOVERNOR

October 17, 1986

POST OFFICE BOX 2088
STATE LAND OFFICE BUILDING
SANTA FE, NEW MEXICO 87501
(505) 827-5800

Mr. John A. Aday
Rt. 1, Box 28
Estancia, New Mexico 87016

Re: D'Spain Well No. 2
C-12-6N-6E
Torrance County, New Mexico

Dear Mr. Aday:

It is this office's understanding that the above-referenced well was originally drilled as a water well and that your past operations have deepened this well to test for oil and gas potential. Your Sundry Notice has indicated that the well was deepened 555 feet, 4 1/2-inch casing was set at 1264 feet and a cement plug was set at 1280 feet. The minimum plugging requirement on this well would therefore consist of placing 40 sacks of cement at the top of your existing cement plug at 1280 feet. This 40-sack plug would then fill the open hole section (1269'-1280') and bring the cement up into the 4 1/2' casing. This operation may be done by running tubing and pumping cement or by using a dump bailer.

The enclosed forms will need to be filled out completely in order to close out this well file. Should you have any questions, please contact me at this office.

Sincerely,

ROY E. JOHNSON,
Sr. Petroleum Geologist

REJ/dr