

N.

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

12091

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

J. P. Stewart

Harry Lammons

Well No. 1 Company or Operator in N.M.P.M. of Sec. 3 Lease 3

R. 12 E, N. M. P. M., Wild Cat Field, Torrance County.

Well is 1300 feet south of the North line and 1300 feet west of the East line of N.W. 1/4 S-3-T 3N R-12-E

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Harry Lammons, Address Ft. Sumner, New Mex

If Government land the permittee is, Address

The Lessee is J. P. Stewart, Address Paducah, Texas

Drilling commenced June 6, 1940, Drilling was completed October 15, 1943

Name of drilling contractor L. V. Fitzwater, Address Wichita Falls, Texas

Elevation above sea level at top of casing 9 feet.

The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from None to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 240 to 263 feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
3 1/2	20	Std	?	419-8"	Std	No	No		No

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	SACKS OF CEMENT	METHOD USED	MUD GRAV.	AMOUNT OF MUD USED
10	8 1/2	426	20	Pump		

## PLUGS AND ADAPTERS

Heaving plug—Material None Length Depth Set

Adapters—Material None Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
None						

Results of shooting or chemical treatment

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet.

Cable tools were used from Tap feet to T D 767' feet, and from feet to feet.

## PRODUCTION

Put to producing 19

The production of the first 24 hours was barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

## EMPLOYEES

L. V. Fitzwater, Driller

Floyd Hiskett, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 30

day of April 1945

Alice L Childers  
Notary Public

My Commission expires Dec 20, 1947

Holts NM 4/30/45  
Place Date

Name J P Stewart

Position owner

Representing self

Company or Operator.

Address 659 E Rose Ave

Bill Lower Corp

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
Surface	to 25 ft	25 ft	Glechia
25	66	41	Lime shells
66	76	10	Sharp Brown Sand
76	85	9	White Lime
85	116	31	Red Shale
116	126	10	Granite Wash
126	166	60	Red Beds
166	173	17	Granite Wash
173	190	27	Red Beds
190	228	38	Grey Sand & Lime
228	230	2	Lime
230	234	14	Granite
234	241	7	Sharp Sand & Lime
241	259	22	" " "
259	263	4	" " "
263	273	10	40' fresh water in hole
273	292	19	Sand & Lime
292	300	8	Sand & Lime (Hard)
300	380	80	Red Beds or Clay
380	408	28	Sand & Lime (Hard)
408	412	4	Green Shale (quartz)
412	414	2	Ghst & Lime
414	426	12	" "
			Set 419' 8" of 8 1/2 IN. Pipe with 20 Sacks encore Cement
426	428	2	Granite Wash
428	478	5	Sandy Quartz
478	487	9	Sand & Lime
487	501	14	Green Shale
501	541	40	Sandy quartz & Lime
541	657	116	Sandy quartz & Lime
657	703	46	chist & Quartz
703	714	11	Quartz
714	767	53	Granite or Malpine
	Corrected S L M	-	745 ft. T. D.
	Tools Lost		in Hole and Abandoned.