## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## **MISCELLANEOUS NOTICES**

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

		Indicate Nature of Notice by Check	ing Below
otice of Intention o Change Plans		Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper
OTICE OF INTENTION O PLUG WELL	x	Notice of Intention to Plug Back	Notice of Intention to Set Liner
otice of Intention o Squeeze		Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)
otice of Intention OGUN Perforate	and the second s	Notice of Intention (Other)	Notice of Intention (Other)
IL CONSERVATION COM ANTA FE, NEW MEXICO	MISSION	Albuquerque, N.M.	August 30, 1955
entlemen :		(Face)	(Date)
			Overmier & Cacy
W. L. C	acy		Well No. 1 in (Unit)
SE 1/4 NE 1/4 of (40-acre Subdivision)	Sec23	L <i>ease</i> , T <b>6N</b> , R <b>5K</b> ,N	MPM., Wildcat
Torrence	Cou	nty.	
December 20, 1954.	(FOLLOW) of 8 5/8 Then ab	L DETAILS OF PROPOSED PL INSTRUCTIONS IN THE RULES By surface casing @ 60° wi bout February 4, 1955 set	AND REGULATIONS)  Ath 30 sacks cement about  A85 of A line pine 2
485† with 65 sacks Acidized open hole bradenhead to surf  Propose to plug we cement into 4" pip	of 8 5/8 Then ab Total with 100 ace. Rem	INSTRUCTIONS IN THE RULES  By surface casing @ 60° without February 4, 1955 set depth of 575°. Plugged to gallons. 4" pipe faile mainder of samples will be outring 10 sacks cement in	AND REGULATIONS)  AND REGULATIONS)  AND REGULATIONS)  AND REGULATIONS  AND
Acidized open hole bradenhead to surf  Propose to plug we cement into 4" pip 4" marker 4' above	of 8 5/8 Then ab Total with 100 ace. Rem	Instructions in the rules  By surface casing @ 60' without February 4, 1955 set depth of 575'. Plugged to By gallons. 4" pipe faile By gallons. 4" pipe faile By gallons will be By tring 10 sacks cement in Spot 10 sacks cement plug By sevel and abandon well.	AND REGULATIONS)  At 30 sacks cement about 485' of 4" line pipe 6 back with cement to 520'.  At 6 100'. Squeezed in  a furnished to the Commission.  Bottom of hole to bring at top of well. Place usual
Propose to plug we cement into 4" pip 4" marker 4' above	of 8 5/8 Then ab Total with 100 ace. Rem Il by spo Then ground 1	INSTRUCTIONS IN THE RULES  By surface casing @ 60' with the surface casing with the surface casing a surface casing a surface casing with the surface casing with	AND REGULATIONS)  AND REGULATIONS  AND REGULATIO
Propose to plug we cement into 4" pip 4" marker 4' above	of 8 5/8 Then ab Total with 100 ace. Rem Il by spo Then ground 1	INSTRUCTIONS IN THE RULES  By surface casing @ 60' with the surface casing with the surface casing a surface casing a surface casing with the surface casing with	AND REGULATIONS)  AND REGULATIONS  AND REGULATI

Albuquerque, New Mexico