

AREA 640 ACRES
LOCATE WELL CORRECTLYNEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

F. E. Gilbreath & E. D. Spears Burch Hotel, Breckenridge, Texas
Company or Operator Address
Berkshire Bros. et al Well No. 2 in N.E. of N.W. 1/4 Sec. 19, T. 6 N
Lease
R. 9 E, N. M. P. M., Wildcat Field, Torrence County.
Well is 660 feet south of the North line and 660 feet west of the East line of N.W. 1/4 Sec. 19
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Berkshire Bros. Address Estancia, New Mexico
If Government land the permittee is Address
The Lessee is Lloyd Croslin Address Lubbock, Texas
Drilling commenced 11 - 21 19 50 Drilling was completed 12 - 8 19 50
Name of drilling contractor Wasson Oil Company Address Big Spring, Texas
Elevation above sea level at top of casing 6102 feet.
The information given is to be kept confidential until May be released now 19

OIL SANDS OR ZONES

No. 1, from None to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 28 to 310 feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10 1/2"	40#	8	Nat'l	329'	Bottom	slightly beveled and cemented with 129 sacks of cement from top to bottom.			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
8-3/4	None					

PLUGS AND ADAPTERS

Heaving plug—Material Wood Length 8 Ft. Depth Set 15 Ft.
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		None				

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS NONE

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours. Gallons gasoline per 1,000 cu. ft. of gas.
Rock pressure, lbs. per sq. in.

EMPLOYEES

Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 11th day of December 19 50
Breckenridge, Texas 12/11/50
Name F. E. Gilbreath
Position Field Supt.
Representing F. E. Gilbreath & E. D. Spears
Company or Operator
Address Burch Hotel, Breckenridge, Texas
My Commission expires June 1951
LOUISE ATHEY
Notary Public, Stephens Co. Tex.
Notary Public

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
Surface	28	28	Clay
28	34	6	Clay & gravel
34	160	126	Sand & gravel
160	175	15	Sandy red shale
175	220	45	Sand
220	310	90	Sand, gravel with shale streaks
310	327	17	Sticky red shale
327	329	2	Lime
329	331	2	Red shale Set surface pipe at 329'
331	385	54	Sandy shale with lime streaks
385	410	25	Lime
410	490	80	Lime shells
490	505	15	Red shale
505	760	255	Red bed
760	840	80	Lime sandy
840	1200	360	Red shale
1200	1236	36	Red shale
1236	1260	24	Lime
1260	1300	40	Sandy red shale
1300	1305	5	White lime
1305	1420	115	Red bed
1420	1430	10	Lime hard
1430	1475	45	Red shale
1475	1500	25	Lime
1500	1600 1605	105	Red Bed
1605	1660	55	Lime
1660	1715	55	Lime shells & red shale
1715	1740	25	Lime
1740	1790	50	Red shale Bentonite & Gyp
1790	1850 1840	50	Lime
1840	1880	40	Red bed
1880	1900	20	Hard Lime
1900	1980	80	Red shale
1980	2480	500	Lime
2480	2615	135	Lime porous
2615	2620	5	Lime very hard
2620	2640	20	Lime dolomitic
	2640	Total Depth	